



CORNING

UniCam® Connector Standard-Performance

Installation Toolkit Basic, LC, SC, ST® compatible

Contents [[hide](#)]

[1 TKT-UNICAM Connector Standard Performance](#)

[2 Features and Benefits](#)

[3 Specifications](#)

[4 Documents / Resources](#)

[4.1 References](#)

TKT-UNICAM Connector Standard Performance

Part Number:

TKT-UNICAM

The standard UniCam® connector installation tool kit (TKTUNICAM) is a basic installation tool kit used to terminate all UniCam connector styles (SC, LC and ST compatible connectors).

UniCam high-performance multimode connectors (SC, LC and ST compatible) can achieve their optical specifications with the use of this kit. A convenient carrying bag is provided with all the components necessary to terminate UniCam connectors.

The TKT-UNICAM can also be upgraded with a visual fault locator (VFL-350) that provides a visual feedback feature when terminating connectors. The installer can watch an amber glow in the back of the connector to dim or disappear indicating proper mating of the field fiber to fiber stub within the connector. This is very useful for training new installers and reducing scrap rates.

Features and Benefits

Terminates single-mode and multimode fibers

Various installation options

Convenient carrying case

Minimizes setup and teardown time



Specifications

General Specifications

Product Type	Connector Tools and Toolkits
Compatibility	LC, SC and ST® compatible
Technology	No-Epoxy/No-Polish

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	Passed EIA/TIA 568-B.3

Dimensions

Height	24.13 cm
Width	12.7 cm
Depth	34.5 cm
Weight	2.3 kg

Ordering Information

Product Number	TKT-UNICAM
EAN Code	4.04267E+12
Package Contents	UniCam® Installation Tool, Cleaver, Continuity Test Set (CTS) Installation Tool, CTS Adapters, SC UPC/ST® compatible UPC Jumper, LC UPC/ST Compatible UPC Jumper, Gauge Card, Fiber Preparation Tools, Fiber Cleaning Tools
Units per Delivery	1-Jan
Shipping Height	241.3 cm
Shipping Width	127 cm
Shipping Depth	345 cm



Corning Optical Communications LLC

4200 Corning Place

Charlotte, NC 28216

United States [800-743-2675](tel:800-743-2675)

FAX: [828-325-5060](tel:828-325-5060)

International: +1-[828-901-5000](tel:828-901-5000)

www.corning.com/opcomm


A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks.

All other trademarks are the properties of their respective owners.

Corning Optical Communications is ISO 9001 certified.

© 2025 Corning Optical Communications.
All rights reserved.

Documents / Resources

	<p>Corning TKT-UNICAM Connector Standard Performance [pdf] Installation Guide</p> <p>TKT-UNICAM, TKT-UNICAM Connector Standard Performance, TKT-UNICAM, Connector Standard Performance, Standard Performance, Performance</p>
---	---

References

- [User Manual](#)

Corning

Connector Standard Performance, Corning, PERFORMANCE, Standard Performance, TKT-UNICAM, TKT-UNICAM Connector Standard Performance

Leave a comment

Your email address will not be published. Required fields are marked *

Comment *

Name

Email

Website

☐ Save my name, email, and website in this browser for the next time I comment.

Post Comment

Search:

e.g. whirlpool wrf535swhz

Search

[Manuals+](#) | [Upload](#) | [Deep Search](#) | [Privacy Policy](#) | [@manuals.plus](#) | [YouTube](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.