Home » cpac System » cpac System SID2M HMI Controller Instructions



cpac System SID2M HMI Controller Instructions





Contents

- 1 Additional Type Approval information and Safety Precautions/Warnings! Legal Statements for SID 2.0, SID 2.0M and SID 2.0MLTE.
- 2 Documents / Resources
 - 2.1 References
- **3 Related Posts**

Additional Type Approval information and Safety Precautions/Warnings! Legal Statements for SID 2.0, SID 2.0M and SID 2.0MLTE.

This document contains

- Additional Type Approval information such as type approval symbols, numbers and texts for the SID 2.0 unit required by national authorities and where this information is not found on the device itself due to limited space.
- Legal Statements and Safety Precautions/Warnings for the SID 2.0 unit required by national authorities.

Country/ Region	Additional Type Approval Information – Statement s/Precautions/Warning
Canada	Contains IC: 10224A-201903EG25G
	This device complies with Part 15 of the FCC Rules an d with RSS-210 and RSS-247 of Industry Canada. Op eration is subject to the following two conditions. (1) this device may not cause harmful interference, an d (2) this device must accept any interference received, including interference that may cause undesired oper ation. t.
	NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:
	 Reorient or relocate the receiving antenna. Increase the separation between the equipment an d receiver. Connect the equipment into an outlet on a circuit different from that to which the receiver is connected. Consult the dealer or an experienced radio/TV tech nician for help.
	FC Contains FCC ID: XMR201903EG25G

USA

This device complies with Part 15 of the FCC Rules an d with RSS-210 and RSS-247 of Industry Canada. Op eration is subject to the following two conditions. (1) th is device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

- NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection agai nst harmful interference in a residential installation. This equipment generates, uses and can radiate ra dio frequency energy and, if not installed and used i n accordance with the instructions, may cause har mful interference to radio communications. Howeve r, there is no guarantee that interference will not occ ur in a particular installation. If this equipment does cause harmful interference to radio or television rec eption, which can be determined by turning the equi pment off and on, the user is encouraged to try to c orrect the interference by one or more of the followi ng measures:
- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment an d receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV tech nician for help.

NOTICE: Changes or modifications made to this equip ment not expressly approved by (manufacturer name) may void the FCC authorization to operate this equipm ent.

Radio frequency radiation exposure Information: This equipment complies with FCC radiation exposure limit s set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20 cm between the radiator and your body. This transmitter should not be co-located or operating in conjunction with any other antenna or transmitter.

Japan	Device approval numbers R: 202-JKM116 T: D23-002 8 202 LTE module: Quested EG25-G Approval number JATE : AD 19 0040 201 / 00 Approval number TELEC: 201-1 90133 / 00
Europe	WLAN: This device may be operated at 2412-2472 M Hz, 5150-5350 MHz and 5470-5725 MHz.

Documents / Resources



cpac System SID2M HMI Controller [pdf] Instructions
AHV-SID2M, AHVSID2M, SID2M, SID2M HMI Controller, HMI Controller, Controller

References

• User Manual

Manuals+, Privacy Policy