


Devantech ESP32LR42 WiFi 4 x 16A Relays Module User Manual

[Home](#) » [Devantech](#) » Devantech ESP32LR42 WiFi 4 x 16A Relays Module User Manual 

Contents

- 1 Devantech ESP32LR42 WiFi 4 x 16A Relays Module
- 2 ESP32LR42 Changes from v1.5 to v1.6
- 3 Overview
 - 3.1 Control Protocols
- 4 USB Configuration Commands
 - 4.1 ST Status. Return the system status
 - 4.2 RB ReBoot
 - 4.3 HTML Commands
 - 4.4 Webpage
 - 4.5 Schematics
 - 4.6 Power Supply
 - 4.7 PCB dimensions
 - 4.8 Appendix 1
- 5 Documents / Resources
 - 5.1 References
- 6 Related Posts



Devantech ESP32LR42 WiFi 4 x 16A Relays Module

ESP32LR42
Changes from v1.5 to v1.6

Setup commands MU and MW were added to provide an MQTT username and password.

Overview

The ESP32LR42 is a WIFI connected relay module using the popular ESP32.

It provides 4 relays capable switching up to 16Amps and 2 digital inputs with pull-ups than can interface directly with volt free contacts. The normally open relay contacts have snubbers fitted across them, and can drive inductive loads such as contactors and solenoids.

Power for the board is 12v dc, which can be provided by a standard universal wall power supply. A 1A or greater supply should be selected.

Control Protocols

1. Simple plain text commands sent to the module.
2. HTML commands
3. MQTT
4. A built in webpage

WIFI

The ESP32LR42 connects via 2.4GHz WIFI to your network. Therefore it must be located in a position where it gets a good WIFI signal. The module should not be enclosed in a metal box/cabinet as this will shield the WIFI signal.

You can check the signal level by looking at the RSSI figure which is reported by the ST (Status) command.

Configuration

The ESP32LR42 is configured by connecting a USB cable to your PC and running a terminal program. PuTTY is a good option if you don't have any other preferences.

The serial port should be set to 115200 baud, 8 bit, 1 stop, no parity, no flow control.

USB Configuration Commands

ST Status. Return the system status

Status:

Firmware Version: 1.2

IP: 0.0.0.0 (192.168.0.30)

Subnet: 0.0.0.0

Gateway: 0.0.0.0

Primary DNS: 0.0.0.0

Secondary DNS: 0.0.0.0

SSID: *****

Password: *****

ASCII TCP Port: 17123

RSSI: -66

MQTT Server: 192.168.0.115

MQTT Port: 1883

MQTT ID: ESP32LR42

MQTT User: myUsername

MQTT Password: *****

Relay1 Topic: R1Topic

Relay2 Topic: R2Topic

Relay3 Topic: R3Topic

Relay4 Topic: R4Topic

Input1 Topic: Input1Topic

Input2 Topic: Input2Topic

When the IP address is set to 0.0.0.0 this means that the IP address is being provided by your networks DHCP server. In that case the assigned IP address is also provided, as above.

When the SSID and Password are setup, they will be displayed until the next reset, After that they will only show as *****.

RB ReBoot

This will restart the module. It may produce a lot of random characters as the ESP32's boot logging runs at a different baud rate. If it succeeds in connecting to your network it will report the IP address.

Re-Bootting.. .

#####XL###C#####5)#####iafb##### #*U Y##### #i#U5 Q#####

WiFi connected.

IP address:

192.168.0.6

IP Sets the modules IP address

Enter IP followed by the required IP address. Entering address 0.0.0.0 means the IP will be obtained from your networks DHCP server. The new IP address will take effect after the next re-boot.

IP "192.168.0.123"

OK. Saved IP Address: 192.168.0.123

SB Sets the SuBnet mask

SB "255.255.255.0"

OK. Saved Subnet Mask: 255.255.255.0

GW Sets the GateWay address

This is normally the IP address of your router.

GW "192.168.0.1"

OK. Saved Gateway Address: 192.168.0.1

PD Sets the Primary DNS

The can be the IP address of your router which will then use your ISP provided DNS. You can also specify the DNS such as 8.8.8.8 for Googles DNS server.

PD "192.168.0.1"

OK. Saved Primary DNS: 192.168.0.1

SD Sets the Secondary DNS

The can be the IP address of your router which will then use your ISP provided DNS. You can also specify the DNS such as 8.8.4.4 for Googles DNS server.

SD "8.8.4.4"

OK. Saved Secondary DNS: 8.8.4.4

SS This sets the SSID

The SSID is the public name of your WIFI network Enter your WIFI's SSID here.

SS "Devantech"

OK. Saved SSID: Devantech

PW Sets your networks WIFI password

PW "Kj~kCZUV*UGA6SG~"

OK. Saved Password: Kj~kCZUV*UGA6SG~

PA Sets the TCP/IP port number for the ASCII commands

PA 17126

OK. Saved ASCII port number: 17126

AP Sets the ASCII password

AP "My Secret Password"

OK. Saved Ascii Password: My Secret Password

MS Sets the MQTT broker address

MS "192.168.0.121"

OK. Saved MQTT Server: 192.168.0.121

MD Sets the MQTT ID for this module

MS "Unique Module Name"

OK. Saved MQTT ID: Unique Module Name

MP Sets the MQTT broker's port

Normally, this should be set to 1883.

mp 1883

OK. Saved MQTT port number: 1883

If you are not using MQTT, set the port to 0. This will turn off MQTT, otherwise it will continuously try to connect if there is no MQTT broker.

MU Sets the MQTT user name (V1.6+)

This is for MQTT brokers that are setup to require a username and password. For open MQTT brokers that do not require a user name/password, these may be ignored.

MU "my Username"

OK. Saved MQTT User: my Username

MW Sets the MQTT password (V1.6+)

This is for MQTT brokers that are setup to require a username and password.

MW "my Super Secret Password"

OK. Saved MQTT Password: my Super Secret Password

R1-R4 Sets the MQTT topic this relay is subscribed to

R3 "Workshop/Heater"

OK. Saved Relay 3 Topic: Workshop/Heater

In use, the payload for relay topics should be a string with the first character set to '0' or '1' (ASCII characters 0x31/0x30).

N1-N2 Sets the MQTT topic this Input will publish to

N2 "Workshop/Heater"

OK. Saved Input 2 Topic: Workshop/Heater

The payload generated for input topics is a string with the first character set to '1' if the input is open or unconnected, and '0' if the input pins are shorted. (ASCII characters 0x31/0x30).

TCP/IP Commands

The ESP32LR42 has a built in TCP/IP command set which allows you to control the module remotely.

All commands are sent using plain ASCII text. PuTTY is a good cross platform terminal program to use for testing.

The TCP/IP port is the one you set-up with the PA command during USB configuration. Do not use port 80 as that is reserved for the HTML commands and Webpage.

SR Set Relay

This is used to turn a relay on or off

To turn Relay 1 on:

SR 1 1

The first number is the relay number from 1 to 8. The second number is 1 or 0, on or off.

So turn turn relay 1 off again:

SR 1 0

The command will respond with ok or fail.

SR 1 1

ok

SR 1 6

fail < 6 is not valid, only 1 or 0 for on/off

SR 9 1

fail < relay 9 does not exist.

GR Get Relay

Will return the state of the relay.

To get the status of relay 3:

GR 3

1

GR 3

0

GR 9

fail < relay 9 does not exist.

GI Get Input

Will return the status of an input.

GI 2

0 Input 2 is low (Green Led is on)

GI 2 Input 2 is high (Green Led is off)

1

GI 9

fail Only 2 inputs available

AL Get All 2 inputs

AL

10 Here, Input 2 is low, all others are high.

Inputs are numbered from left to right, 1 to 2.

Password

From version 1.5 we have added a password to the ASCII commands, this can be set with the AP command over the USB connection. The password is passed as a prefix to any command.

For example if a password is set and relay 1 is required to be turned on, start with the password (example password of 1234), then the command, so it becomes:

1234 SR 1 1

HTML Commands

There are a set of HTML commands that can be used to control the module.

?Rly3=1 This will turn on relay 3

?Rly3=0 This will turn off relay 3

?Rly3=2 This will toggle relay 3 to the opposite state.

You can enter the commands into a browser immediately after the IP address. <http://192.168.0.3/?Rly3=1>
This will turn on relay 3.

In response the module will return an XML file, which your browser will display.

```
<ESP32LR42DATA>
<RELAYS>
<RLY1>off</RLY1>
<RLY2>on</RLY2>
<RLY3>on</RLY3>
<RLY4>on</RLY4>
</RELAYS>
<INPUTS>
<INP1>1</INP1>
<INP2>0</INP2>
</INPUTS>
</ESP32LR42DATA>
```

The XML file is generated after the command has executed, therefore will reflect the new status of the relays.

Webpage

The built in webpage can be used as a remote app to monitor and control the relays. You can access the page as a default with just the IP address or by specifying index.htm.

Mean-Well-HVG-240-240W-Constan-Voltage-Constant-01

The webpage contains the Javascript to send an HTML toggle command, as described in the previous section. It will send the toggle command each time a button is clicked. It then uses the responding XML file to color the buttons and set the Input buttons to indicate input status.

Schematics

CPU

Mean-Well-HVG-240-240W-Constan-Voltage-Constant-02

Note.

The CPU schematic is the same for the ESP32LR20, ESP32LR42 and ESP32LR88. Relays 5-8 and Inputs 3-8 are not available on the ESP32LR42.

Power Supply

Mean-Well-HVG-240-240W-Constan-Voltage-Constant-03

Relay Outputs

1 of 4 identical circuits shown

Mean-Well-HVG-240-240W-Constan-Voltage-Constant-04

The relays are capable of switching up to 16 Amps at 24vdc or 230vac. A data sheet of the relay can be found [here](#). Only the normally open (N/O) contact has the snubber circuitry.

Digital Input

1 of 2 identical circuits shown



Digital Inputs have a pull-up resistor to 3.3v and will operate with a simple contact closure to ground. Alternatively, they may be connected to 3.3v logic. The clamping diodes prevent operation at voltages higher than 3.3v, so don't connect to 5v logic.

PCB dimensions

Mean-Well-HVG-240-240W-Constan-Voltage-Constant-06

Appendix 1

Programming the ESP32LR42 with Arduino studio

Customizing the ESP32LR42 can easily be achieved by using the Arduino studio and importing the required libraries.

Step 1 – Arduino IDE installation

Obtain and install the latest Arduino IDE from <https://www.arduino.cc/en/Main>/Software it should be the latest to ensure compatibility.

Step 2 – Add the ESP32 library URL to the Arduino IDE

Go to File>Preferences

Now in the Preferences screen below we need to enter

https://dl.espressif.com/dl/package_esp32_index.json into the “Additional Board Manager URLs” option. If you already have libraries added you may need to add a comma between the URLs

Mean-Well-HVG-240-240W-Constan-Voltage-Constant-07

You can now click the OK button to finish with this screen.

Step 3 – Install the ESP32 library

Go to Tools>Board:>Boards Manager...

Mean-Well-HVG-240-240W-Constan-Voltage-Constant-08

Now filter by “esp32” and install the Es press if Systems library

Mean-Well-HVG-240-240W-Constan-Voltage-Constant-09

Step 4 – Board selection

Go to Tools>Board:> and select ESP32 Dev Module

Step 5 – Add MQTT library


Go to Tools>Manage Libraries...

Filter by Pub Sub Client and select Pub Sub Client by Nick O’Leary, then press the install button

Mean-Well-HVG-240-240W-Constan-Voltage-Constant-11

That’s it! Your Arduino IDE should now be able to program the ESP32LR42 module. The factory shipped code is available Here: <https://github.com/devantech>

Documents / Resources

	<p>Devantech ESP32LR42 WiFi 4 x 16A Relays Module [pdf] User Manual</p> <p>ESP32LR42, WiFi 4 x 16A Relays Module, ESP32LR42 WiFi 4 x 16A Relays Module, Relays Module, Module</p>
---	---

References

- [Robot Electronics](#)
- [Robot Electronics](#)
- dl.espressif.com/dl/package_esp32_index.json
- [devantech · GitHub](#)
- [Software | Arduino](#)