



# DIGITUS DA-70827 USB Type C 4K 2 In 1 DisplayPort + VGA Graphics Adapter Installation Guide

[Home](#) » [DIGITUS](#) » DIGITUS DA-70827 USB Type C 4K 2 In 1 DisplayPort + VGA Graphics Adapter Installation Guide 



DA-70827 USB Type C 4K 2 In 1 DisplayPort + VGA Graphics Adapter  
Installation Guide



## Contents

- [1 Introduction](#)
- [2 Main Features](#)
- [3 Package Contents](#)
- [4 Specification](#)
- [5 Documents / Resources](#)
- [6 Related Posts](#)

## Introduction

With the DIGITUS® USB-C™ to DisplayPort™ + VGA Adapter Cable, you can connect a monitor, projector or TV with DisplayPort™ or VGA connection to the USB-C™ connection of your notebook or tablet. No additional adapters are required. Depending on the source device, this cable supports resolutions of up to 4K / 30 Hz. Thanks to Plug and Play, you don't have to install any drivers or change any settings – Just plug in and get started. You won't need any additional adapters or converters. Simply use the DIGITUS® adapter cable USB-C™ to DisplayPort™ + VGA adapter cable.

## **Main Features**

- Universal USB-C™ Graphics Adapter with DisplayPort™ and VGA Output
- Full 4K resolution at 30 Hz
- With integrated audio transmission for a Dolby Surround sound experience (except for VGA)
- High-quality aluminum housing
- The power supply is provided via the USB-C™ port
- Plug and Play – no driver installation required

## **Package Contents**

- 1 x USB Type-C™ 4K 2-in-1 DisplayPort™ + VGA Graphics Adapter
- 1 x Quick installation guide

## **Specification**

<b>Technical</b>	
Video resolution	4K Ultra HD (UHD) resolution with 4096 x 2160p / 30Hz
Power supply	The power supply is provided via the integrated USB-CTM interface on the adapter
Weight	50 g
Color depth	12 bit
Color	Black
Housing	High-quality aluminum housing
Length	20 cm
Dimension (LxWxH)	200 x 62 x 15.2 mm
Supports	HDCP 2.2 DisplayPort™ 1.4 HDMI® 1.4b Lip Sync (audio/video synchronization) 21:9 Cinemascope 8-channel LPCM, 192 kHz, 24-bit audio capability DTS EDID 1.6 (device recognition)
Supported operating systems	Android 10.0, Chrome OS 86.0, macOS 11.0.1, Windows 8.1, Linux 5.4, iPad Pro (3rd) or higher versions
Operating humidity	20% – 80% RH
Operating temperature	-10°C ~ +50°C

Manufacturer's notice: The video output capabilities depend on your notebook's graphic card and the connected monitor. Some screens also limit the available resolution. Your device equipped with USB-C™ must support the DisplayPort™ video mode (DP Alt Mode) in order to be compatible with this adapter/converter.


Hereby ASSMANN Electronic GmbH declares that the Declaration of Conformity is part of the shipping content. If the Declaration of Conformity is missing, you can request it by post under the below-mentioned manufacturer address.

[www.assmann.com](http://www.assmann.com)

Assmann Electronic GmbH  
 Auf dem Schüffel 3  
 58513 Lüdenscheid  
 Germany



**Documents / Resources**

 <p>DIGITUS</p> <p>USB Type-C™ 4K 2-in-1 DisplayPort™ + VGA Graphics Adapter</p> <p>Quick Installation Guide DA-70827</p>	<p><a href="#">DIGITUS DA-70827 USB Type C 4K 2 In 1 DisplayPort + VGA Graphics Adapter</a> [pdf] Installation Guide</p> <p>DA-70827, USB Type C 4K 2 In 1 DisplayPort VGA Graphics Adapter, DA-70827 USB Type C 4K 2 In 1 DisplayPort VGA Graphics Adapter</p>
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------