



DMXINM TGP083 Smart Toilet with Bidet Built in Instructions

[Home](#) » [DMXINM](#) » DMXINM TGP083 Smart Toilet with Bidet Built in Instructions 

DMXINM TGP083 Smart Toilet with Bidet Built in



Contents

[1 Supplemental Instructions for Function Operations](#)

[2 Documents / Resources](#)

[2.1 References](#)

[3 Related Posts](#)

Supplemental Instructions for Function Operations

1. Water Temperature Adjustment

To adjust the water temperature, use the “Water temp” button on the remote control. There are four temperature levels to choose from: room temperature, 34°C, 37°C, and 40°C.

2. Seat Temperature Adjustment

To adjust the seat temperature, use the “**Seat temp**” button on the remote control. There are four temperature levels to choose from: room temperature, 34°C, 37°C, and 40°C.

3. Warm Air Temperature Adjustment

To adjust the warm air temperature, use the “**Dry temp**” button on the remote control. There are four levels to choose from: room temperature, 01, 02, and 03.

4. Warm Air Drying Function Instructions

To use the warm air drying function, a person must be seated on the toilet seat for it to activate. The seat has a sensor to prevent accidental activation. Press the “Drying” button on the remote control to start the drying process and press the “Stop” button after drying is complete.

5. Hip Cleaning Function Instructions

To use the hip cleaning function, a person must be seated on the toilet seat for it to activate. The seat has a sensor to prevent accidental activation. Press the “Hips” button on the remote control to start the hip cleaning function. The nozzle will first self-clean and then perform the cleaning process. Use the “Flow adjust” button to increase or decrease water flow, and use the “Position adjust” button to move the nozzle forward or backward. Press the “Stop” button after cleaning is complete.

6. Female Cleaning Function Instructions

To use the female cleaning function, a person must be seated on the toilet seat for it to activate. The seat has a sensor to prevent accidental activation. Press the “female” button on the remote control to start the female cleaning function. The nozzle will first self-clean and then perform the cleaning process. Use the “Flow adjust” button to increase or decrease water flow, and use the “Position adjust” button to move the nozzle forward or backward. Press the “Stop” button after cleaning is complete.

7. Side Knob Operations Instructions

The four buttons on the side knob, from left to right, represent “Female cleaning” “Toilet flushing” “Stop” and “Hip cleaning”. Turn the knob clockwise to activate the “Female cleaning” function and counterclockwise to activate the “Hip cleaning” function. Press the knob once to stop the cleaning process and press it again to activate the “Warm air drying” function.

8. Foot Sensor to Open Toilet Seat Explanation

When using the toilet, the smart toilet will sense the presence of a person and automatically open the toilet seat. For male urination, you can use the foot sensor to open the toilet seat. After the toilet seat is open, simply bring your foot close to the sensor device located under the toilet, and the seat will automatically open.

9. Night Light Switch Instructions

The night light can be turned on/off by long-pressing the “**Night light**” button on the remote control.

10. Automatic Flushing On/Off Instructions

To activate or deactivate the automatic flushing function, long-press the “Flush water” button on the remote control for 3 seconds and wait to hear a “drip” sound, indicating that the smart toilet has executed the command to turn on/off the automatic flushing.

11. Automatic Toilet Seat Opening/Closing Function Instructions

To enable or disable the automatic opening/closing of the toilet seat, long-press the “Open” button on the remote control for 3 seconds and wait to hear a “drip” sound, indicating that the smart toilet has executed the command to turn on/off the automatic seat opening/closing function.

