



# DOCKTECK USB-Ax3 Type-C PD Charging Adapter User Manual

[Home](#) » [DOCKTECK](#) » DOCKTECK USB-Ax3 Type-C PD Charging Adapter User Manual 

# DOCKTECK

Type-C to HDMI/USB-Ax3/SD/Micro  
SD/Type-C PD Charging Adapter  
User Manual



## DEAR CUSTOMER

Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or using this product. Please keep this manual for future reference.

### Contents

- [1 INTRODUCTION](#)
- [2 FEATURES](#)
- [3 SPECIFICATIONS](#)
- [4 PACKAGE CONTENTS](#)
- [5 CONNECTION DIAGRAM](#)
- [6 Documents / Resources](#)

## INTRODUCTION

This is a Type-C 7-in-1 hub with HDMI, 3 USB-A, SD/TF card slots and Type-C female port, providing an ideal solution for extending the port of Type-C or Thunderbolt™ 3 host(PC/Laptop/Mobile phone,etc.) especially for those host with a single Type-C port. This hub adopts the latest DP Alt mode supported IC, enabling to output HDMI video with max 4K/30Hz and at the meanwhile transfer USB 3.0 data with max 5Gbps. 3 USB-A ports allow you to connect 3 USB A devices simultaneously. SD/Micro SD card slots allow to insert 2 cards simultaneously for data transmission or for reading/writing information on the host. Besides, the Type-C female supports PD 3.0 with 10W is dedicated to the functioning of this product, the rest power (max 90W) will be passed to charge for the host. It can work on all Type-C and Thunderbolt™ 3 host that supports DP Alt mode. When working on Thunderbolt™ 3 host, this product transmits DP signal.

## FEATURES

- Interface:
  - Type-C Male x 1 (connect to Type-C host PC)
  - USB-A Female x 3
  - HDMI Female x 1
  - Type-C female x 1 (PD)
  - SD Card Slot x 1
  - Micro SD Card Slot x 1
- Support USB 3.0 super speed (Max 5Gbps) transmission, downward compatible with USB 2.0
- USB 3.0 port supports to charge (max 0.9A) and transmit data for the USB device simultaneously
- Support Secure Digital v3.0 UHS-I (Ultra High Speed): SDR12 (12.5Mbyte/s) / SDR25 (25Mbyte/s) / SDR50(50Mbyte/s) / DDR50(50Mbyte/s) / SDR104(104Mbyte/s)
- Type-C Female x 1 (for PD Charging)
- Support PD Charging 100W (20V/5A)
- Support HDMI resolution up to 4K@30Hz

## SPECIFICATIONS

<b>Input/Output Connector</b>	
Input	Type-C Male x 1
Output	HDMI Female x 1 USB-A Female x 3 SD Card Slot x 1 Micro SD Card Slot x 1 Type-C female x 1 (PD)
<b>Warranty</b>	
Limited Warranty	1 Year
<b>Environmental</b>	
Operating Temperature	0°C to +45°C
Operating Humidity	10% to 90 % RH (no condensation)
Storage Temperature	-10°C to +70°C
Storage Humidity	10% to 90 % RH (no condensation)
<b>Power Supply</b>	
USB-C PD Charging Port	100W(20V/5A)
<b>Regulatory Approvals</b>	
Certifications	/
<b>Accessory Adapter</b>	
User Manual	English Version

## PACKAGE CONTENTS

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the shipping carton:


- Main unit x1
- User Manual x1

## CONNECTION DIAGRAM



# DOCKTECK

## Documents / Resources

 <p>DOCKTECK USB-Ax3 Type-C PD Charging Adapter [pdf] User Manual</p>	<p><a href="#">DOCKTECK USB-Ax3 Type-C PD Charging Adapter</a> [pdf] User Manual USB-Ax3 Type-C PD Charging Adapter, Type-C PD Charging Adapter, PD Charging Adapter, C harging Adapter, Adapter</p>
--	--