



# Dockteck USB C Hub 4K HDMI Adapter User Manual

[Home](#) » [DOCKTECK](#) » Dockteck USB C Hub 4K HDMI Adapter User Manual 

## Contents

- [1 Dockteck USB C Hub 4K HDMI Adapter](#)
- [2 INTRODUCTION](#)
- [3 FEATURES](#)
- [4 SPECIFICATIONS](#)
- [5 PACKAGE CONTENTS](#)
- [6 CONNECTION DIAGRAM](#)
- [7 Documents / Resources](#)



## Dockteck USB C Hub 4K HDMI Adapter



DEAR CUSTOMER Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or using this product. Please keep this manual for future

reference.

## INTRODUCTION

This is a Type-C multiple-port adapter with HDMI, SD/TF and 2 USB-A, allowing to extend Type-C port of the host to be multiple ports. The USB-A port allows you to connect USB device or another hub to the host USB-C computer; the HDMI port allows you to connect an HDMI monitor so that you can watch videos on a big screen; and the Micro SD and SD/MMC port allows you to read information in the memory card on the host PC. It can work on all Type-C and Thunderbolt™3 host that supports DP Alt mode. When working on Thunderbolt™3 host, this product transmits DP signal.

## FEATURES

- **Interface:**
  - Type-C Male x1 (connect to Type-C host PC)
  - USB-A Female x2
  - HDMI Female x1
  - SD slot x1, Micro SD slot x1
- Support USB 3.0 super speed (5Gbps) transmission, downward compatible with USB 2.0
- Support HDMI resolution up to 4Kx2K@30Hz
- Support Secure Digital v3.0 UHS-I (Ultra High Speed) SDR12  
(12.5Mbyte/s)/SDR25(25Mbyte/s)/SDR50(50Mbyte/s)/SDR104(104Mbyte/s)
- Support SD and Micro SD to work simultaneously
- Easy to use and carry

## SPECIFICATIONS

Input	USB-C Male x1
Output	USB 3.0 Female x2 HDMI Female x1 Micro SDX1 SD/MMCX1
<b>Resolution</b>	
Resolution	Up to 3840×2160@30Hz
<b>Physical</b>	
Size(L-W-H)	110*22.5*16(mm)
Weight	50g
<b>Warranty</b>	
Limited Warranty	1 Year
<b>Environmental</b>	
Operating Temperature	0 °C to +45°C
Operating Humidity	10% to 85 % RH (no condensation)
Storage Temperature	-10°C to +70°C
Storage Humidity	5% to 90 % RH (no condensation)
<b>Regulatory Approvals</b>	
Certifications	FCC,CE
<b>Power Supply</b>	
Power Source	Bus Power
<b>Accessories</b>	
User Manual	English Version

## PACKAGE CONTENTS


Before attempting to use this unit, please check the packaging and make sure the following items are contained in the shipping carton:

- Main unit x1
- User Manual x1

## CONNECTION DIAGRAM



## Documents / Resources

<p>Type-C to HDMI(4K/30Hz)/USB-Ax2 /SD/Micro SD Adapter User Manual</p> 	<p><a href="#">Dockteck USB C Hub 4K HDMI Adapter</a> [pdf] User Manual  USB C Hub 4K HDMI Adapter, Hub 4K HDMI Adapter, 4K HDMI Adapter, HDMI Adapter, Adapter</p>
---	---