



Dongguan Mingliang Electronic Technology T-609 Two Way Radio User Manual

[Home](#) » [Dongguan Mingliang Electronic Technology](#) » Dongguan Mingliang Electronic Technology T-609 Two Way Radio User Manual 

USER'S MANUAL

Contents



- [1 Getting Started](#)
- [2 Battery Meter](#)
- [3 Turning Your Radio On and Off](#)
- [4 Setting the Volume](#)
- [5 Battery Meter](#)
- [6 Control Buttons](#)
- [7 Talking and Listening](#)
- [8 Checking the Channel Before Transmitting](#)
- [9 Special Features](#)
- [10 Push to Talk Timeout Timer](#)
- [11 Locking the Keypad](#)
- [12 Special Features](#)
- [13 Scan Advance](#)
- [14 Removing Channels from the Scan List\(Nuisance Delete Feature\)](#)
- [15 Setting and Transmitting Call Tones](#)
- [16 Voice Activation \(VOX\)](#)
- [17 Setting the Sensitivity Level](#)
- [18 Setting the double channel monitor](#)
- [19 Setting the SQUELCH Level 1-6](#)
- [20 Setting the double channel monitor](#)
- [21 Safety and General Information](#)
- [22 Exposure to Radio Frequency Energy](#)
- [23 Operational Cautions](#)
- [24 Battery Charger Safety Instructions](#)
- [25 Documents / Resources](#)
- [26 Related Posts](#)







Getting Started

Installing the AA Batteries Your radio uses 3 AA Alkaline batteries.

1. With the back of the radio facing you, lift the battery latch up to release the battery cover and remove
2. Insert 3 AA Alkaline batteries as shown on the inside of the battery compartment.
3. Reposition the battery cover and press it down to secure. The Sondpex Walkie-Talkie can use a NiMH rechargeable battery instead of 3 AA Alkaline batteries.

Battery Meter


The battery icon shows the battery charge level,  from full to empty . When the battery is empty, the radio chirps periodically after release

WARNING SYMBOLS AND DEFINITIONS	
	This is the safety alert symbol. It is used to alert you to potential personal injury hazards. Obey all safety messages that follow this symbol to avoid possible injury or death.
	Indicates a hazardous situation which, if not avoided, will result in death or serious injury.
	Indicates a hazardous situation which, if not avoided, could result in death or serious injury.
	Indicates a hazardous situation which, if not avoided, could result in minor or moderate injury.
 	Addresses practices not related to personal injury.

. The radio powers off when the voltage drops below a predetermined level to protect the rechargeable battery.

Note: Remove the batteries before storing your radio for extended periods of time. Batteries corrode over time and may cause permanent damage to your radio.


Turning Your Radio On and Off

After you insert batteries turn the radio on, the radio chirps, and the display briefly shows all feature icons available on your radio. The display then scrolls through the available channels and Interference Eliminator Codes. Press and hold  buttons turn the radio off.

Setting the Volume

- Press the up button to increase the speaker volume.
- Press the down button to decrease the speaker volume.
- The speaker volume level is indicated by the numbers 1-16
- displayed

Battery Meter

1. With the radio on, press , The current channel flashes.
2. Press up or down to set the channel.
3. Press PTT to save the channel setting.

Control Buttons

Use /Z to:

- Scan
- Turn the radio on/off

Use UP/DOWN to:

- Adjust volume
- Scroll through menus






Use /MON to:

- Transmit call tone

Use  to:

- Select menu options
- Exit the menu (when pressed while in a menu)
- Lock and unlock the keypad (when held down and not in a menu)

Use

WARNING SYMBOLS AND DEFINITIONS	
	This is the safety alert symbol. It is used to alert you to potential personal injury hazards. Obey all safety messages that follow this symbol to avoid possible injury or death.
	Indicates a hazardous situation which, if not avoided, will result in death or serious injury.
	Indicates a hazardous situation which, if not avoided, could result in death or serious injury.
	Indicates a hazardous situation which, if not avoided, could result in minor or moderate injury.
	Addresses practices not related to personal injury.

to:

- Talk
- Save a setting


Talking and Listening

To communicate, all radios in your group must be set to the same channel and Interference Eliminator Code. To talk, press, and hold PTT. Hold the radio 2 to 3 inches away from your mouth when speaking.

When you finish speaking, release PTT (press to talk, release to listen)...

Checking the Channel Before Transmitting


Your radio has multiple channels shared on a “take a turn” basis. For uninterrupted communication, do not talk on a channel if someone else is currently talking on it.

To check for activity on a channel before you talk, press and hold /MON. If you hear static, the channel is clear to use.

Special Features

Interference Eliminator Code

Interference Eliminator Codes help minimize interference by providing you with a choice of code combinations. To set the code for a channel:

1. Press  until the code starts to flash.
2. Press UP or DOWN to select the code 0-121 OR 1 2 1 -0.
3. Press PTT to save the code setting.



You can set a different code for each channel using this procedure.



Note: You must set the Interference Eliminator Code to 0 on an FRS radio that uses Interference Eliminator Codes to communicate with other FRS radios that do not have Interference Eliminator Codes.

Push to Talk Timeout Timer

To prevent accidental transmissions and save battery life, the radio emits a continuous warning tone and stops transmitting if you press PTT for 180 continuous seconds.



Locking the Keypad

To prevent accidentally changing your radio settings, press and hold  for 3 seconds or until  display. You can turn the radio on and off, adjust the volume, receive, transmit, send a call tone, and monitor channels. All other functions are locked.

To unlock the radio, press and hold  for 3 seconds or until  it is no longer displayed

Special Features

Use scanning to monitor channels for transmissions or to find someone in your group who has accidentally changed channels.

To start scanning, briefly press and release . The scan indicator  displays. When the radio detects channel activity, it stops scanning and you can hear the transmission. To respond to the transmission, press PTT within 5 seconds.

Scan Advance

If the radio stops scanning on a channel you do not want to listen to, briefly press and release, or resume scanning for the next active channel.




Removing Channels from the Scan List(Nuisance Delete Feature)






To remove a channel so the radio does not stop on it while scanning, press and hold UP or DOWN for at least 3 seconds, then release. This temporarily removes the channel from the scan list. To restore the channel, turn the radio off and then back on.

Note: You cannot remove the channel your radio was set to when you started the scan(called your home channel)


Setting and Transmitting Call Tones

Your radio can transmit different call tones to other radios in your group so you can alert them that you want to talk.

- 1. With the radio on, press  3 times. The current call tone-setting flashes  displays.
- 2. Press UP or DOWN to change and hear the call tone.
- 3. Press  or

WARNING SYMBOLS AND DEFINITIONS	
	This is the safety alert symbol. It is used to alert you to potential personal injury hazards. Obey all safety messages that follow this symbol to avoid possible injury or death.
	Indicates a hazardous situation which, if not avoided, will result in death or serious injury.
	Indicates a hazardous situation which, if not avoided, could result in death or serious injury.
	Indicates a hazardous situation which, if not avoided, could result in minor or moderate injury.
	Addresses practices not related to personal injury.

to set the new call tone.



To transmit your call tone to other radios set to the same channel and Interference Lelimator Code as your radio, press 

Notes

- Setting the call tone to 0 disables the cal 1 tone feature.



Voice Activation (VOX)

Voice activation (VOX) allows you to talk hands-free.

- 1. Press PTT and  Turn the radio on.
- 2. Turn the radio on.  displays.
- 3. To transmit, speak into the microphone. There is a short delay between the time you start talking and when the radio transmits.
- 4. To receive, stop talking. To turn VOX off, press PTT.

Setting the Sensitivity Level

Adjusting your radio's sensitivity level helps minimize the possibility of unintended noises triggering a transmission and helps the radio pick up soft voices.

1. Press  until  display.
2. Press UP or DOWN to select the sensitivity level:

3=High Sensitivity


for quiet environments

2=Medium Sensitivity


for most environments

1=Low Sensitivity for noisy environments


Setting the double channel monitor

1. Press  until CH displays, The current channel flashes.
2. Press UP or DOWN to set the **monitor** channel.
3. Press PTT to save the **double channel monitor** setting.

Setting the SQUELCH Level 1-6

1. Press  until SL displays.
2. Press UP or DOWN to select the receive sensitivity level:
 - 01=**High receive Sensitivity**
 - 02-05=**Medium receive Sensitivity**
 - 06=**Low receive Sensitivity**

Setting the double channel monitor

1. Press  until PR displays, The current channel flashes.
2. Press UP or DOWN to set the **LO OR HI** level
3. Press PTT to save the **TX POWER LO/HI** setting.

Safety and General Information

Important Information on Safe and Efficient Operation Read This Information Before Using Your Radio

The information provided in this document supersedes the general safety information contained in user guides published prior to July 2000.

Transmit and Receive Procedure

Your two-way radio contains a transmitter and a receiver. To control your exposure and ensure compliance with the general population/uncontrolled environment exposure limits, always adhere to the following procedure:

- Transmit no more than 50% of the time.
- To transmit(talk), press the Push to Talk(PTT) button.
- To receive calls, release the PTT button.

Transmitting 50% of the time, or less is important because the radio generates measurable RF energy exposure

only when transmitting (in terms of measuring standards compliance).

Exposure to Radio Frequency Energy

Your radio is designed to comply with the following national and international standards and guidelines regarding exposure of human beings to radiofrequency electromagnetic energy: Two-Way Radio Operation When using your radio as traditional two-way radio, hold the radio in a vertical position with the microphone one to two inches (2.5 to 5 cm) away from the lips.

Facilities

To avoid electromagnetic interference and/or compatibility conflicts, turn off your radio in any facility where posted notices instruct you to do so. Hospitals or health care facilities may be using equipment that is sensitive to external RF energy.

Aircraft

When instructed to do so, turn off your radio when onboard an aircraft. Any use of a radio must be in accordance with applicable regulations per airline crew instructions.

Potentially Explosive Atmospheres

Turn off your radio prior to entering any area with a potentially explosive atmosphere. Do not remove, install, or charge batteries in such areas. Sparks in a potentially explosive atmosphere can cause an explosion or fire resulting in bodily injury or even death. Note: The areas with potentially explosive atmospheres referred to above include fueling areas such as below decks on boats, fuel or chemical transfer or storage facilities, areas where the air contains chemicals or particles, such as grain, dust, or metal powders, and any other area where you would normally be advised to turn off your vehicle engine. Areas with potentially explosive atmospheres are often but not always posted.

Blasting Caps and Areas

To avoid possible interference with blasting operations, turn off your radio when you are near electrical blasting caps, in blasting areas, or in areas posted: "Turn off two-way radio." Obey all signs and instructions.

Operational Cautions

Antennas

Do not use any portable radio that has a damaged antenna.

If a damaged antenna comes into contact with your skin, a minor burn can result.

Batteries

All batteries can cause property damage and/or bodily injury such as burns if a conductive material such as jewelry, keys, or beaded chains touches exposed terminals.

The conductive material may complete an electrical circuit (short circuit) and become quite hot. Exercise care in handling any charged battery, particularly when placing it inside a pocket, purse, or another container with metal objects.

Battery Charger Safety Instructions

1. Do not expose the charger to rain or snow.
2. Do not operate or disassemble the charger if it has received a sharp blow, or has been dropped or damaged in any way.
3. Never alter the AC cord or plug provided with the unit. If the plug will not fit the outlet, have the proper outlet installed by a qualified electrician. An improper condition can result in a risk of electric shock.
4. To reduce the risk of damage to the cord or plug, pull the plug rather than the cord when disconnecting the

charger from the AC receptacle.

5. To reduce the risk of electric shock, unplug the charger from the outlet before attempting any maintenance or cleaning.
6. Use of an attachment, not recommended, may result in a risk of fire
7. Make sure the cord is located where it will not be stepped on, tripped over, or subjected to damage or stress.
8. An extension cord should not be used unless absolutely necessary. Use of an improper extension cord could result in a risk of fire and/or electric shock. If an extension cord must be used, make sure that:
The pins on the plug of the extension cord are the same number, size, and shape as those on the plug of the charger.
The extension cord is properly wired and in good electrical condition.
The cord size is 18 AWG for lengths up to 100 feet, and 16 AWG for lengths up to 150 feet.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.


Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

SAR tests are conducted using standard operating positions accepted by the FCC with the walkie talkie transmitting at its highest certified power level in all tested frequency bands, although the SAR is determined at the highest certified power level, the actual SAR level of the walkie talkie while operating can be well below the maximum value. Before a new model is available for sale to the public, it must be tested and certified to the FCC that it does not exceed the exposure limit established by the FCC, tests for each product are performed in positions and locations as required by the FCC.

For body-worn operation, this device has been tested and meets the FCC RF exposure when used with an accessory designated for this product or when used with an accessory that contains no metal. To maintain compliance with the FCC RF exposure guideline, hold the transmitter and antenna at least 2.5 centimeters from your face and speak in a normal voice, with the antenna pointed up and away from the face. This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.

Documents / Resources

	Dongguan Mingliang Electronic Technology T-609 Two Way Radio [pdf] User Manual T-609, T609, 2AONLT-609, 2AONLT609, T-609 Two Way Radio, Two Way Radio
---	--