



DRAGINO LHT65S-NE117 LoRaWAN Temperature and Humidity Sensor Owner's Manual

[Home](#) » [DRAGINO](#) » DRAGINO LHT65S-NE117 LoRaWAN Temperature and Humidity Sensor Owner's Manual 

Contents

- 1 [DRAGINO LHT65S-NE117 LoRaWAN Temperature and Humidity Sensor Owner's Manual](#)
- 2 [OVERVIEW:](#)
- 3 [Features:](#)
- 4 [Sensor Spec:](#)
- 5 [Built-in Humidity Sensor:](#)
- 6 [External Temperature Sensor:](#)
- 7 [Order Info:](#)
- 8 [Documents / Resources](#)
 - 8.1 [References](#)

DRAGINO LHT65S-NE117 LoRaWAN Temperature and Humidity Sensor Owner's Manual



OVERVIEW:

The Dragino LHT65S-NE117 Temperature & Humidity sensor is a Long Range LoRaWAN Sensor. It includes a built-in Temperature & Humidity sensor and has an external sensor connector to connect to an external Temperature Sensor.

The LHT65S-NE117 allows users to send data and reach extremely long ranges. It provides ultra-long range spread spectrum communication and high interference immunity whilst minimizing current consumption. It targets professional wireless sensor network applications such as irrigation systems, smart metering, smart cities, building automation, and so on.

LHT65S-NE117 external probe uses TI TMP117A NIST traceability temperature sensor, with 0.1°C accuracy in normal temperature range.

LHT65S-NE117 has a built-in 2400mAh non-chargeable battery which can be used for more than 10 years*.

LHT65S-NE117 is full compatible with LoRaWAN v1.0.3 Class A protocol, it can work with a standard LoRaWAN gateway.

LHT65S-NE117 supports Datalog feature. It will record the data when there is no network coverage and users can retrieve the sensor value later to ensure no miss for every sensor reading.

Features:

LoRaWAN v1.0.3 Class A protocol Datalog feature

Tri-color LED to indicate status

AT Commands to change parameters

External probe uses TI TMP117A NIST traceability temperature sensor

Remote configure parameters via LoRaWAN Downlink Built-in 2400mAh battery for more than 10 years of use

Firmware upgradable via program port Bands: CN470/EU433/KR920/US915/EU868/AS923/AU915 Built-in Temperature & Humidity sensor

Sensor Spec:

- Built-in Temperature Sensor:
- Resolution: 0.01°C
- Accuracy Tolerance : Typ ± 0.3 °C Long Term Drift: < 0.02 °C/yr Operating Range: -40 ~ 80 °C

Built-in Humidity Sensor:

Resolution: 0.04 %RH

Accuracy Tolerance : Typ ± 0.3 RH Long Term Drift: < 0.02 °C/yr Operating Range: 0 ~ 96 %RH

External Temperature Sensor:


- silica gel cable
- ± 0.1 °C (maximum) from -20 °C to 50 °C
- ± 0.2 °C (maximum) from -40 °C to 100 °C
- ± 0.3 °C (maximum) from -55 °C to 150 °C

Order Info:

- LHT65S-NE117-XX
- XX: Frequency Bands, options: EU433,CN470,EU868,IN865, KR920,AS923,AU915,US915

Read More About This Manual & Download PDF:

Documents / Resources

	<p>DRAGINO LHT65S-NE117 LoRaWAN Temperature and Humidity Sensor [pdf] Owner's Manual</p> <p>LHT65S-NE117, LHT65S-NE117 LoRaWAN Temperature and Humidity Sensor, LoRaWAN Temperature and Humidity Sensor, Temperature and Humidity Sensor, Humidity Sensor, Sensor</p>
---	---

References

- [🌀 Dragino :: Open Source WiFi, Linux Appliance](#)