

DSPPA DSP5211L Ceiling Speaker Owner's Manual

Home » DSPPA » DSPPA DSP5211L Ceiling Speaker Owner's Manual





This product is a coaxial two frequency ceiling speaker, with a wide range of sound diffusion, large output power, easy installation, and can reproduce the voice and music. It's an ideal choice for you to install a ceiling mounted speaker with perfect sound quality. Among them, DSP5211CL is a ceiling speaker of DSP5211L with back cover.

Contents

- 1 Features
- 2 Specifications
- 3 Documents /

Resources

4 Related Posts

Features

- Adopts the fashionable thin-edge planer and the carbon alloy aluminum mesh design with the RAL white coating so as to integrate with any indoor place perfectly.
- Equipped with a 6.5" bass unit with magnetic circuit encapsulated with special engineering plastic process, and the drum paper formed with tripping and hot pressing of algae salved organisms, for the purpose of superstrong reproduction of voice and music.
- Concentric 0.75" tweeter ,provide clear and clear treble,the diffraction of a high profile provides a broad,uniform coverage.
- It is in conformity with the IEC 268-5 power handling capacity (PHC) standard, and able to operate continuously for 100 hours and carry out simulating acoustic feedback exposure (SAFE) test. It is able to bear the double rated powers within a short period, so as to ensure the high reliability of the loudspeaker under extreme conditions, prolong the service life, and reduce the possibility of occurrence of fault or degradation of performance to a great extent.
- Powerful clip design, durable and reliable, easy to install.

Specifications

Item	DSP5211L	DSP5211CL
Drive Units	6.5"×1, 0.75"×1	
Rated Impedance	8Ω	
Rated Power	10W	
Sensitivity (1m, 1W)	93±2dB	
MAX. SPL. (1m)	103±2dB	
Frequency Response	90Hz-18KHz	
Product Dimensions	Ø 190×80mm	Ø 190×105mm
Weight	0.8kg	0.9kg



Documents / Resources



<u>DSPPA DSP5211L Ceiling Speaker</u> [pdf] Owner's Manual DSP5211L, DSP5211CL, DSP5211L Ceiling Speaker, Ceiling Speaker, Speaker

Manuals+,