



# DYMO 210D LabelManager All-Purpose Portable Label Maker User Guide

[Home](#) » [DYMO](#) » DYMO 210D LabelManager All-Purpose Portable Label Maker User Guide 

## Contents

- [1 DYMO 210D LabelManager All-Purpose Portable Label Maker](#)
- [2 CREATE LABELS FAST WITH SMART KEYS](#)
- [3 Features](#)
- [4 Single Unit Includes](#)
- [5 Kit Includes](#)
- [6 Quick Specs](#)
- [7 D1 Standard Polyester Labels](#)
- [8 D1 Durable Vinyl Labels](#)
- [9 D1 Permanent Polyester Labels](#)
- [10 D1 Flexible Nylon Labels](#)
- [11 Documents / Resources](#)
- [12 Related Posts](#)



**DYMO 210D LabelManager All-Purpose Portable Label Maker**



## CREATE LABELS FAST WITH SMART KEYS

Customize labels using a Computer-style keyboard and one-touch Smart Keys for fast formatting

### Features

- Large LCD display
- Computer-style keyboard
- One-touch Smart Keys for fast formatting
- Long-lasting rechargeable battery pack
- 20+ ways to format text
- 200+ symbols and clip-art images
- Print up to 1/2 in (12 mm) wide labels

### Single Unit Includes

- LabelManager 210D
- D1 Starter Label Cassette, 12mm x 3m Black On White
- Quick Start Guide
- 2 + 1 – Year Limited Warranty\*

### Kit Includes



- LabelManager 210D + Softcase Bag
- D1 Starter Label Cassette, 12mm x 3m Black On White
- Quick Start Guide
- Charging Adapter
- 2 + 1 – Year Limited Warranty\*

| Item Number                       | Description                   |      | Length (cm) | Width (cm) | Height (cm) | QTY | EAN           | Customer Price |
|-----------------------------------|-------------------------------|------|-------------|------------|-------------|-----|---------------|----------------|
| S096 8970                         | LabelManager 210D Q WERTZ     | Unit | 9.7         | 22.2       | 20.3        | 1   | 3501170964071 |                |
| S096 4070                         | LabelManager 210D Q WERTZ KIT | Unit | 6.4         | 16.5       | 15.5        | 1   | 3501170968970 |                |
| <b>Accessories (www.dymo.com)</b> |                               |      |             |            |             |     |               |                |
| S072 1430                         | Charging Adapter              | Unit | 11.5        | 6.0        | 9.0         | 1   | –             |                |
|                                   |                               |      |             |            |             |     |               |                |

## Quick Specs

| Quick Specs                 |                                 |
|-----------------------------|---------------------------------|
| Unit Dimensions (H x W x L) | 155 x 165 x 64 mm               |
| Weight (excluding battery)  | 435 g                           |
| Mac®/PC Compatible          | No                              |
| Accepts Label Sizes         | 6mm, 9mm and 12mm               |
| Tape Platform               | D1, Durables                    |
| Resolution                  | 180 dpi                         |
| Printing System             | Thermal Transfer                |
| Print Speed                 | 12 mm/sec                       |
| Barcodes                    | No                              |
| Cutter Type                 | Manual                          |
| Batteries                   | 6 AA (not included)             |
| Adapter                     | Yes (optional, sold separately) |
| Networking                  | No                              |
| Country of Origin           | China                           |

## D1 Standard Polyester Labels



For hundreds of tasks around the office or home office, such as filing, storage and asset tracking. Temperature rating: -18°C to 90°C

| <b>D1 STANDARD LABELS (3 m)</b>     | <b>6 mm</b> | <b>9 mm</b> | <b>12 mm</b> |
|-------------------------------------|-------------|-------------|--------------|
| ABC                                 | —           | —           | 2084349      |
| ABC                                 | —           | —           | 2084401      |
| <b>D1 STANDARD LABELS (7 m)</b>     | <b>6 mm</b> | <b>9 mm</b> | <b>12 mm</b> |
| ABC                                 | S0720780    | S0720680    | S0720530     |
| ABC                                 | S0720770    | S0720670    | S0720500     |
| ABC                                 | S0720790    | S0720730    | S0720580     |
| ABC                                 | —           | S0720710    | S0720560     |
| ABC                                 | —           | S0720740    | S0720590     |
| ABC                                 | —           | S0720720    | S0720570     |
| ABC                                 | —           | —           | S0720610     |
| ABC                                 | —           | S0720690    | S0720540     |
| ABC                                 | —           | —           | S0720510     |
| ABC                                 | —           | —           | S0720600     |
| ABC                                 | —           | S0720700    | S0720550     |
| ABC                                 | —           | —           | S0720520     |
| <b>D1 STANDARD MULTIPACKS (7 m)</b> | <b>6 mm</b> | <b>9 mm</b> | <b>12 mm</b> |
| ABC                                 | —           | 2093096     | 2093097      |

## D1 Durable Vinyl Labels



Industrial strength adhesive helps to ensure labels stay stuck to a variety of surfaces. Temperature rating: -40°C to 80°C

|                                  |              |
|----------------------------------|--------------|
| <b>D1 DURABLE LABELS (3 m)</b>   | <b>12 mm</b> |
| ABC                              | 1978366      |
| ABC                              | 1978365      |
| ABC                              | 1978367      |
| <b>D1 DURABLE LABELS (5.5 m)</b> | <b>12 mm</b> |
| ABC                              | 1978364      |

## D1 Permanent Polyester Labels



Professional, polished finish ideal for panels, blocks, faceplates, shelves, bins and more. Temperature rating: -40°C to 150°C\*

|                                       |              |
|---------------------------------------|--------------|
| <b>D1 PERMANENT POLYESTER (5.5 m)</b> | <b>12 mm</b> |
| ABC                                   | S0718060     |

\*depends on surface

## D1 Flexible Nylon Labels



Specifically designed for curved surfaces and wire and cable marking. Temperature rating: -40°C to 60°C

|                                  |              |
|----------------------------------|--------------|
| <b>D1 FLEXIBLE NYLON (3.5 m)</b> | <b>12 mm</b> |
| ABC                              | S0718040     |

The DYMO® high quality labels are made in Belgium

This information is being provided for general information purposes and the compliance standards and certifications referenced herein are based on current standards which are subject to change.

**Documents / Resources**

|                                                                                   |                                                                                                                                                                                                                                                                                            |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <p><a href="#">DYMO 210D LabelManager All-Purpose Portable Label Maker</a> [pdf] User Guide</p> <p>210D LabelManager All-Purpose Portable Label Maker, 210D, LabelManager All-Purpose Portable Label Maker, All-Purpose Portable Label Maker, Portable Label Maker, Label Maker, Maker</p> |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

[Manuals+](#).