


Contents [[hide](#)]

- [1 DYNAMENT AN0007 Arduino to Platinum COMM](#)
- [2 Specifications](#)
- [3 Product Usage Instructions](#)
- [4 Connecting the Sensor](#)
- [5 FAQ](#)
- [6 Documents / Resources](#)
 - [6.1 References](#)

DYNAMENT

DYNAMENT AN0007 Arduino to Platinum COMM



Specifications

- Product Name: ARDUINO to PLATINUM COMMS HELP DOCUMENT
- Manufacturer: Dynament Limited

- Address: Hermitage Lane Industrial Estate, Kings Mill Way, Mansfield, Nottinghamshire, NG18 5ER, UK
- Contact: Tel: 44 (0)1623 663636, Email: sales@dynament.com, Website: www.dynament.com
- Issue: 1.2, Date: 09/04/2025

Product Usage Instructions

Connecting the Sensor

This data sheet uses the Arduino Mega as an example. Connect as follows:

- 5v -> 5v Arduino pin
- 0v -> Arduino GND
- Tx -> Arduino RX1
- Rx -> Goes to the output of the potential divider.

The input goes to Arduino Tx

Voltage Compatibility

The Arduino uses 5V logic high while the Platinum Sensor uses 3.3V. Use a voltage divider with suggested values for R1 and R2 as 4K7 to prevent damage to the Sensor.

Arduino IDE Setup

1. Download the newest version of the Arduino IDE software from the Arduino website.
2. Select the Arduino board, processor, and port in the tools drop-down menu.

Code Upload

1. Copy the provided example code into the Arduino IDE.
2. Upload the code to the Arduino by clicking the arrow.
3. Open the serial monitor to view data transmission.

Connecting the Sensor

This data sheet uses the Arduino Mega as an example. The Arduino Mega provides

more than one comm port, therefore comm port 1 is used to communicate with the sensor and comm port 0 is used to print to the PC.

The Arduino uses 5v logic high whereas the Platinum Sensor uses 3.3v, so to prevent damage to the Sensor a voltage divider must be used. Suggested values for R1 and R2 are 4K7Ω.




Figure 1: Lowers the voltage to useable level

The Sensor transmit line going to the Arduino receive doesn't need a divider, as 3.3V is an acceptable input to the Arduino.

To power the Sensor, it must be connected to 5V and 0V. To do this, you can use the pins on the Arduino.

After this is complete, the sensor should now have the following pins connected: 5V -> 5V Arduino pin

- 0v -> Arduino GND
- Tx -> Arduino RX1
- Rx -> Goes to the output of the potential divider. The input goes to Arduino Tx.
- After this is complete, your Platinum Sensor should be connected as shown:




Figure 2: Sensor is shown upside down with a solder adapter

- If you are using an Arduino with only one comm port (like the Arduino Uno) you will have to connect it to that, however when you use the serial monitor (shown later) it will also show the hex that is transmitted.

Arduino IDE

Go to the Arduino website and download the newest version of the Arduino IDE software. Once installed, you should see the following screen:




Figure 3: Arduino home screen

In the tools drop-down menu, select the Arduino board, processor, and port you are using:

Copy in this example code:

- `void send_read_live_data_simple(); void receive_read_live_data_simple();`

- `void setup() { Serial.begin(38400);Serial1.begin(38400); }`
- `void loop(){send_read_live_data_simple();receive_read_live_data_simple();
delay(5000);}`
- `void send_read_live_data_simple(){ // 0x10, 0x13, 0x06, 0x10, 0x1F, 0x00, 0x58
Serial1.write(0x10); Serial1.write(0x13); Serial1.write(0x06); Serial1.write(0x10);
Serial1.write(0x1F); Serial1.write(0x00);Serial1.write(0x58); }`
- `void receive_read_live_data_simple(){while (Serial1.available())
{Serial.print(Serial1.read(), HEX); Serial.print("|"); } Serial.println(); }`

- Click the arrow to upload the code to the Arduino.
- After the Arduino has been programmed, open the serial monitor.




Figure 6: Open the Serial Monitor



Code Explanation

The Arduino IDE uses C++ to program the Arduino.

```
void send_read_live_data_simple();
void receive_read_live_data_simple();
```

- This line is a forward declaration. This is used to tell the Microcontroller that further down in the program, the 'send_read_live_data_simple' function and the 'receive_read_live_data_simple' function will be called.

```
void setup() {
  Serial.begin(38400);
  Serial1.begin(38400);
}
```

- Next is the setup function. This code gets run only once on startup. It starts the Serial0 and Serial1 ports. Serial0 is what is shown in the serial monitor screen. Serial1 is the port to communicate with the sensor.

```
void loop() {
  send_read_live_data_simple();
  receive_read_live_data_simple();
  delay(5000);
}
```

- This is the main loop; this code gets repeatedly looped. You can see by reading the function names that it sends a request to read a simplified version of the live data structure. Then it reads the receive port to read the reply. After this, the Microcontroller waits 5000ms.

```
void send_read_live_data_simple(){
  // 0x10, 0x13, 0x06, 0x10, 0x1F, 0x00, 0x58
  Serial1.write(0x10);
  Serial1.write(0x13);
  Serial1.write(0x06);
  Serial1.write(0x10);
  Serial1.write(0x1F);
  Serial1.write(0x00);
  Serial1.write(0x58);
}
```


- This function writes the request to get the live data simple struct to serial port 1. As previously mentioned, if you only have one serial port, you should change Serial1 to Serial.

To see the full list of commands, refer to the Premier sensor Communications protocol document. Here is the part of the document that tells you what to write for this command:

Read live data simply

Send the following bytes:

DLE, RD. Variable 10, OLE, EOE Checksum High byte. Checksum low byte or CRC High byte, CRC low byte, i.e. 0x10, 0x13, 006, 0x10. 0x1F, 0x00, 0x58 0x9B. 0x8F



This function loops the read function while there is still data to be received from the Platinum Sensor. Serial1.read() reads the data from Serial1 which is connected to the sensor and prints it on Serial0 so it can be seen on the serial monitor. The character '|' is then printed to break up each byte that is received to make it clearer on the serial monitor.

After this is complete, it writes a new line to the serial monitor.

Packet Breakdown

Figures 8 and 9 show the output of a serial decoder connected to the receive and transmit lines.




Figure 8: Outgoing Packet




Figure 9: Incoming Packet

Figure 10 and 11 show the outgoing and incoming hex respectively with a column that shows which command it is.

Packet	Data	Command
1	10	DLE
2	13	RD
3	06	Variable ID
4	10	DLE
5	1F	EOF
6	00	Checksum High
7	58	Checksum Low

Figure 10: Outgoing Packet Description

Please note the Gas reading is a decimal not an integer. This decimal is in IEEE-754 format, you can use an online converter like this to convert it. The gas value in this case shows -250 (as it was in error mode at the time).

Using Serial.read()

The previous code only printed the data received to the serial monitor, if you want to save the data in variables you will need to do some further processing. The packet you receive is split into bytes, because of this you will need to concatenate some of this data

into variables.

Serial1.Read() returns an int (which for Arduino is 16 bits); however, only the first 8 bits are used. Because of this, we can copy it into a smaller data type that is only 8 bits; in this case, I will use char.

```
char readByte = Serial1.read();
```

For the packets that are only a byte long, this works fine:

Packet	Data	Command
1	10	DLE
2	1A	DAT
3	8	Data Length

For the packets that are 2 bytes or 4 bytes long, you will need to concatenate the data.

4	4	Version
5	0	Version
6	4	Status Flags
7	0	Status Flags
8	0	Gas Reading
9	0	Gas Reading
10	7A	Gas Reading
11	C3	Gas Reading

You can do this in a lot of different ways, here what I am going to do is left shift the data and then OR it.

```
char readByte1 = Serial1.read();  
char readByte2 = Serial1.read();  
  
int readInt = (int)readByte2 << 8 | readByte1;
```

Using this code, if readByte1 is 0x34 and readByte2 is 0x12.

- (int)readByte2 // this converts the 0x12 into 0x0012.
- (int)readByte2 << 8 // this shifts the bits over by a byte making it 0x1200.
- (int)readByte2 << 8 | readByte1 // this then gets OR'ed, with 0x34 making 0x1234.

Another way to do this would be to put the values into an array and then convert the array into the type you want:

Chars are a byte long, whereas floats are 4 bytes long. Because of this, if we make an array of 4 chars with our values in, we and change the type to float.

In this case readArray is a pointer to a char array. (float*)readArray this part casts it to a

pointer to a float and then a * is added to the front to get the value of the float.

Advanced Conversion Notes


1. Serial.read() returns an int instead of a char because errors will return negative values. Your program should check for this.
2. uint8_t and uint16_t should be used in place of char and int, respectively, as these types do not have a standard size (on my PC, int is 32 bits, whereas on the Arduino, it is 16 bits).
3. The comms protocol contains byte stuffed characters (also known as control characters), this is explained in more detail in the tds0045 Premier sensor Communications protocol document. Because of this the read live data simple packet will occasionally be bigger than expected.

FAQ

Q: What should I do if I have an Arduino Uno with only one COM port?

A: Connect the Platinum Sensor to that port. When using the serial monitor, it will also show the transmitted hex.

Documents / Resources

	DYNAMENT AN0007 Arduino to Platinum COMM [pdf] User Guide AN0007 Arduino to Platinum COMM, AN0007, Arduino to Platinum COM M, to Platinum COMM, Platinum COMM
---	---

References

- [User Manual](#)

■ DYNAMENT

◆ AN0007, AN0007 Arduino to Platinum COMM, Arduino to Platinum COMM, DYNAMENT, Platinum COMM, to Platinum COMM

Leave a comment

Your email address will not be published. Required fields are marked *

Comment *

Name

Email

Website

☐ Save my name, email, and website in this browser for the next time I comment.

Post Comment

Search:

e.g. whirlpool wrf535swhz

Search

[Manuals+](#) | [Upload](#) | [Deep Search](#) | [About Us](#) | [Privacy Policy](#) | [@manuals.plus](#) | [YouTube](#) | [LinkedIn](#) | [FaceBook](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.