



ELM-PA-G3-W
Elmdene Panic
Buttons Panic
Alarm with
Double Push
Buttons



ELM-PA-G3-W Elmdene Panic Buttons Panic Alarm with Double Push Buttons Instructions

[Home](#) » [ELMDENE](#) » ELM-PA-G3-W Elmdene Panic Buttons Panic Alarm with Double Push Buttons Instructions



Contents

- [1 ELM-PA-G3-W Elmdene Panic Buttons Panic Alarm with Double Push Buttons](#)
- [2 FAQ](#)
- [3 Installation](#)
- [4 Operation](#)
- [5 Product Overview](#)
- [6 Features](#)
- [7 Technical Information](#)
- [8 Documents / Resources](#)
 - [8.1 References](#)



ELM-PA-G3-W Elmdene Panic Buttons Panic Alarm with Double Push Buttons



FAQ

Q: Are Elmdene Panic Buttons waterproof?

A: No, the panic buttons are not waterproof. They should be installed in indoor locations away from moisture.

Q: Can I paint the panic buttons to match my wall color?

A: It is not recommended to paint the panic buttons as it may affect their performance and durability. Stick to the available finishes for best results.

ELM-PA-G3-SS

Installation

1. Choose an appropriate location for the panic button in your commercial or domestic space.
2. Ensure that the control panel is compatible with the provided integral resistors.
3. If needed, make use of the double pole connection option.
4. If wiring multiple units to one zone, utilize the spare terminals for through connection.

Operation

1. In case of an emergency, press the panic button firmly to trigger the alarm system.
2. Follow your organization's or household's emergency procedures after activating the panic button.

Product Overview

The Elmdene range of panic buttons has been ergonomically designed and are ideal for use in commercial and domestic intruder installations.

All units are double-push and are provided with integral resistors for use with most control panels. There is also

the option for double pole connection if required. Spare terminals allow through connection for multiple units wired to one zone.

They are available in 2 colours (White and Stainless Steel finishes)

Features

- Silent operation
- Grade 3
- Environmental class II
- FSL and D/P connection
- Multiple control panel and resistor options
- Easy connection of multiple units
- Cover and rear tamper
- Anti-lock reset mechanism
- Independent micro switch tamper
- Metal reset key
- Selectable normally closed or open contacts
- 5 year warranty

Technical Information

- Contact Voltage Rating 30V dc
- Contact Current Rating 1A (max)
- Operating temp. -10°C to +40°C
- Operating Life > 1 x 10⁸ Operations

The units comply fully with 'The ACPO 10 Point Plan' and all requirements under EN50131-1:2006 and PD6662:2017.

Part Numbers

Part Number	Finish	Dimensions W x L x H mm
ELM-PA-G3-W	White	62 x 80 x 27
ELM-PA-G3-SS	Stainless Steel	

Approvals


CE Mark

RoHS Compliant

© 2011-2015 Elmdene International Limited
Specifications subject to change without notice.

www.elmdene.co.uk

Documents / Resources



[ELMDENE ELM-PA-G3-W Elmdene Panic Buttons Panic Alarm with Double Push Buttons \[pdf\] Instructions](#)
ELM-PA-G3-W Elmdene Panic Buttons Panic Alarm with Double Push Buttons, ELM-PA-G3-W, Elmdene Panic Buttons Panic Alarm with Double Push Buttons, Buttons Panic Alarm with Double Push Buttons, Alarm with Double Push Buttons, Double Push Buttons, Push Buttons, Buttons

References

- [User Manual](#)

[Manuals+.](#) [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.