

Eltako 30000408 Wireless and Battery Less Bell Push Button



Eltako 30000408 Wireless and Battery Less Bell Push Button User Guide

[Home](#) » [Eltako](#) » Eltako 30000408 Wireless and Battery Less Bell Push Button User Guide 

Contents

- [1 Eltako 30000408 Wireless and Battery Less Bell Push Button](#)
- [2 Product Information](#)
- [3 Specification](#)
- [4 Using Instructions](#)
- [5 Technical Data](#)
- [6 Contact](#)
- [7 More Information](#)
- [8 Documents / Resources](#)
 - [8.1 References](#)



Eltako 30000408 Wireless and Battery Less Bell Push Button



Product Information

Specifications

- **Model:** FKD-30 000 420-1
- **Type:** Wireless and Batteryless Bell Pushbutton

Frequently Asked Questions

- **Q:** Is the bell pushbutton weatherproof?
 - **A:** Yes, the bell pushbutton is designed to be weatherproof and suitable for outdoor use.
- **Q:** How far is the wireless range of the bell pushbutton?
 - **A:** The wireless range typically extends up to 100 meters in an open area, but this can vary based on environmental factors.

Specification



- **Temperature at mounting location:** -20°C up to +50°C.
- **Storage temperature:** -25°C up to +70°C.
- **Relative humidity:** annual average value <75%.

Using Instructions

- Wireless bell pushbutton 80x40x15 mm, with energy generator. Generates the energy for radio telegrams by pushing the button, therefore without connecting cable and no stand-by loss.
- Labeling field 43x12 mm. For example for Dymo label tape 9 mm and 12 mm.

- The radio bell pushbutton transmits 1 signal that can be evaluated like a 1-way wireless\ pushbutton.
- The FKD can be screwed onto a flat surface or glued to the wall using the enclosed adhesive foil.
- Before screwing on, the housing must be opened and the prepared holes in the holding plate must be pierced with a pointed object.
- Set of 2 stainless-steel counter-sunk screws 2,9×25 mm and plugs 5×25 mm are enclosed.

Technical Data

- **Protection degree:** IP54 (Dust and splash water protection)



enocean® THE UNIQUE WIRELESS PROFESSIONAL SMART HOME STANDARD

- **Frequency:** 868.3 MHz
- **Transmit power:** max. 10 mW

Hereby, Eltako GmbH declares that the radio equipment type FKD- is in compliance with Directive 2014/53/EU. The full text of the EU declaration of conformity can be accessed via the QR code or the internet address under 'Documents'.

Must be kept for later use!

Contact

Eltako GmbH

- D-70736 Fellbach

Technical Support English:

- +49 711 943 500 25
- technical-support@eltako.de
- eltako.com

More Information

Manuals and documents in further languages:



- <http://eltako.com/redirect/FKD->



33/2023 Subject to change without notice.

Documents / Resources

	<p>Eltako 30000408 Wireless and Battery Less Bell Push Button [pdf] User Guide</p> <p>30000408 Wireless and Battery Less Bell Push Button, 30000408, Wireless and Battery Less Bell Push Button, Battery Less Bell Push Button, Less Bell Push Button, Bell Push Button, Push Button</p>
--	--

References

- [User Manual](#)

Manuals+ Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.