



# ENG01RF Series Programmable Thermostat User Guide

[Home](#) » [ENG01RF Series](#) » ENG01RF Series Programmable Thermostat User Guide 

ENG01RF Series Programmable Thermostat



## Contents

- 1 Introduction
- 2 Product Compliance
- 3 Safety Information
- 4 Installation
- 5 Wall mounting
- 6 Connection description for wired thermostat E901
- 7 Wall mounting E901RX receiver from the wireless kit
  - 7.1 LED indications in the receiver
- 8 LCD icon description
- 9 Button description
- 10 Setting Time / Setting Date
- 11 Manual mode – temperature settings
- 12 Setting the comfort temperature
- 13 Setting the economic temperature
- 14 AUTO mode – work according to the schedule
- 15 Selection of factory (0-3) programs
- 16 Choosing and programming (4-9) user programs
- 17 The second type of schedule and the programming method is described below
- 18 E901RF pairing process with the receiver
- 19 Installer settings
- 20 Installer parameters
- 21 Technical specification
- 22 Documents / Resources
  - 22.1 References
- 23 Related Posts

## Introduction

E901 & E901RF is a weekly, surface-mounted electronic room thermostat intended for home use. It has been designed for control of heating devices (e.g. gas, oil boilers, heat pumps) or cooling devices. It has the function of creating your own schedules. Thanks to the built-in algorithms, it offers much better temperature control accuracy than traditional mechanical thermostats. Please read these instructions carefully before using the device for the first time. The thermostat should use AA, 1.5V alkaline batteries. Put the batteries in the battery compartment located under the flap. Rechargeable batteries are not allowed.

## Product Compliance

This product complies with the following EU Directives:

**E901:** 2014/30/EU, 2014/35/EU, 2011/65/EU

**E901RF:** 2014/53/EU, 2011/65/EU 868.0 MHz – 868.6 MHz; <13dBm

### Please note!

This document is a quick guide for installing and operating the product and indicates its most important features and functions

## Safety Information

Use in accordance with national and EU regulations. Use the device only as intended, keeping it in a dry condition. The product is for indoor use only. Installation must be carried out by a qualified person in accordance with national and EU regulations

## Installation

Installation must be performed by a qualified person with appropriate electrical qualifications, in accordance with the standards and regulations in force in a given country and in the EU. The manufacturer is not responsible for non-compliance with the instructions.

## WARNING:


For the entire installation, there may be additional protection requirements, which the installer is responsible for.




■ The purpose of this symbol is to indicate that this device should not be discarded in household waste. For the protection of the environment, human health and natural resources, disposal should only take place at an appropriate recycling collection facility for WEEE directive products. For more information on disposal and recycling of this product please contact local municipal authorities, disposal services or the original point of purchase.

On sale, exchange or disposal of a device we recommend you reset or delete any device settings. Internet connected devices should be removed from any registered online accounts, Mobile or Web Apps, or the online account should be closed to ensure device data is no longer linked or associated with your personal details. It is the consumer's responsibility to remove a device, close an account, or notify us of any change in ownership to ensure any association or linkage to personal accounts is removed or updated.

## Wall mounting



Remove the thermostat cover as shown in the picture.



If there are batteries inside, remove them.

2




Use a screwdriver to push the plastic tabs in as shown in the figure until you feel resistance, and tilt the front part of the housing.

3



Separate the front part from the back part in the direction shown above.

4




Then fix the back cover to the wall using the supplied mounting screws and the holes provided (see bigger arrows). Connect the wires to the COM / NO connector (see smaller arrows).

5



Using the hinges from left, fold the back and front covers by moving as shown in the picture above until they click into place.

### Connection description for wired thermostat E901



### Wall mounting E901RX receiver from the wireless kit

Receiver's switches description:



	<b>LEFT SWITCH</b>
<b>1.</b>	<b>ON – Manual mode</b> – receiver ON
<b>2.</b>	<b>OFF – Manual mode</b> – receiver OFF
	<b>RIGHT SWITCH</b>
<b>3.</b>	<b>MANUAL</b> – Receiver works in manual mode (according to the left switch)
<b>4.</b>	<b>AUTO</b> – Receiver works in AUTO mode (according to the thermostat's command)

**LED indications in the receiver**





The status of the receiver is indicated by two LEDs. These are LEDs with the following colors:

1. – green (upper one),
2. – orange (lower one).


**A detailed explanation of the meaning of the LEDs can be found in the table below:**

	<b>DESCRIPTION</b>
--	--------------------

<b>The green LED lights up</b>	<p>The receiver is connected to the 230V power supply.</p> <p>The receiver can be controlled by thermostat if it is in automatic mode when the right switch is in the AUTO position.</p> <p>The receiver can be started manually when the right switch is in the MANUAL position.</p>
<b>The green LED flashes</b>	<p>The receiver is in the pairing mode and is looking for a signal from the thermostat (then you must activate the“SYNC” parameter in the thermostat).</p>
<b>The green LED is off</b>	<p>The receiver is disconnected from the 230V power supply or the left switch is in the OFF position.</p>


<p><b>The orange LED lights up</b></p>	<p>In automatic mode, the receiver received a heating / cooling signal from the thermostat.</p> <p>}The receiver was started in manual mode (left ON switch, right MANUAL switch)</p>
<p><b>The orange LED flashes</b></p>	<p>The receiver was paired but lost communication with the thermostat due to out of range or low battery in the thermostat. The receiver starts flashing after 40 minutes of time when it does not receive a signal from the thermostat.</p>
<p><b>The orange LED is off</b></p>	<p>The receiver does not send a heating / cooling signal.</p>

#### Connection description for wireless thermostat E901RF





OR

### LCD icon description




1. Program timeline indicator
2. AM/PM
3. Clock
4. Day of the week indicator
5. Settings icon
6. Key lock function
7. Send a signal (pairing)
8. Holiday Mode
9. Low battery indicator
10. Antifrost Mode
11. Comfort Mode
12. Economic Mode
13. Cooling mode – ON
14. Heating mode – OFF
15. Temperature unit
16. Room / setpoint temperature
17. Temporary override
18. Program number


### **Button description**

Button	Function
▼	Change the parameter value down
▲	Change the parameter value up
<b>D</b>	Set the day of the week
<b>H</b>	Set the hour
<b>M</b>	Set the minutes
☀	Comfort temperature
🌙➔	Economic temperature / Holiday mode
AUTO  ↺	AUTO mode / Back button
PROG 	Programming / Program selection
✓	Confirm function
● <b>Reset</b>	Factory Reset

### Setting Time / Setting Date



- D** – Press D button to set the day.
- H** – Press H button to set the hour.

 – Press M button to set the minutes.

## Manual mode – temperature settings

There are several temperature levels at our disposal. Only one temperature level is realized 24 hours a day in manual mode. You can set a different temperature for each level.



– **Comfort Mode** – in this mode, the thermostat is to maintain a constant day temperature. When the temperature is set manually, e.g. 23 ° C, the thermostat maintains it until user switches to another operating mode or set a different temperature, e.g. 21 ° C.



– **Economic Mode** – in this mode, the thermostat is to maintain the reduced (night) temperature. When the temperature is set manually, e.g. 17 ° C, the thermostat maintains it until user switches to another mode or set a different temperature, e.g. 19 ° C.




The values of these temperatures are taken into account in the automatic mode (for the first type of schedule -> see next page).


## Setting the comfort temperature




Press any button to highlight the screen, then follow the steps below:



1




Press  button to enter comfort temperature mode. The sun icon should be visible on the display


2



Using  or  buttons set new comfort temperature value

3




Confirm by  button or wait until the thermostat will approve your choice itself and display the main screen.


### Setting the economic temperature






Press any button to highlight the screen, then follow the steps below








Press  button to enter economic temperature mode. The moon icon should be visible on the display.

Using  or  buttons set new economic temperature value.




Confirm by  button or wait until the thermostat will approve your choice itself and display the main screen.

### AUTO mode – work according to the schedule

 **AUTO**  
 In the automatic mode, the thermostat maintains the set temperature according to the schedule selected by the user. You can choose from 2 types of schedule to manage the temperature during the week.

The first type of schedule (factory set with a time line) and its programming is described below:




There are 9 programs available. Programs 0-3 are factory programs. Programs 4-9 can be defined by user.


### Selection of factory (0-3) programs



Press any button to highlight the screen, then follow the steps below:




Press **PROG** button to enter the programming mode



Select the week period using or buttons.

Confirm by button





Using or buttons choose program number (0-3). Confirm by button. The thermostat will proceed to program selection for the next time period


### Choosing and programming (4-9) user programs



Press any button to highlight the screen, then follow the steps below:






Press  button to enter the programming mode.




Select the week period using  or  buttons. Confirm by  button.







3




Using  or  buttons choose program number (4-9).

4



Then – each time you press the sun –  button or moon button –  you move the timeline one hour –  and assign a comfortable (  ) or economic (  ) temperature. Confirm by  button.


**PLEASE NOTE! Programs should be set for each week days.**




The second type of schedule and the programming method is described below






Press any button to highlight the screen, then follow the steps below:




Press **PROG** button for 5 seconds to enter to the schedule programming selection mode.




Using  or  buttons choose the second type of schedule programming




Confirm by  button. Thermostat will return to the main screen saving the second type of schedule programming. The timeline will also disappear.

4



Press **PROG** button to enter the programming mode.


5







Select the week period using  or  buttons. Confirm by  button.







6



Using  or  buttons set the program start and then after confirmation by  button, set the minutes. Confirm by  button.

7



Use  or  buttons to set the temperature. Confirm by  button.  
The thermostat will proceed to set the next program (a maximum of 6 programs can be set).




#### PLEASE NOTE!

Programs should be set for each week days.


**E901RF pairing process with the receiver**



**PLEASE NOTE!** E901RF THERMOSTAT IS ALREADY PAIRED WITH THE RECEIVER!






If you want to re-pair the devices with each other, make sure that the receiver is disconnected from the power supply, and the switches on it are in the ON and AUTO positions. Then connect the receiver to the power supply and wait for the green diode to glow continuously. Next, move the left switch to the OFF position and back to the ON position with a quick motion. After all, the green diode will start blinking, which will confirm that the receiver has entered the pairing mode.




Press  button for 5 seconds.

5







Use  or  buttons to select SYNC parameter.


6



Confirm by  button.




Using  or  buttons choose YES and start the pairing process on a new frequency by pressing the  button.




The thermostat started to send a signal to find the receiver (the symbol of the blinking antenna) and started the countdown with the number 10 (min). The pairing process may take up to 10 minutes

9




When the green diode on the receiver lights up continuously, the devices have been paired on a new frequency

10




The thermostat will display the message „good“, which means that the devices are successfully paired with each other.

11





The thermostat will return to the main screen.

 **WARNING!** If the green diode on the receiver has not stopped blinking after 10 minutes, repeat the pairing process taking into account the distance between devices, obstacles and interference.


**Installer settings**







1






To enter installer parameters press and hold  button for 5 seconds.

2



You are in the installer mode. Use  or  buttons to move between parameters. Enter the parameter by  button. Edit the parameter using  or  button. Confirm the new parameter value with the  button.

### Installer parameters

Pxx	Function	Value	Description	Default value
P01	Heating/Cooling Selection		Cooling	
			Heating	
P02	Control method temperature	1	SPAN $\pm 0,25^{\circ}\text{C}$	1
		2	SPAN $\pm 0,5^{\circ}\text{C}$	
		3	TPI for Underfloor Heating	
		4	TPI for Radiators	
		5	TPI for Electrical Heating	
P03	Display temperature resolution	0,5°C	This parameter specifies the accuracy of the displayed (measured) temperature.	0,5°C
		0,1°C		
P04	Offset temperature	-3.5°C to + 3.5°C	If the thermostat indicates wrong temperature, you can correct it by $\pm 3.5^{\circ}\text{C}$	0°C

P05	Relay type	NO	Normally Open type of relay	NO
		NC	Normally Closed type of relay	
P06	Clock format	24h	24 hour	24h
		12h	12 hour	
P07	Temperature Scale	°C	Celsius	°C
		°F	Fahrenheit	
P08	Minimum setpoint	5°C – 34,5°C	Minimum heating / cooling temperature that can be set	5°C
P09	Maximum setpoint	5,5°C – 35°C	Maximum heating / cooling temperature that can be set	35°C
P10	Key sound	NO	Off	YES
		YES	On	
P11	PIN Code	NO	Disabled	NO
		PIN	Enabled	
P12	Require a PIN to unlock the keys every time	NO	Function disabled	YES
		YES	Function enabled	
CLR	Clear settings factory reset	NO	No action	NO
		YES	Factory Reset	
*Only for <b>E901RF</b> thermostat				
SYNC	Pairing function with receiver ( SYNC)	NO	Function disabled	NO

## Technical specification

### Wired thermostat E901

Thermostat supply	2 x AA batteries
Rating max	5 (3) A
Outputs	Voltage-free NO/COM relay
Temperature range	

### Wireless thermostat E901RF (868 MHz)



Thermostat supply	2 x AA batteries
Receiver supply	230 V AC 50 Hz
Receiver rating max	16 (5) A
Receiver outputs	x 16 (5) A Receiver outputs Voltage-free NO/COM relay
Temperature range	5 – 35°C

Distributor:  
 QL CONTROLS Sp z o.o. Sp. k.  
 43-262 Kobielice 4 Rolna St. Poland



## Documents / Resources

	<a href="#">ENGGO CONTROLS E901RF Series Programmable Thermostat</a> [pdf] User Guide E901RF, E901, E901 Programmable Thermostat, E901RF Series Programmable Thermostat, Programmable Thermostat, Thermostat
--	--

## References

- [ENGGO Controls - Sterowanie ogrzewaniem](#)