



## ESi Controls 4 RF Pairing Receiver Instructions

[Home](#) » [ESi Controls](#) » ESi Controls 4 RF Pairing Receiver Instructions 

### ESi Controls 4 RF Pairing Receiver Instructions



If your RF receiver and room thermostat RF bond is lost, follow the instructions below.

1. On your RF receiver, press & hold the **M/A** button until the MANUAL button flashes green. Release the button.
2. On your thermostat, move the slider bar to the OFF position.
3. Hold the **A** button, **H** button & + buttons until the green light on your RF receiver stops flashing.
4. Move the slider bar to AUTO.

If both of the buttons on your RF receiver are flashing, isolate the power to your RF receiver for a full 10 minutes, then switch it back on and follow the steps above.




## Contents

## 1 Documents / Resources

## 1.1 References

## 2 Related Posts

## Documents / Resources



# ESi Controls 4 RF Pairing Receiver [pdf] Instructions

## 4 RF Pairing Receiver, Pairing Receiver, Receiver

## References

- User Manual

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.