

# ESPRESSIF WRL-17830 ESP32 WROOM MCU Module 16MB PCB Antenna User Guide

[Home](#) » [ESPRESSIF](#) » ESPRESSIF WRL-17830 ESP32 WROOM MCU Module 16MB PCB Antenna User Guide

## Contents [ [hide](#) ]

- [1 ESPRESSIF WRL-17830 ESP32 WROOM MCU Module 16MB PCB Antenna](#)
- [2 Design Change in ECO V3](#)
- [3 Impact on Customer Projects](#)
- [4 Label Specification](#)
- [5 Ordering Information](#)
- [6 Documents / Resources](#)
  - [6.1 References](#)
- [7 Related Posts](#)



**ESPRESSIF WRL-17830 ESP32 WROOM MCU Module 16MB PCB Antenna**



This document describes differences between V3 and previous ESP32 silicon wafer revisions.

## Release Notes

Date	Version	Release notes
2020.01	V1.0	Initial release.
2020.07	V1.1	Added item 6 to Chapter 1 Design Changes in ECO V3.

### Documentation Change Notification

Espressif provides email notifications to keep customers updated on changes to technical documentation. Please subscribe at <https://www.espressif.com/en/subscribe>.

### Certification

Download certificates for Espressif products from <https://www.espressif.com/en/certificates>.

## Design Change in ECO V3

Espressif has recently released one wafer-level change on ESP32 Series of products (ECO V3). This document describes differences between V3 and previous ESP32 silicon wafer revisions. Below are the main design changes in ECO V3 Series of chips:

1. PSRAM Cache Bug Fix: Fixed “When the CPU accesses the external SRAM in a certain sequence, read & write errors can occur.”. Details of the issue can be found in item 3.9 in ESP32 ECO and Workarounds for Bugs.
2. Fixed “When each CPU reads certain different address spaces simultaneously, a read error can occur.” Details of the issue can be found in item 3.10 in ESP32 ECO and Workarounds for Bugs.
3. Optimized 32.768 KHz crystal oscillator stability, the issue was reported by client that there is a low probability that under ECO V1 hardware, the 32.768 KHz crystal oscillator couldn't start properly.
4. Fixed Fault injection issues regarding secure boot and flash encryption are fixed. Reference: Security Advisory concerning fault injection and eFuse protections (CVE-2019-17391) & Espressif Security Advisory Concerning Fault Injection and Secure Boot (CVE-2019-15894)
5. Improvement: Changed the minimum baud rate supported by the CAN module from 25 kHz to 12.5 kHz.
6. Allowed Download Boot mode to be permanently disabled by programming new eFuse bit UART\_DOWNLOAD\_DIS. When this bit is programmed to 1, Download Boot mode cannot be used and booting will fail if the strapping pins are set for this mode. Software program this bit by writing to bit 27 of EFUSE\_BLK0\_WDATA0\_REG, and read this bit by reading bit 27 of EFUSE\_BLK0\_RDATA0\_REG. Write disable for this bit is shared with write disable for the flash\_crypt\_cnt eFuse field.

## Impact on Customer Projects

This section is intended to help our customers to understand the impact of using ECO V3 in a new design or replacing older version SoC with ECO V3 in existing design.

### Use Case 1: Hardware and Software Upgrade

This is the use-case where the new project is being initiated or upgrade for hardware and software in an existing

project is a possible option. In such a case, the project can benefit from protection against fault injection attack and can also take advantage of newer secure boot mechanism and PSRAM cache bug fix with slightly enhanced PSRAM performance.

#### 1. Hardware Design Changes:

Please follow the latest Espressif Hardware Design Guideline. For 32.768 KHz crystal oscillator stability issue optimization, please refer to Section Crystal Oscillator for more information.

#### 2. Software Design Changes:

1. Select Minimum configuration to Rev3: Go to menuconfig > Component config > ESP32-specific, and set the Minimum Supported ESP32 Revision option to “Rev 3”.
2. Software version: Recommend to use RSA-based secure boot from IDF4.1 and later. IDF3.X Release version can also work with application with original secure boot V1.

#### Use Case 2: Hardware Upgrade Only

This is the use-case where customers have existing project which can allow hardware upgrade but software needs to remain the same across hardware revisions. In this case the project gets benefit of security to fault injection attacks, PSRAM cache bug fix and 32.768KHz crystal oscillator stability issue. The PSRAM performance continues to remain the same though.

#### 1. Hardware Design Changes:


Please follow latest Espressif Hardware Design Guideline.

#### 2. Software Design Changes:

Client can continue to use the same software and binary for deployed product. The same application binary will work on both ECO V1 and V3 chip versions.

### Label Specification

- The label of ESP32-D0WD-V3 is shown below:



- The label of ESP32-D0WDQ6-V3 is shown below:



## Ordering Information

For product ordering, please refer to: Espressif Products Ordering Information.








## Disclaimer and Copyright Notice

- Information in this document, including URL references, is subject to change without notice.
- THIS DOCUMENT IS PROVIDED AS IS WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY OTHERWISE ARISING OUT OF ANY PROPOSAL, SPECIFICATION OR SAMPLE.
- All liability, including liability for infringement of any proprietary rights, relating to use of information in this document is disclaimed. No licenses express or implied, by estoppel or otherwise, to any intellectual property rights are granted herein.
- The Wi-Fi Alliance Member logo is a trademark of the Wi-Fi Alliance. The Bluetooth logo is a registered trademark of Bluetooth SIG.
- All trade names, trademarks and registered trademarks mentioned in this document are property of their respective owners, and are hereby acknowledged.
- Copyright © 2020 Espressif Inc. All rights reserved.
- Espressif IoT Team
- [www.espressif.com](http://www.espressif.com)

## Documents / Resources

	<p><a href="#">ESPRESSIF WRL-17830 ESP32 WROOM MCU Module 16MB PCB Antenna</a> [pdf] User Guide</p> <p>WRL-17830, ESP32 WROOM MCU Module 16MB PCB Antenna, WRL-17830 ESP32 WROOM MCU Module 16MB PCB Antenna, WROOM MCU Module 16MB PCB Antenna, MCU Module 16MB PCB Antenna, 16MB PCB Antenna, Antenna</p>
--	---

## References

-  [Overview | Espressif Systems](#)
-  [Wi-Fi & Bluetooth MCUs and AIoT Solutions | Espressif Systems](#)
-  [Certificates | Espressif Systems](#)
-  [Documentation Feedback | Espressif Systems](#)
-  [Espressif Security Advisory Concerning Fault Injection and Secure Boot \(CVE-2019-15894\) | Espressif Systems](#)
-  [Security Advisory concerning fault injection and eFuse protections \(CVE-2019-17391\) | Espressif Systems](#)
-  [Subscribe | Espressif Systems](#)