



eWeLink BASICR4 Wi-Fi Smart Switch User Manual

[Home](#) » [EWeLink](#) » eWeLink BASICR4 Wi-Fi Smart Switch User Manual 

Contents

- [1 eWeLink BASICR4 Wi-Fi Smart Switch](#)
- [2 Introduction](#)
- [3 Specification](#)
- [4 Installation](#)
- [5 Add device](#)
- [6 Installation and use](#)
 - [6.1 Lay flat before use](#)
- [7 Device function](#)
- [8 FAQ](#)
- [9 FCC Warning](#)
- [10 Documents / Resources](#)
 - [10.1 References](#)

eWeLink

eWeLink BASICR4 Wi-Fi Smart Switch



Introduction

A Wi-Fi smart switch integrating APP remote control, voice control, timer and other functions. You can control your home appliances anytime, anywhere, and also create a variety of smart scenes to facilitate your life.



Remote Control




Voice Control



Timer Schedule




LAN Control



Power-on State



Smart Scene



Share Device



Create Group

Button

- **Single press:** Changing the on/off state of relay contacts
- **Long press for 5s:** Enter pairing mode

Wi-Fi LED indicator (Blue)

- **Flashes two short and one long:** The device is in pairing mode.
- **Keeps on:** Online
- **Flashes once:** Offline
- **Flashes twice:** LAN
- **Flashes three times:** OTA
- **Keep flashing:** Overheat protection

1. Wiring ports
2. Protective cover

Compatible Voice Assistants




Specification

Model	BASICR4
MCU	ESP32-C3FN4
Input	100-240V ~ 50/60Hz Max 10A
Output	100-240V ~ 50/60Hz Max 10A
Max. power	2400W@240V
Wireless Connectivity	Wi-Fi IEEE 802.11b/g/n 2.4GHz
Net weight	45.8g
Product dimension	88x39x24mm
Color	White
Casing material	PC V0
Applicable place	Indoor
Working temperature	-10°C~40°C
Working humidity	10%~95% RH, non-condensing
Certification	ISED/FCC/RoHS/ETL/CE/SRRC
Executive standard	EN IEC 60669-2-1, UL 60730-1, CSA E 60730-1

Installation

Power off




- Please install and maintain the device by a professional electrician. To avoid electric shock hazard, do not operate any connection or contact the terminal connector while the device is powered on!

Wiring instruction

To ensure the safety of your electrical installation, either a Miniature Circuit Breaker (MCB) or a Residual Current Operated Circuit Breaker (RCBO) with an electrical rating of 10A must be installed before the BASICR4.


Wiring: 16-18AWG SOL/STR copper conductor only, Tightening torque: 3.5 lb-in



- Make sure all wires are connected correctly.

Power on

After powering on, the device will enter the Pairing Mode defaulted during the first use, and the LED indicator flashes in a cycle of two short and one long.



- The device will exit the Pairing Mode if it is not paired within 10 minutes. If you want to enter this mode again, please long press the button for 5s until the LED indicator flashes in a cycle of two short and one long and then

release.



Add device

Download the eWeLink App


- Please download the “eWeLink” App from the Google Play Store or Apple App Store.




Add device



1. Please follow the wiring instructions to connect the wires (ensure power is disconnected in advance and consult an electrician if needed)
2. Power on the device




3. Enter“Scan”
4. Scan the BASICR4 QR code on the device body





5. Select "Add Device"

6. Long press the button for 5 seconds



7. Check Wi-Fi LED indicator flashing status (Two short and one long)

8. Search for the device and start connecting






9. Select the "Wi-Fi" network and enter the password.

10. Device "Added completely".

Installation and use

Lay flat before use

Use of Fixing Screws




1. Screw the lower cover to the wall
2. Close the upper cover
3. Secure the protective cover with screws

Device function

Magic Switch Mode

After short-circuiting the L1 and L2 of the switch terminals through the wires, the device can still be online and can be controlled through the APP after the users flip the wall switch to turn off/on the light.

- Add a wire to connect L1 to L2 on the wall switch following the manual, and the device will stay online even when you switch it off via the wall switch after “Magic Switch Mode” enabled.
- The “Power-on State” will automatically be set to OFF, to make the “Magic Switch Mode” functional when enabled.
- The “Magic Switch Mode” will automatically disable after your adjustment to the “Poweron State”.



Note: Only compatible with mainstream brands of double pole rocker switch. The rear-end light needs to be compatible with mainstream brands of LED, energy-saving lamps, and incandescent lamps ranging from 3W to 100W.

- This function also applies to dual-control lamps

Auxiliary overheating protection

With the product's built-in temperature sensor, the real-time maximum temperature of the entire product can be detected and speculated, which prevents the product from deformation, melting, fire or live devices in case of over-temperature. The device automatically cuts off the load when it gets too hot. To exit the overheating protection mode, simply press the button on the device after confirming that the load is functioning normally without any internal shorts, excessive power, or leaks.

- Please note that this function only serves as auxiliary protection and cannot be used in place of a circuit breaker.

Device Network Changing

- Change the device's network by "Wi-Fi Settings" in the "Device Settings" page on the eWeLink App.

Factory Reset

- Reset the device to factory settings by "Delete device" in the eWeLink App.

FAQ

Fail to pair Wi-Fi devices with the eWeLink App

1. Make sure the device is in pairing mode. The device will automatically exit the pairing mode if it is not paired within 10 minutes.
2. Please enable location service and allow access to location permission. Before connecting Wi-Fi network, please enable the location service and allow access to the location permission. Location information permission is used to obtain Wi-Fi list information, if you "disable" the location service, the device cannot be paired.
3. Make sure your Wi-Fi works on 2.4GHz band.
4. Make sure to enter the Wi-Fi SSID and password correctly without special characters. An incorrect password is a common cause of pairing failure.
5. To ensure good signal transmission while pairing, please place the device close to the router.

The LED indicator flashes twice on repeated means the server fails to connect.

1. Make sure the networking is normal. Check the internet works well by connecting your phone or PC. If fail to connect, please check the availability of the Internet connection.
2. Please check the maximum number of devices that can be connected to your router. If your router has a low capacity and the number of devices connected to it exceeds the maximum, remove some devices or use a higher-capacity router. If the above methods cannot help to solve the problem, please submit your problem to "Help & Feedback" on the eWeLink App.

Wi-Fi devices are "offline"

1. Devices fail to connect to the router.
2. Entered the wrong Wi-Fi SSID and password.
3. Wi-Fi SSID and password contain special characters, for example, our system can't recognize Hebrew and Arabic characters, which causes Wi-Fi connections to fail.
4. Low capacity of the router.
5. The Wi-Fi signal is weak. The router and the devices are too far apart, or there is an obstacle between the router and the device, which prevents the signal from being transmitted.

FCC Warning

1. This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:
 1. This device may not cause harmful interference, and
 2. This device must accept any interference received, including interference that may cause undesired operation.
2. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, under part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used by the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and the receiver.
- Connect the equipment to an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20 cm between the radiator and your body. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

ISED Notice

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

1. This device may not cause interference.
2. This device must accept any interference, including interference that may cause undesired operation of the device. This Class B digital apparatus complies with Canadian ICES-003. This device complies with RSS-247 of Industry Canada.

SAR Warning

Under normal use of conditions, this equipment should keep a separation distance of at least 20cm between the antenna and the body of the user.

WEEE Warning

WEEE Disposal and Recycling Information All products bearing this symbol are waste electrical and electronic equipment (WEEE as in directive 2012/19/EU) which should not be mixed with unsorted household waste. Instead, you should protect human health and the environment by handing over your waste equipment to a designated collection point for the recycling of waste electrical and electronic equipment, appointed by the government or local authorities. Correct disposal and recycling will help prevent potential negative consequences to the environment and human health. Please contact the installer or local authorities for more information about the location as well as the terms and conditions of such collection points.

EU Declaration of Conformity

Hereby, Shenzhen Sonoff Technologies Co., Ltd. declares that the radio equipment type BASICR4 complies with Directive 2014/53/EU. The full text of the EU Declaration of Conformity is available at the following internet address: <https://sonoff.tech/usermanuals>

EU Operating Frequency Range

- **Wi-Fi:802.11** b/g/n20 2412–2472 MHZ ;
- 802.11 n40: 2422-2462 MHZ ;
- **BLE:** 2402–2480 MHz


EU Output Power

- Wi-Fi 2.4G≤20dBm ; BLE≤13dBm

Scatola	Manuale
PAP 21	PAP 22
Carta	Carta
RACCOLTA DIFFERENZIATA	
Verifica le disposizioni del tuo Comune.	
Separa le componenti e conferiscile in modo corretto.	

- **Manufacturer:** Shenzhen Sonoff Technologies Co., Ltd.
- **Address:** 3F & 6F, Bldg A, No. 663, Bulong Rd, Shenzhen, Guangdong, China
- **ZIP code:** 518000 Service
- **email:** support@itead.cc
- **Website:** sonoff.tech Made in China
- Points de collecte sur www.quefairedemesdechets.fr

Documents / Resources

 <p>BASICR4 Wi-Fi Smart Switch</p> <p>Introduction</p> <p>A Wi-Fi smart switch integrating 40W max power, voice control, timer, and other functions. You can control your home appliances remotely through the eWeLink app. Control of smart devices is flexible and easy to use.</p> <p>Product Guide How to Use How to Install eWeLink App</p>	<p>eWeLink BASICR4 Wi-Fi Smart Switch [pdf] User Manual</p> <p>BASICR4 Wi-Fi Smart Switch, BASICR4, Wi-Fi Smart Switch, Smart Switch, Switch</p>
--	--

References

- [User Manual](#)