




faytech 24" Capacitive Touch PC N4200 User Guide

[Home](#) » [faytech](#) » faytech 24" Capacitive Touch PC N4200 User Guide 




24" Capacitive Touch PC N4200
FT24N4200CAPOB



Yes ☒
No ☐

Supports Clamps



Optically Bonded



- **Intel ® Pentium ® N4200 QuadCore CPU**
- **4GB RAM memory, 128GB Industrial SSD**
- **Supports Windows 10 & Linux (32Bit, 64Bit)**
- **Anti-glare surface treatment (chemical etching)**
- **10-Finger-Multi Touch Capacitive Touch Panel**
- **1.1mm cover glass with 7H surface hardness**
- **Optically bonded Touch Panel to LCD Panel**
- **Patented IP65 front with silicon seal**
- **Integrated W-LAN**
- **2-year guarantee (24/7 usage)**


faytech's Capacitive PC series stands out among the competition with its fanless silent operation, IP65 front panel design, high reliability, and fine craftwork.

This device is made for 24/7 operation and is the perfect choice for industrial and business applications. It has a flat edge-to-edge glass with IP65 water- and dustproof front panels and a sturdy aluminum case with stable VESA 100 fixation bolts.

The PC is powered by faytech's industrial Apollo Lake mainboard. It is driven by the powerful Intel ® Pentium ® N4200 QuadCore processor with up to 2.50 GHz clock frequency. This version is equipped with 4GByte RAM, 128G SSD and Intel's HD Graphic chipset, supporting FullHD, DirectX 11.1 and OpenGL 4.0.

These faytech PCs are the perfect choice for a wide variety of applications including POS systems, control panels in industrial fields, in kiosk systems, office/residence automation, digital signage, and in areas like shopping malls, classrooms, hotels, and many more.

Legend / Notes	
Applicable to version 3	(v3)
Applicable to version 4	(v4)
Applicable to all Versions	None



Product name				24" Capacitive Touch PC N4200			
Model number / EAN number				FT24N4200CAPOB / 6920734000333			
Global Article Code	European Article Code	Release date (D/M/Y)	Version	Global Article Code	European Article Code	Release date (D/M/Y)	Version
3030505559	1010502023	01/07/2021	v3				

IP Rating
IP65 Front / IP40 Back

LCD Panel	
Screen diagonal (Inch/cm)	24/60.97
Display active screen size (cm)	53.13×29.88
Aspect ratio	16:9
Physical resolution	1920×1080
External Maximum showable resolution – HDMI, DP	1920×1200
Colours displayed	16.7M
Brightness (cd/m ²)	500
Contrast	1000:1
Typical reaction time Tr / Tf (ms)	3.5/1.5
Visual Angle horizontal/vertical (°)	170/160
Surface Hardness	LED / 20,000

Operation / Mechanical	
Operating Temperature (°C)	-10 ~ +60
Humidity Range (RH)	10% – 90%
Net weight (kg)	5.86
Gross weight (kg)	9.30 (incl. cartonage)
Housing material	Rubber frame, Aluminum IPC back case
Housing (mm) L × W × H	579.4 × 347.0 × 57.5
Cut-out for clamp supports (mm) L × H	555.4 × 323.0
Max. wall thickness for clamp supports (mm)	5.0
Amount of clamps required	7
Mounting	VESA 100

Internal Connectors (occupied)		
1x SO-DIMM, max. 8GB, DDR3L 1333/1600/1867 non-ECC, Single channel memory		
3x RS232/RS485 COM connectors switchable in BIOS		
2x LCD Backlight control/LCD panel voltage box		
1x 5V/12V SATA power connector	1x 12V DC power connector (2-pin)	
1x 4-pin SATA power connector	1x S/PDIF output pin header	
1x 8-bit Digital I/O interface	1x Line-out / Mic-in header	
1x Front Panel box header	1x Serial ATA 6Gb/s	
1x MIPI CSI connector	1x LVDS box header	2x USB 3.0 box header

PC System	
CPU	Intel' Pentium' QuadCore N4200
Graphic GPU	Inter HD Graphics
Audio	Realtek ALC3236 Audio CODEC
Memory	4GB DDR3L non-ECC (max. 8GB)
Storage (switchable)	faytech Industrial 128GB SSD
Network	2x Realtek PCIe GB LAN 8111G (1x optional with POE); W-LAN
Driver Support	Win10: Linux: 32Bit/64Bit
Preinstalled OS	Linux Ubuntu


Touch Panel	
Touch Technology	Projected Capacitive 10-Point Multitouch
Touch Connector	USB
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Surface Treatment	Anti-glare (chemical etching)
Glass Strengthening	Chemically Strengthened

Power	
Power Indicator	Green LED
Power Supply	100-240V ACDC active switching; 12V DC-Out
Working Power (V)	12
Power Consumption (W)	36
Stand-By Consumption (W)	<1

External Connectors	
1x 12V DC-In (screwable)	
1x W-LAN antenna connector (RP-SMA male)	
2x USB 2.0	2x USB 3.0
1x HDMI	1x DP
1x MIC-In & EAR-Out	
1x 10-PIN DIO as RJ50	
1x COM – RS 232/422/485 switchable: 5V/12V1RI option (COM1. DSUB9)	
1x COM – RS 232: RXJTX (COM2. DSUB9)	
2x COM – RS 232 & 485: RXITX & A+/B(COM3&4, RJ12)	
2x 10/100/1000MtAt R345 Ports	
1x 2.5" module slot, changeable SSD included	

Expansion Slots
1x mSATA full size (occupied by SSD)
1x M.2 E-Key Slot (occupied by Wifi card)
1x SATA connector
1x External PCIe x1 Straddle connector

Included in the Delivery
Power Supply (see Power section)
W-LAN antenna (RP-SMA female)
Short Installation Manual
Standard Stand



Tolerance: $\pm 1\text{mm}$

Errata and technical modifications reserved

Update Notes:

Version: Changes:
v3 – First version

Headquarters Corporate

faytech AG

Bischhauser Aue 10
37213 Witzzenhausen
Germany

support@faytech.com

contact@faytech.com

www.faytech.com

China: +86 755 8958 0612

Germany: +49 5542 30374 10

USA: +1 646 843 0877

India: +91 11 49707436

Japan: +070 4127 5167



Contents

1 Documents / Resources

1.1 References

2 Related Posts

Documents / Resources

	<p>faytech 24" Capacitive Touch PC N4200 [pdf] User Guide 24 Capacitive Touch PC N4200, FT24N4200CAPOB</p>
	<p>faytech 24" Capacitive Touch PC [pdf] User Guide 24 Capacitive Touch PC, FT24I5CAPOB, i5-7300u</p>

References

- [faytech Industrial touch panel pc | Touch Monitors and Pcs | faytech](#)