Manuals+ — User Manuals Simplified.

FDI UEZGUI-4357-50WVN-BA 5.0 Pcap Touch Screen LCD GUI Development Kit Instruction Manual

Instruction Manual

Contents

5.0" PCAP Touch Screen LCD GUI Development Kit

Congratulations on the purchase of your µEZ® GUI development kit! Our goal is to ensure you have a pleasant experience familiarizing yourself with the functions and capabilities of our products.

To Begin Development with your µEZ GUI:

1. Power on the device by connecting the 5V power adapter tone end of the USB cable and the other end to the µEZ GUI P2.
   Note: Do not connect the µEZ GUI to a computer USB port. Standard USB 2.0/3.0 ports will not provide sufficient power to the device.
2. Visit **TeamFDI.com/StartHere** to download the UEZGUI-4357-50WVN Start Here Guide. This guide will provide step-by-step instructions and supporting files for designing your first graphical user interface.

UEZGUI-4357-50WVN Kit Contents

- 5.0"PCAP Touch Screen LCD GUI Production Module (Part number: UEZGUI-4357-50WVN-BA)
- SEGGER J-LinkTM
- 9 Pin Samtec Cable Lite Cortex-M JTAG Debugger
- (2) USB Type A to USB Type Mini-B USB Cables
- Universal A/C to 5V USB Power Supply

Also Included:

- Industrial microSDHC card
- Expansion board for µEZ GUI with 70-pin breakout and optional RS232.
  Note: The 4-bit microSD card slot is not designed for this µEZ GUI. (Part Number: UEZGUI-EXP-BRKOUT)
- 20 Pin Flex Cable
- 50 Pin Flex Cable

Documents / Resources

	FDI UEZGUI-4357-50WVN-BA 5.0 Pcap Touch Screen LCD GUI Development Kit [pdf] Instruction Manual UEZGUI-4357-50WVN-BA 5.0 Pcap Touch Screen LCD GUI Development Kit, UEZGUI-4357-50WVN-BA, 5.0 Pcap Touch Screen LCD GUI Development Kit, Screen LCD GUI Development Kit, GUI Development Kit, Development Kit

References

- **User Manual**