

FEITIAN

**F600
Android
Payment
PAD**



FEITIAN F600 Android Payment PAD Instruction Manual

[Home](#) » [Feitian](#) » FEITIAN F600 Android Payment PAD Instruction Manual 

Contents

- [1 FEITIAN F600 Android Payment PAD](#)
- [2 Product Introduction](#)
- [3 Product Appearance](#)
- [4 Specifications](#)
- [5 Battery and Power Source](#)
- [6 Features](#)
- [7 Certifications](#)
- [8 Installation](#)
- [9 FCC Statement](#)
- [10 Frequently Asked Questions](#)
- [11 Documents / Resources](#)
 - [11.1 References](#)
- [12 Related Posts](#)

FEITIAN

FEITIAN F600 Android Payment PAD



Product Appearance

The F600 features a stylish and portable design suitable for mobile use.

Screen

8-inch screen with 1280*800 resolution and Capacitive Touch Panel.

Communication Interface

- **RF Band:** 4GFDD-LTE:B2/4/5/7, TDD-LTE:B38, 3GWCMA B2/4/5, 2GGSM B2/5
- Type-C USB port for connectivity and charging
- WiFi support for 2.4G/5G network, 802.11a/b/g/n/ac
- Bluetooth 2.1 EDR/3.0 HS/4.2 LE/5.0 LE
- **GPS support:** GPS/BDS/GLONASS/Galileo/QZSS/SBAS, L1
- NFC support for POS function, 13.56MHz, ISO/IEC 14443, ISO18092, Type A&B Felica, Mifare card

Battery and Power Source

Non-removable polymer lithium battery: 3.8V/8000mAh with charge protection and RTC battery.

Audio

- Speaker for audio playback
- Mic for audio recording
- Buzzer for notifications

Camera

- Front Camera: 5M, FF
- Rear Camera: 8M, AF

SIM card

The device supports two micro SIM cards.

PSAM card

The device supports PSAM card insertion.

TF-card

The device supports micro TF card insertion.

Contact IC Card Reader

Supports contact IC card (ISO/IEC 7816, Conform to EMV L1/L2).

Product Usage Instructions**Charging the Device:**

Connect the Type-C USB port to a power source using the provided cable for charging.

Connecting to Bluetooth:

Turn on the Bluetooth feature on your smart phone or tablet and search for the F600 device to pair them.

Processing Payments:

Open the payment application on your connected device and follow the on-screen instructions to complete the payment process using the F600 POS device.

Product Introduction

Feitian F600 is a smart mobile POS product with PCI certification. It has a stylish and smart design. Connect with smart phone or tablet via Bluetooth interface, you can easily and quickly complete the payment process. It can achieve payment progress anytime anywhere which provides end users with a new experience of payment.

This product is developed based on Android 14 operating system, software including android system and secure system, the function is simple and easy to use.

Both android system and secure system can be upgraded remotely or upgraded by OTG+U disk, lower the following cost of development and maintenance.

The features of this product:

Portable

The appearance is portable, suitable for mobile use.

Powerful

Support contact card and contactless card. Support WiFi and Bluetooth.

Support 1* type C Port, support USB2.0 and OTG.

Certified

PCI6, EMV L1&L2, EMV CL L1, Amex, paywave, Paypass, Discover, JCB, Pure, QUICS, TQM(TBD)
DGM&UN38.3&MSDS,PVOC,CE, GSMA, WEEE

Remote upgrading

Firmware can be upgraded remotely, reducing the cost of late development and maintenance.

Product Appearance

The F600 product appearance is shown as follows:



Figure 1 F600 appearance figure

Specifications

1. Dimensions

Size: 251*136*15.8(mm)

2. Screen

Use a 8-inch screen with a resolution of 1280*800 and capcit Capacitive Touch Panel.

3. Communication Interface

- RF Band
 - 4G FDD-LTE:B2/4/5/7
- TDD-LTE:B38
 - 3G WCDMA B2/4/5
 - 2G GSM B2/5
- Type-C USB port

When the device is connected to the host (for example, PC) through this interface, and this interface provides functions such as charging.
- WiFi

This device can be connected to 2.4G/5G network, support 802.11a/ b/ g/ n/ ac.
- Bluetooth 2.1 EDR/ 3.0 HS/ 4.2 LE/ 5.0 LE

This device can be connected to smart phone or bluetooth headset through this interface.
- GPS

This device supports GPS/ BDS/ GLONASS/ Galileo/ QZSS/ SBAS, L1.
- NFC

NFC is a POS function, which supports 13.56MHz,ISO/IEC 14443,ISO18092, Type A&B Felica,Mifare card.

Battery and Power Source

Non removable polymer lithium battery, 3.8V/8000mAh, with charge protection and RTC battery.

1. Audio

- Speaker

This device can play audio through this interface.

- Mic

This device can record through this interface.

- Buzzer

Notify the user by beeping when needed.

2. Camera

- Front Camera

A front camera: 5M,FF

- Rear Camera

A front camera: 8M,AF

SIM card

This device can insert into two micro sim card.

PSAM card

This device can insert into PSAM card.

TF-card

This device can insert into micro TF card.

Contact IC card Reader

Support contact IC card (ISO/IEC 7816,Conform to EMV L1/L2). When inserting the IC card,please let the chip side toward the side of the screen.



Magnetic Stripe Card Reader

The magnetic stripe card must be compliant with ISO/IEC 7811, ISO/IEC 7813 standard. The magnetic strip card reader can read data from magnetic track 1, 2, 3 at the same time, support bi-directional swipe,swipe speed ranges from 10mm/s to 100mm/s. The life cycle is over 400,000 times. The magnetic stripe must be backward when swiping card.



Contactless IC Card Reader

Support contactless IC card (ISO/IEC 14443, ISO18092, Type A&B, Felica, Mifare card, working frequency 13.56MHz)



Features

- Tamper-proof and anti-power-down protection
- Support DUKPT key systems
- RSA AES 3DES SHA-1 SHA-256 Support RSA, AES, 3DES, SHA-1, SHA-256
- Support SM2, SM3, SM4
- Physical tamper-proof has self-destruction function
- Support redevelopment

Certifications

- PCI6
- EMV L1/L2
- EMV CL L1
- Amex
- PayPass
- PayWave
- Discover
- JCB
- PURE
- QUICS
- TQM(TBD)
- DGM
- MSDS
- UN38.3
- CE
- PVOC
- GSMA
- WEEE

Installation

Step 1. Charging the device

- Insert the USB charging cable into the Type-C port on the down side of the device.
- Connect the other end of the USB charging cable into a powered USB socket.
- A charging symbol will appear over the battery symbol in the top right corner of the device during charging.
- Charging of the battery will typically take between 1 and 3 hours, whilst not in use.
- Battery condition is indicated in the display when the device is switched on.
- The terminal is fitted with an internal rechargeable battery which can be removed or replaced. This battery should be charged for at least 1 hours when using the terminal for the first time. It is recommended that the battery is charged to at least 40% of its capacity every 4 months.

Step 2. Turning on the device

- Hold down the power button 2 seconds, the system will start.
- If required, remove the protective film from the display.

Step 3. Mobile payment application

Please follow the instructions provided by your bank or service provider to download the mobile application onto this device.

Step 4. Performing a chip card sale transaction with PIN

- When prompted, insert the customer's chip card into the slot at the right hand side of the device with the chip facing upwards.

- Follow the instructions provided by your bank or service provider to complete the transaction.

Step 5. Performing a contactless transaction

- Transactions may be completed using a contactless card or enabled product. The contactless symbol is display on the screen of the device.
- To read a contactless card it must be positioned in close proximity to the device over the contactless symbol.
- Follow the instructions provided by your bank or service provider to complete the transaction.

Troubleshooting

In the unlikely event you experience issues with this product, please follow the guidelines below. If this does not resolve the issue, please contact your solution provider for further assistance.

No display

- Charge the device with the supplied USB cable.
- Ensure the USB socket being used is powered.

Poor battery life

- Ensure the power is being supplied during charging.
- Check battery charge indicator is at maximum
- Charge for 2 hours to ensure a full charge whilst not in use.

Cannot read Cards

- Ensure the chip card has been inserted in the correct orientation.
- Ensure the contactless card has been placed at a distance of 0 to 4 cm from the device.
- Test with another card of the same type.

Caution and Safety Instructions

- Do not attempt to disassemble, modify, service or repair any part.
- Do not use if damaged or with signs of tampering.
- Only use the device with supplied or manufacturer-certified accessories.
- To avoid the potential hazard of electrical shock do not use in wet environments or during an electrical storm.
- Do not use in proximity of potentially flammable gases or substances.
- Ensure cables used do not cause a trip hazard or risk the device being dropped on to a hard surface.
- Do not expose to excessive heat or cold. Only operate between -10 °C and 50 °C.
- Before cleaning, disconnect from the electrical outlet. Use only a dry or dampened soft cloth.
- Do not immerse, use liquids, sprays or aerosol cleaners. Clean all spillages quickly.
- This device is intended for handheld use only or in an approved cradle/stand.
- Dispose any part in an environmentally sound manner and in accordance with local laws.
- F600 product will not be held liable for any damage resulting from user operation that does not comply with the above-stated guidance.

- If the device will be stored/unused for extended periods of time, then it is imperative that the battery be recharged every six months or sooner to at least 30–40% of maximum charge while the terminal is in 'OFF' position.

Frequency bands and power

- Maximum radio frequency power transmitted in the frequency bands in which this equipment operates is below the limit values specified in the corresponding Harmonized Standards.
- The frequency bands and power limits applicable to this equipment are: Bluetooth: 2.402 GHz – 2.480GHz, 5180~5825 MHz, BT2.1 EDR/ 3.0 HS/ 4.2 LE/ 5.0 LE; NFC: 13.56 MHz, Type-A/B, Felica.

FCC Statement

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

1. This device may not cause harmful interference, and
2. This device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected
- Consult the dealer or an experienced radio/TV technician for help

CAUTION

Risk of explosion if the battery is replaced by an incorrect type; disposal of a battery into fire or a hot oven, or mechanically crushing or cutting of a battery, that can result in an explosion; leaving a battery in an extremely high temperature surrounding environment that can result in an explosion or the leakage of flammable liquid or gas; a battery subjected to extremely low air pressure that may result in an explosion or the leakage of flammable liquid or gas.

Non-compliance with the above restrictions may result in violation of RF exposure guidelines.

SAR statement

This equipment complies with radiation exposure limits set forth for an uncontrolled environment. End user must follow the specific operating instructions for satisfying RF exposure compliance. This transmitter must not be colocated or operating in conjunction with any other antenna or transmitter.

The portable device is designed to meet the requirements for exposure to radio waves established by the FCC. These requirements set a SAR limit of 1.6 W/kg averaged over one gram of tissue. The highest SAR value reported under this standard during product certification for use when properly worn on the body.

Frequently Asked Questions


Q: How can I upgrade the firmware of the F600 remotely?

A: The firmware of the F600 can be upgraded remotely through the provided methods, reducing the cost of development and maintenance.

Q: Can the F600 support contactless card payments?

A: Yes, the F600 supports both contact card and contactless card payments, providing versatility in payment options.

Documents / Resources

	<p>FEITIAN F600 Android Payment PAD [pdf] Instruction Manual ZD3FTF600, ZD3FTF600, ftf600, F600 Android Payment PAD, F600, Android Payment PAD, Payment PAD, PAD</p>
--	---

References

- [FT FEITIAN – Technologies Co., Ltd.](#)
- [FT](#) | [FEITIAN-](#) | | | | [IC](#) | [IC](#) | [IC](#) |
- [User Manual](#)

[Manuals](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.