

FIRSTECH 2WQ9R-SS Car Starter Compustar Keyless Entry System User Guide

[Home](#) » [FIRSTECH](#) » FIRSTECH 2WQ9R-SS Car Starter Compustar Keyless Entry System User Guide 

Contents










- [1 FIRSTECH 2WQ9R-SS Car Starter Compustar Keyless Entry System](#)
- [2 QUICK START](#)
- [3 REMOTE OPTION MENU](#)
- [4 FCC COMPLIANCE](#)
- [5 Documents / Resources](#)
 - [5.1 References](#)
- [6 Related Posts](#)








FIRSTECH 2WQ9R-SS Car Starter Compustar Keyless Entry System



QUICK START

BUTTON	FUNCTION DESCRIPTION
	Tap this icon 1 time to lock and/or arm your system. Double tap this icon to unlock and/or disarm your system. Hold this icon for 2.5 seconds to activate OR cancel the remote start sequence.
	Tap this icon 1 time to wake up the screen and view the system status (Default: Temperature) Tap again to toggle between Temperature/Car Battery/Remote Battery status. Double tap this icon to ENTER remote user option. Use “  /  ” to navigate the user features and a single tap of the “  ” to change the selected feature. Hold this icon for 2.5 seconds to EXIT remote user option.
	Tap this icon 1 time to lock and/or arm your system.
	Hold this icon for 5 seconds to activate “panic” feature.
	Tap this icon 1 time to unlock and/or disarm your system.
	Hold this icon for 2.5 seconds to open the trunk, if equipped. If fails, ask you your Compustar Dealer for details on how to enable this feature.

REMOTE OPTION MENU

FEATURE	LCD READOUT 	FUNCTION / DESCRIPTION
Enter Remote Menu	 “Double Tap”	Enter the Remote Option Menu
Exit Remote Menu	 “Hold for 2.5 sec”	Exit the Remote Option Menu
Move Through Menu	 “Single Tap”	Moves down on the Remote Option Menu
Move Up Menu	 “Single Tap”	Moves up on the Remote Option Menu
Passive Arming	Passive On/Off	Activates “Passive” feature
2 Way Paging Display	Full / Half	Full – Receive all alarm trigger alerts. Half – Receive remote confirmation alerts only.
Valet	Valet On/Off	Enables/Disables the Valet Mode.
Sliding Doors	Sliding Door L/R	Allows you to use the Lock and Unlock icons for sliding doors via Aux 1 and 2.
Auxiliary	AUX mode On/Off	Enables/Disables programmed auxiliary functions (AUX Mode must be on)
Language	English/Francais/Espanol	Changes the language of the remote between English, French, Spanish.
Temperature	Fahrenheit/Celsius	Enables the remote to display vehicle internal temperature in Fahrenheit or Celsius.
Sound	Sound 1/2/3 Vibration	Adjust the volume of your remote or turn the silent mode on.
Screen Saver	Screen timeout 8 sec / 4 sec	Adjusts the time your LCD will stay on after an icon is pressed.

WARNING

It is the responsibility of the vehicle operator to ensure that their vehicle is parked in a safe and responsible manner.

- When leaving the vehicle, it is the user's responsibility to ensure that the gearshift lever is in "Park" in order to avoid accidents upon remote starting. (Note: Make sure that the automatic vehicle cannot start in "Drive".)
- It is the user's responsibility to ensure that the remote starter is disabled or put into valet mode before Servicing.

FCC COMPLIANCE

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- This device may not cause harmful interference.
- This device must accept any interference received, including interference that may cause undesired operation.

CAUTION: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this device.


IC COMPLIANCE

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(S).

Operation is subject to the following two conditions:

- This device may not cause interference.
- This device must accept any interference, including interference that may cause undesired operation of the device.

Documents / Resources

	<p>FIRSTECH 2WQ9R-SS Car Starter Compustar Keyless Entry System [pdf] User Guide RCL300-2WLR, RCL3002WLR, VA5RCL300-2WLR, VA5RCL3002WLR, 2WQ9R-SS, Car Starter Compustar Keyless Entry System, 2WQ9R-SS Car Starter Compustar Keyless Entry System</p>
---	--

References

- [Patents | firstechllc.com](#)