



FLEX AUTOMATION Meter Switch FX-S69A Manual

[Home](#) » [FLEX AUTOMATION](#) » FLEX AUTOMATION Meter Switch FX-S69A Manual 

Contents

- 1 FLEX AUTOMATION
- 2 Meter Switch
 - 2.1 SKU: FX-S69A
 - 2.2 Quickstart
 - 2.3 Important safety information
 - 2.4 What is Z-Wave?
 - 2.5 Product Description
 - 2.6 Prepare for Installation / Reset
 - 2.6.1 Reset to factory default
 - 2.6.2 Safety Warning for Mains Powered Devices
 - 2.7 Inclusion/Exclusion
 - 2.7.1 Inclusion
 - 2.7.2 Exclusion
 - 2.8 Quick trouble shooting
 - 2.9 Association – one device controls an other device
 - 2.9.1 Association Groups:
 - 2.10 Configuration Parameters
 - 2.10.1 Parameter 1: Change the state of indicator light
 - 2.10.2 Parameter 2: Memory function
 - 2.10.3 Parameter 3: Watt Meter Report period
 - 2.10.4 Parameter 4: KWH Meter Report period
 - 2.10.5 Parameter 5: Threshold of Watt for load caution
 - 2.10.6 Parameter 6: Threshold of KWH for load caution
 - 2.11 Technical Data
 - 2.12 Supported Command Classes
 - 2.13 Explanation of Z-Wave specific terms
 - 2.14 Related Posts

FLEX AUTOMATION

Meter Switch

SKU: FX-S69A





Quickstart

This is a

On/Off Power Switch
for
Brazil.

To run this device please connect it to your mains power supply.

To add this device to your network execute the following action:

1. Enter your Z-Wave controller into inclusion mode2. Press the socket on/off button three times within 1.5 seconds to be included.

Please refer to the
[Manufacturers Manual](#) for more information.

Important safety information

Please read this manual carefully. Failure to follow the recommendations in this manual may be dangerous or may violate the law.

The manufacturer, importer, distributor and seller shall not be liable for any loss or damage resulting from failure to comply with the instructions in this manual or any other material.

Use this equipment only for its intended purpose. Follow the disposal instructions.

Do not dispose of electronic equipment or batteries in a fire or near open heat sources.

What is Z-Wave?

Z-Wave is the international wireless protocol for communication in the Smart Home. This device is suited for use in the region mentioned in the Quickstart section.

Z-Wave ensures a reliable communication by reconfirming every message (**two-way communication**) and every mains powered node can act as a repeater for other nodes (**meshed network**) in case the receiver is not in direct wireless range of the transmitter.



This device and every other certified Z-Wave device can be **used together with any other certified Z-Wave device regardless of brand and origin** as long as both are suited for the same frequency range.

If a device supports **secure communication** it will communicate with other devices secure as long as this device provides the same or a higher level of security. Otherwise it will automatically turn into a lower level of security to maintain backward compatibility.

For more information about Z-Wave technology, devices, white papers etc. please refer to www.z-wave.info.

Product Description

This smart energy plug is able to detect current wattage (5-3000W) and overload wattage (3010-3300W) of connected lights or appliances. When detecting overload state, the switch will be disabled and its on/off button will be lockout of which LED will flash quickly. However, unplug and re-connect the switch and it will reset its overload condition to normal status.

Prepare for Installation / Reset

Please read the user manual before installing the product.

In order to include (add) a Z-Wave device to a network it **must be in factory default state**. Please make sure to reset the device into factory default. You can do this by performing an Exclusion operation as described below in the manual. Every Z-Wave controller is able to perform this operation however it is recommended to use the primary controller of the previous network to make sure the very device is excluded properly from this network.

Reset to factory default

This device also allows to be reset without any involvement of a Z-Wave controller. This procedure should only be used when the primary controller is inoperable.

1. To reset, press the socket on/off button three times within 1.5 seconds
2. then the fourth time, press and hold for seconds until the socket LED is off
3. the socket reset successfully
Use the "Reset" procedure only in the event that

the network primary controller is missing or otherwise inoperable

Safety Warning for Mains Powered Devices

ATTENTION: only authorized technicians under consideration of the country-specific installation guidelines/norms may do works with mains power. Prior to the assembly of the product, the voltage network has to be switched off and ensured against re-switching.

Inclusion/Exclusion

On factory default the device does not belong to any Z-Wave network. The device needs to be **added to an existing wireless network** to communicate with the devices of this network. This process is called **Inclusion**.

Devices can also be removed from a network. This process is called **Exclusion**. Both processes are initiated by the primary controller of the Z-Wave network. This controller is turned into exclusion respective inclusion mode. Inclusion and Exclusion is then performed doing a special manual action right on the device.

Inclusion

1. Enter your Z-Wave controller into inclusion mode
2. Press the socket on/off button three times within 1.5 seconds to be included.

Exclusion

1. Enter your Z-Wave controller into exclusion mode
2. Press the socket on/off button three times within 1.5 seconds to be excluded.

Quick trouble shooting

Here are a few hints for network installation if things dont work as expected.

1. Make sure a device is in factory reset state before including. In doubt exclude before include.
2. If inclusion still fails, check if both devices use the same frequency.
3. Remove all dead devices from associations. Otherwise you will see severe delays.
4. Never use sleeping battery devices without a central controller.
5. Dont poll FLIRS devices.
6. Make sure to have enough mains powered device to benefit from the meshing

Association – one device controls an other device

Z-Wave devices control other Z-Wave devices. The relationship between one device controlling another device is called association. In order to control a different device, the controlling device needs to maintain a list of devices that will receive controlling commands. These lists are called association groups and they are always related to certain events (e.g. button pressed, sensor triggers, ...). In case the event happens all devices stored in the respective association group will receive the same wireless command wireless command, typically a 'Basic Set' Command.

Association Groups:

Group NumberMaximum NodesDescription

1	5	It can be associated by other devicesProfile: general lifeline(Profile MSB=0, profile LSB=1)Group 1: lifeline
---	---	----------------------------------------------------------------------------------------------------------------

Configuration Parameters

Z-Wave products are supposed to work out of the box after inclusion, however certain configuration can adapt the function better to user needs or unlock further enhanced features.

IMPORTANT: Controllers may only allow configuring signed values. In order to set values in the range 128 ... 255 the value sent in the application shall be the desired value minus 256. For example: To set a parameter to 200 it may be needed to set a value of 200 minus 256 = minus 56. In case of a two byte value the same logic applies: Values greater than 32768 may needed to be given as negative values too.

Parameter 1: Change the state of indicator light

Default status of socketLED is on as indicator when the load is off

Size: 1 Byte, Default Value: 1

SettingDescription

0 – 1	1 means night light mode, 0 means turn off the night light mode
-------	-----------------------------------------------------------------

Parameter 2: Memory function

Default with memory: the socket status is same as before when power on

Size: 1 Byte, Default Value: 1

SettingDescription

0 – 1	0 means no memory function, 1 means memory function
-------	-----------------------------------------------------

Parameter 3: Watt Meter Report period

Watt Meter Report period

Size: 2 Byte, Default Value: 720

SettingDescription

1 – 32767	Watt Meter Report period
-----------	--------------------------

Parameter 4: KWH Meter Report period

KWH Meter Report period

Size: 2 Byte, Default Value: 6

SettingDescription

1 – 32767	KWH Meter Report period
-----------	-------------------------

Parameter 5: Threshold of Watt for load caution

Threshold of Watt for load caution

Size: 2 Byte, Default Value: 3000

SettingDescription

10 – 3000	Threshold of Watt for load caution
-----------	------------------------------------

Parameter 6: Threshold of KWH for load caution

Threshold of KWHfor load caution

Size: 2 Byte, Default Value: 10000

SettingDescription

1 – 10000	Threshold of KWH for load caution
-----------	-----------------------------------

Technical Data

Hardware Platform	ZM5202
Device Type	On/Off Power Switch
Network Operation	Always On Slave
Firmware Version	HW: 1 FW: 2.00
Z-Wave Version	6.51.06
Certification ID	ZC10-17055612
Z-Wave Product Id	0x004F.0x0004.0x0002
Supported Meter Type	Electric Energy
Color	White
Frequency	XXfrequency
Maximum transmission power	XXantenna

Supported Command Classes

- Association Grp Info
- Association V2
- Basic
- Configuration
- Device Reset Locally
- Firmware Update Md V2
- Manufacturer Specific V2
- Meter V3
- Powerlevel
- Switch All
- Switch Binary
- Version V2
- Zwaveplus Info V2

Explanation of Z-Wave specific terms

- **Controller** — is a Z-Wave device with capabilities to manage the network.
Controllers are typically Gateways,Remote Controls or battery operated wall controllers.
- **Slave** — is a Z-Wave device without capabilities to manage the network.

Slaves can be sensors, actuators and even remote controls.

- **Primary Controller** — is the central organizer of the network. It must be a controller. There can be only one primary controller in a Z-Wave network.
- **Inclusion** — is the process of adding new Z-Wave devices into a network.
- **Exclusion** — is the process of removing Z-Wave devices from the network.
- **Association** — is a control relationship between a controlling device and a controlled device.
- **Wakeup Notification** — is a special wireless message issued by a Z-Wave device to announce that it is able to communicate.
- **Node Information Frame** — is a special wireless message issued by a Z-Wave device to announce its capabilities and functions.