



## Fluidmaster PRO1000A-037 Universal Side Entry Cistern with Link and Seat User Manual

[Home](#) » [FLUIDMASTER](#) » Fluidmaster PRO1000A-037 Universal Side Entry Cistern with Link and Seat User Manual 

### Contents

- [1 Fluidmaster PRO1000A-037 Universal Side Entry Cistern with Link and Seat](#)
- [2 Product Information](#)
- [3 Product Usage Instructions](#)
- [4 INSTALL WITH CONFIDENCE](#)
- [5 EQUIPPED WITH FLUIDMASTER TECHNOLOGY](#)
- [6 SPECIFICATIONS](#)
- [7 Documents / Resources](#)
  - [7.1 References](#)



**Fluidmaster PRO1000A-037 Universal Side Entry Cistern with Link and Seat**



## Product Information

The PRO1000A-037 is a universal side-entry cistern with a link and seat. It is equipped with Fluidmaster technology, ensuring a powerful flush system that is adjustable up to 9/4.5L. The cistern is designed for confident installation and meets the AS 1172.2 standards.

The cistern comes with an inlet valve, model PRO75-AU, and an outlet valve, model 560AU02. It has the following specifications:

- SKU: PRO1000A-037-P1
- Case Qty: 1
- Product Dimensions (H/W/D): 391 x 420 x 133 millimeters
- Case Dimensions (H/W/D): 495 x 452 x 212 millimeters
- Case Weight: 5 kilograms
- EAN: 9354172000223

For more information, you can visit the official website at [www.fluidmaster.com.au](http://www.fluidmaster.com.au). If you have any inquiries, you can contact Fluidmaster Australia Holdings Pty Ltd. at +61 (03) 8870 2555 or via email at [salesau@fluidmaster.com](mailto:salesau@fluidmaster.com).

## Product Usage Instructions

To install the PRO1000A-037 universal side-entry cistern, follow these steps:

1. Ensure the water supply to the cistern is turned off.
2. Remove any existing cistern components if necessary.
3. Position the cistern in the desired location, making sure it is level and secure.
4. Connect the inlet valve (PRO75-AU) to the water supply using the provided fittings.
5. Connect the outlet valve (560AU02) to the toilet bowl using the appropriate connectors.
6. Adjust the flush system to the desired flush volume. The PRO1000A-037 is adjustable up to 9/4.5L.
7. Turn on the water supply and check for any leaks or abnormalities.
8. Once everything is functioning correctly, attach the link and seat to the cistern.
9. Test the flush system by flushing the toilet multiple times to ensure proper operation.

For further assistance or troubleshooting, refer to the user manual or contact Fluidmaster Australia Holdings Pty Ltd.

## INSTALL WITH CONFIDENCE

- Universal Side-Entry Inlet
- Full Range Flush Pipe Kit Included
- 4.5/3L Dual Flush Technology
- Simple Flush Volume Conversion to 6/3L or 9/4.5L
- UV Resistant Certified – Plastic Cistern
- Saves Water with Superior Performance

## EQUIPPED WITH FLUIDMASTER TECHNOLOGY



## SPECIFICATIONS


SPECIFICATIONS			Case Pack		
SKU	Case Qty	Product Dimensions H/W/D (Millimet ers)	Case Dimensions H/W/D (Millimet ers)	Case Wei ght (Kgs)	EAN
PRO1000A-037 -P1	1	391 x 420 x 133	495 x 452 x 212	5	9354172000223

[www.Fluidmaster.com.au](http://www.Fluidmaster.com.au)

Fluidmaster Australia Holdings Pty Ltd.  
6/100 New Street, Ringwood, Victoria 3134 Australia  
+61 (03) 8870 2555 | Toll Free: 1 800 931 166  
Email: [salesau@fluidmaster.com](mailto:salesau@fluidmaster.com)

© 2020 Fluidmaster, Inc.  
® Registered trademark of Fluidmaster, Inc.  
FM91723, GRev1, 10/2022

## Documents / Resources

	<p><a href="#">Fluidmaster PRO1000A-037 Universal Side Entry Cistern with Link and Seat</a> [pdf] User Manual</p> <p>PRO1000A-037 Universal Side Entry Cistern with Link and Seat, PRO1000A-037, Universal Side Entry Cistern with Link and Seat, Cistern with Link and Seat, and Seat</p>
---	--

## References

- [Toilet Cisterns | Inlet & Outlet Toilet Valves | Fluidmaster Australia](#)

Manuals+.