


FN-Link®
6220T-IF WiFi Dual
Band Combo
Module



FN-LINK 6220T-IF WiFi Dual Band Combo Module Instruction Manual


[Home](#) » [Fn-Link](#) » FN-LINK 6220T-IF WiFi Dual Band Combo Module Instruction Manual 

Contents

- [1 FN-LINK 6220T-IF WiFi Dual Band Combo Module](#)
- [2 Product Usage Instructions](#)
- [3 FAQ](#)
- [4 General Description](#)
- [5 Features](#)
- [6 Block Diagram](#)
- [7 General Specification](#)
- [8 Pin Definition](#)
- [9 Size reference](#)
- [10 Layout Recommendation](#)
- [11 Reference Design](#)
- [12 Package](#)
- [13 FCC STATEMENT](#)
- [14 CONTACT](#)
- [15 Documents / Resources](#)
 - [15.1 References](#)
- [16 Related Posts](#)



FN-LINK 6220T-IF WiFi Dual Band Combo Module



Product Usage Instructions

- To use the 6220T-IF module, follow these steps:
- Insert the module into the host device's interface securely.
- Ensure proper power supply to the module.
- To configure the module for your specific application:
- Refer to the product datasheet for detailed specifications.
- Use the provided interfaces to communicate with the module.

FAQ

- **Q:** What is the operating temperature range of the 6220T-IF module?
- **A:** The operating temperature range is not specified in the manual text provided.
- **Q:** Can the module support both Wi-Fi and Bluetooth simultaneously?
- **A:** Yes, the module supports the co-existence of RF design between Wi-Fi and Bluetooth.

6220T-IF Module Datasheet

Ordering Information	Part NO.	Description
	FG6220TIFX-00	RTL8720DF-VA1-VG,24*16mm 4MB FLASH, UART,USB, SD, S DIO,SPI,I2C

Revision History

Version	Date	Contents of Revision Change	Prepared	Checked	Approved
V1.0	2023/9/5	New version	LXP	ZZQ	QJP

General Description

Introduction

The 6220T-IF is a multi-radio MCU module. With the open CPU architecture, customers can develop advanced applications running on the dual-core 32-bit MCU. The radio provides support for Wi-Fi 802.11 a/b/g/n in the 2.4GHz/5GHz band and BLE 5.0 communications. The rich set of peripherals and high performance make it an ideal choice for smart homes, industrial automation, consumer electronics, etc.

Description

Model Name	6220T-IF
Product Description	Support Wi-Fi/Bluetooth functionalities
Dimension	L x W x H: 24 x 16 x 2.3mm
Host Interface	UART,USB,SD, SDIO ,SPI,I2C....
Operating temperature	-20°C to 85°C
Storage temperature	-55°C to 125°C

Features

General

- RTL8720DF-VT1-CG(named RTL8720DF thereafter)chipset embedded, dual-coreprocessor:KM4upto200MHz,KM0upto20MHz
- KM4 on-chip memory: up to 512KB SRAM
- KM0 on-chip memory: up to 64KB SRAM
- 4MB Flash

WIFI Features

- 802.11a/b/g/n 1x1,2.4GHz&5GHz
- Center frequency range of operating channel:2412MHz~2484MHz,5180MHz~5825MHz
- Support 20MHz/40MHz bandwidth, up to the data rate of MCS7
- Wi-Fi WEP,WPA,WPA2,WPA3,WPS;open,shared key,and pair-wise key authentication services
- Support low-power Tx/Rx for short-range application
- Frame aggregation for increased MAC efficiency(A-MSDU, A-MPDU)


Bluetooth Features

- Bluetooth LE: Bluetooth5.0
- Speed:125Kbps,500Kbps,1Mbps,and2Mbps
- Support LE secure connections
- Support LE scatternet
- Support 3Master links/1Slavelink
- Co-existence RF design between Wi-Fi and Bluetooth

Peripherals

- 4x UART interface, baud rate upto 6MHz
- 2x I2C,two speed modes:standard up to10Kbps,fast up to 400Kbps
- 2x SDIO Host/SDIO 2.0 Device, clock up to50MHz
- 3x SPI Master/Slave, baud rate up to50MHz
- 1x USB2.0 HS/FS/LS mode
- 11x PWM with configurable duration and duty cycle from 0~100%
- 19x programmable GPIOs
- KM4 and KM0 both have a GDMA controller, each with 6 channels

Block Diagram



General Specification

G RF Specification

Feature	Description		
WLAN Standard	IEEE 802.11 b/g/n Wi-Fi compliant		
Frequency Range	2.400 GHz ~ 2.4835 GHz (2.4 GHz ISM Band)		
Number of Channels	2.4GHz Ch1 ~ Ch14		
Test Items	Typical Value		EVM
Output Power	802.11b /11Mbps : 18dBm \pm 2 dB		EVM \leq -10dB
	802.11g /54Mbps : 17dBm \pm 2 dB		EVM \leq -25dB
	802.11n /MCS7	: 16dBm \pm 2 dB	EVM \leq -28dB
Spectrum Mask	Meet with IEEE standard		
Freq. Tolerance	\pm 20ppm		
SISO Receive Sensitivity (11b,20MHz) @8% PER	– 1Mbps	PER @ -94 dBm	\leq -83 dBm
	– 11Mbps	PER @ -87 dBm	\leq -76 dBm
Receive Sensitivity (11g,20MHz) @10% PER	– 6Mbps	PER @ -89 dBm	\leq -85 dBm
	– 54Mbps	PER @ -75 dBm	\leq -68 dBm
Receive Sensitivity (11n,20MHz) @10% PER	– MCS=0	PER @ -89 dBm	\leq -85 dBm
	– MCS=7	PER @ -72 dBm	\leq -67 dBm
Receive Sensitivity (11n,40MHz) @10% PER	– MCS=0	PER @ -89 dBm	\leq -82 dBm
	– MCS=7	PER @ -70 dBm	\leq -64 dBm
Maximum Input Level	802.11b: -10 dBm		
	802.11g/n: -20 dBm		
Antenna Reference	PCB antenna with 0~2 dBi peak gain		

GHz RF Specification

Feature	Description	
WLAN Standard	IEEE 802.11a/n/, Wi-Fi compliant	
Frequency Range	5.150 GHz ~ 5.850 GHz (5.0 GHz Band)	
Test Items	Typical Value	EVM
Output Power	802.11a 54Mbps: 18 ± 2 dBm	EVM ≤ -25dB
	802.11n MCS7: 17 ±2 dBm	EVM ≤ -28dB
Receive Sensitivity (11a,20MHz) @10% PER	– 6Mbps PER @ -89 dBm, typical	≤-82
	– 54Mbps PER @ -71 dBm, typical	≤-65

Receive Sensitivity (11n,20MHz) @10% PER	– MCS=0 PER @ -89 dBm, typical	≤-82
	– MCS=7 PER @ -69 dBm, typical	≤-64
Receive Sensitivity (11n,40MHz) @10% PER	– MCS=0 PER @ -87 dBm, typical	≤-79
	– MCS=7 PER @ -67 dBm, typical	≤-61
Maximum input level	802.11a/n: -30 dBm	
Antenna Reference	Small antennas with 0~2 dBi peak gain	

Note: The RF specification will be updated in a future version


Bluetooth Specification

Feature	Description		
General Specification			
Bluetooth Standard	Bluetooth V5.0		
Host Interface	UART		
Antenna Reference	Small antennas with 0~2 dBi peak gain		
Frequency Band	2400MHz ~ 2483.5 MHz		
Number of Channels	40 channels		
Modulation	GFSK		
RF Specification			
	Min(dBm)	Typical(dBm)	Max(dBm)
Output Power (Class 1)	3	5	7
Sensitivity @ BLE=30.8% for GFSK (1Mbps)		-90	
Maximum Input Level	GFSK (1Mbps):-20dBm		

Pin Definition

Pin Outline

< TOP VIEW >



Pin Definition details

Pin Name	Pin No.	Type	Description
B_2	1	I/O	GPIOB_2/UART_RXD
B_1	2	I/O	GPIOB_1/UART_TXD
EN	3	I	<ul style="list-style-type: none">● High: Enable the chip.● Low: Module power off.
B_3	4	I/O	GPIOB_3/SWD_CLK
A_8	5	I/O	GPIOA_8/UART_LOG_RXD
A_12	6	I/O	GPIOA_12/SPI_MOSI
A_13	7	I/O	GPIOA_13/SPI_MISO
VCC	8	P	Power Supply
A_14	9	I/O	GPIOA_14/SPI_CLK/UART_RTS
A_15	10	I/O	GPIOA_15/SPI_CS/UART_CTS
A_26	11	I/O	GPIOA_26/HSDP
A_25	12	I/O	GPIOA_25/HSDM
A_27	13	I/O	GPIOA_27/SWD_DAT
A_28	14	I/O	GPIOA_28/RREF
GND	15	P	Ground
B_20	16	I/O	GPIOB_20/SDIO_CMD
A_7	17	I/O	GPIOA_7/UART_LOG_TXD

B_21	18	I/O	GPIOB_21/SDIO_CLK
B_22	19	I/O	GPIOB_22/SDIO_D0
B_23	20	I/O	GPIOB_23/SDIO_D1
B_18	21	I/O	GPIOB_18/SDIO_D2
B_19	22	I/O	GPIOB_19/SDIO_D3

P: POWER I: INPUT O: OUTPUT VDDIO:3.3V

Electrical Specifications


Power Supply DC Characteristics

	Min.	Typ.	Max.	Unit
Operating Temperature	-20	25	85	deg.C
VCC33	3.0	3.3	3.6	V


Size reference

Module Picture

L x W : 24 x16 (±0.2) mm




H: 2.3(±0.1)mm




Weight

TBD

Layout Recommendation




Reference Design



Recommended Reflow Profile


- Referred to IPC/JEDEC standard.
- Peak Temperature: <260°C
- Number of Times: ≤2 times



Package


Reel

- A roll of 840pcs



Carrier Tape Detail

ITEM	W	A0	B0	D	E	F	F1	K0	P0	P2	P	T
DIM	44	16.40	24.40	1.5	1.75	20.2	40.4	2.80	4.0	2.0	24.0	0.30
TOLE	+0.3 -0.3	±0.15	±0.15	+0.1 -0.0	±0.1	±0.15	±0.10	±0.10	±0.1	±0.15	±0.1	±0.05



Packaging Detail

the take-up package



- Using self-adhesive tape
- Size of black tape: 24mm*24.4m the cover tape :21.3mm*32.6m
- Color of plastic disc: blue



NY bag size:450mm*415mm




size : 350*350*35mm



The packing case size:360*210*370mm

Tray

Use pallet packaging for less than 300 pieces



FCC STATEMENT

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions:

1. this device may not cause harmful interference, and
2. this device must accept any interference received, including interference that may cause undesired operation.

Caution: Any changes or modifications to this device not explicitly approved by the manufacturer could void your authority to operate this equipment.

The device has been evaluated to meet general RF exposure requirements. This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance 20cm between the radiator & your body.

Moisture sensitivity

The Modules is a Moisture moisture-sensitive device level 3, under standard IPC/JEDEC J-STD-020, take care all the relatives requirements for using this kind of components.

Moreover, the customer has to take care of the following conditions:

- Calculated shelf life in sealed bag: 12 months at <40°C and <90% relative humidity (RH)
- Environmental condition during the production: 30°C / 60% RH according to IPC/JEDEC J-STD-033A paragraph 5
- The maximum time between the opening of the sealed bag and the reflow process must be 168 hours if condition
- "IPC/JEDEC J-STD-033A paragraph 5.2" is respected
- Baking is required if conditions b) or c) are not respected
- Baking is required if the humidity indicator inside the bag indicates 10% RH or more

Integration instructions for host product manufacturers according to KDB 996369 D03 OEM Manual v01

Conditions on using FN-LINK TECHNOLOGY LIMITED regulatory approvals:

- The customer must ensure that its product (The "CUSTOMER Product") is electrically identical to FN-LINK TECHNOLOGY LIMITED reference designs. Customer acknowledges that any modifications to FN-LINK

TECHNOLOGY LIMITED reference designs may invalidate regulatory approvals about the CUSTOMER Product, or may necessitate notifications to the relevant regulatory authorities.

- The customer is responsible for ensuring that antennas used with the product are of the same type, with same or lower gains as approved and providing antenna reports to FN-LINK TECHNOLOGY LIMITED.
- The customer is responsible for regression testing to accommodate changes to FNLINK TECHNOLOGY LIMITED reference designs, new antennas, and RF exposure safety testing/approvals.
- Appropriate labels must be affixed to the CUSTOMER Product that complies with applicable regulations in all respects.
- A user's manual or instruction manual must be included with the customer product that contains the text as required by applicable law. Without limitation of the foregoing, an example (for illustration purposes only) of possible text to include is set forth below:

List of applicable FCC rules

- FCC Part 15 Subpart C 15.247, FCC Part 15 Subpart E

Specific operational use conditions

- Radio Technology: Bluetooth BLE
- Operation frequency: 2402-2480MHz
- Channel No.: 40 channels
- Data rate: 1Mbps/2Mbps
- Channel Separation: 2MHz
- Modulation: GFSK
- Antenna Type: PCB antenna, max gain 0.64dBi.
- Radio Technology: 2.4G WIFI
- Operation frequency: 2412MHz-2462MHz for IEEE 802.11 b, g, n/HT20
- 2422MHz~2452MHz for IEEE802.11n/HT40
- Channel No.: 802.11b/802.11g /802.11n (HT20): 11, 802.11(HT40): 9
- Modulation type: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK)
- IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)
- IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
- Antenna Type: PCB antenna, max gain 0.64dBi.
- Radio Technology: 5G WIFI
- Operation Frequency: 802.11a/n (HT20): 5180~5240MHz; 5260-5320MHz; 5500-5700MHz; 5745~5825MHz
- 802.11n (HT40): 5190~5230MHz; 5270-5310MHz; 5510-5670MHz;
- 5755~5795MHz
- Channel separation: 20MHz for 802.11a/ 802.11n (HT20)
- 40MHz for 802.11n (HT40)
- Modulation technology: IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
- IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)
- Antenna Type: PCB antenna, max gain 2.63dBi.

The module can be used for mobile applications with a maximum 2.63dBi antenna. The host manufacturer installing this module into their product must ensure that the final composite product complies with the FCC requirements by a technical assessment or evaluation to the FCC rules, including the transmitter operation. The host manufacturer has to be aware not to provide information to the end user regarding how to install or remove this RF module in the user's manual of the end product which integrates this module. The end user manual shall include all required regulatory information/warning as shown in this manual.

Limited module procedures

Not applicable. The module is a Single module and complies with the requirement of FCC Part 15.212.

Trace antenna designs

The antenna used is the PCB antenna on the module.

RF exposure considerations

If RF exposure statement or module layout is changed, then the host product manufacturer is required to take responsibility of the module through a change in FCC ID or a new application. The FCC ID of the module cannot be used on the final product. In these circumstances, the host manufacturer will be responsible for reevaluating the end product (including the transmitter) and obtaining a separate FCC authorization.

Antennas

- Antenna Specification are as follows:
- Antenna Type: PCB antenna
- Antenna Gain(Peak):2.63 dBi (Provided by customer)
- This device is intended only for host manufacturers under the following conditions:
- The transmitter module may not be co-located with any other transmitter or antenna;

As long as the conditions above are met, further transmitter tests will not be required. However, the host manufacturer is still responsible for testing their end product for any additional compliance requirements required with this module installed (for example, digital device emissions, PC peripheral requirements, etc.).

Label and compliance information

Host product manufacturers need to provide a physical or e-label stating "Contains FCC ID: 2AATL-6220T-IF" With their finished product.

Information on test modes and additional testing requirements

- Radio Technology: Bluetooth BLE
- Operation frequency: 2402-2480MHz
- Channel No.: 40 channels
- Data rate: 1Mbps/2Mbps
- Channel Separation: 2MHz
- Modulation: GFSK
- Antenna Type: PCB antenna, max gain 0.64dBi.
- Radio Technology: 2.4G WIFI
- Operation frequency: 2412MHz-2462MHz for IEEE 802.11 b, g, n/HT20
- 2422MHz~2452MHz for IEEE802.11n/HT40
- Channel No.: 802.11b/802.11g /802.11n (HT20): 11, 802.11(HT40): 9
- Modulation type: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK)

- IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)
- IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
- Antenna Type: PCB antenna, max gain 0.64dBi.
- Radio Technology: 5G WIFI
- Operation Frequency: 802.11a/n (HT20): 5180~5240MHz; 5260-5320MHz; 5500-5700MHz; 5745~5825MHz
- 802.11n (HT40): 5190~5230MHz; 5270-5310MHz; 5510-5670MHz; 5755~5795MHz
- Channel separation: 20MHz for 802.11a/ 802.11n (HT20) 40MHz for 802.11n (HT40)

Modulation technology: IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) Antenna Type: PCB antenna, max gain 2.63dBi.

Host manufacturer must perform a test of radiated & conducted emission and spurious emission, according to the actual test modes for a stand-alone modular transmitter in a host, as well as for multiple simultaneously transmitting modules or other transmitters in a host product.

Only when all the test results of test modes comply with FCC requirements, then the end product can be sold legally.

Additional testing, Part 15 Subpart B disclaimer


The modular transmitter is only FCC authorized for FCC Part 15 Subpart C 15.247 and the host product manufacturer is responsible for compliance to any other FCC rules that apply to the host not covered by the modular transmitter grant of certification. If the grantee markets their product as being Part 15 Subpart B compliant (when it also contains unintentional-radiator digital circuitry), then the grantee shall provide a notice stating that the final host product still requires Part 15 Subpart B compliance testing with the modular transmitter installed.

The end user manual shall include all required regulatory information/warning as shown in this manual, including: This product must be installed and operated with a minimum distance of 20 cm between the radiator and the user body.

CONTACT

- Office: 14th floor, Block B, Phoenix Zhigu, Xixiang Street, Baoan District, Shenzhen
- Factory: NO.8, Litong RD., Liuyang Economic & Technical Development Zone, Changsha, CHINA
- TEL:+86-755-2955-8186 Website:www.fn-link.com

Documents / Resources

	<p>FN-LINK 6220T-IF WiFi Dual Band Combo Module [pdf] Instruction Manual</p> <p>6220T-IF, RTL8720DF-VA1-VG, 6220T-IF WiFi Dual Band Combo Module, 6220T-IF Dual Band Combo Module, WiFi Dual Band Combo Module, Dual Band Combo Module, Dual Band Module, Combo Module, Module</p>
---	---

References

- [Wi-Fi Module, BT Module, IoT Module Manufacturer & Supplier - Fn-Link](#)
- [User Manual](#)

[Manuals](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.