FORTINET

FORTINET FBLE-2024TI OEM/Integrators Bluetooth Low Energy Module



FORTINET FBLE-2024TI OEM/Integrators Bluetooth Low Energy Module Installation Guide

Home » FORTINET » FORTINET FBLE-2024TI OEM/Integrators Bluetooth Low Energy Module Installation Guide



Contents

- 1 FORTINET FBLE-2024TI OEM/Integrators Bluetooth Low Energy Module
- 2 Features
- 3 Description
- **4 Important Notice to OEM integrators**
- **5 Antenna Installation**
- **6 The Host Information for FCC**
- 7 Information on test modes and additional testing requirements
- 8 Documents / Resources
 - 8.1 References
- 9 Related Posts

FORTINET

FORTINET FBLE-2024TI OEM/Integrators Bluetooth Low Energy Module

OEM/Integrators Installation Manual

Model name: FBLE-2024TI

Features

- 2.4GHz RF transceiver compatible with Bluetooth® Low Energy and earlier LE Specifications
- Single-ended or differential RF interface

Description

 The device is a 2.4GHz wireless microcontroller (MCU) supporting Bluetooth® 5.3 Low Energy and Proprietary 2.4GHz applications. Bluetooth basic rate use GFSK modulation, where an instantaneous data rate of 125Kbps and 500Kbps,1 and 2 Mbit/s are possible.

Important Notice to OEM integrators

- 1. This module is approved for OEM installation only.
- This module is approved for operation in FORTINET Network Security Gateway, models as described in this filing.
- Additional testing and re-certification will be necessary when the conditions outlined in this OEM installation manual are not fully satisfied.
- 4. The host manufacturer is responsible for additional EMI/EMC testing to verify compliance as a composite system. When testing the host device for compliance with FCC Part 15 Subpart B/ISED ICES-003, the host manufacturer is required to show compliance while all the transmitter module(s) are installed and operating. The modules should be transmitting and the evaluation should confirm that the module's intentional emissions are compliant (i.e. fundamental and out of band emissions). The host manufacturer must verify that there are no additional unintentional emissions other than what is permitted in the rule(s) or emissions are complaint with the transmitter(s) rule(s).
- 5. For RF Exposure requirement: The host manufacturer must verify that the module continues to comply with the RF exposure limits for each host device. Preliminary assessment is normally required to determine if additional certification for RF Exposure is needed.

End Product Labeling

When the module is installed in the host device, the FCC/IC ID label must be visible through a window on the final device or it must be visible when an access panel, door or cover is easily re-moved. If not, a second label must be placed on the outside of the final device that contains the following text: "Contains FCC ID: TVE-110T17";

OEM/Integrators Installation Manual Model name: FBLE-2024TI

Features

- 2.4GHz RF transceiver compatible with Bluetooth® Low Energy and earlier LE Specifications
- · Single-ended or differential RF interface

Description

The device is a 2.4GHz wireless microcontroller (MCU) supporting Bluetooth® 5.3 Low Energy and Proprietary 2.4GHz applications. Bluetooth basic rate use GFSK modulation, where an instantaneous data rate of 125Kbps and 500Kbps,1 and 2 Mbit/s are possible.

Important Notice to OEM integrators

- 1. This module is approved for OEM installation only.
- 2. This module is approved for operation in FORTINET Network Security Gateway, models as described in this filing.
- 3. Additional testing and re-certification will be necessary when the conditions outlined in this OEM installation manual are not fully satisfied.
- 4. The host manufacturer is responsible for additional EMI/EMC testing to verify compliance as a composite

system. When testing the host device for compliance with FCC Part 15 Subpart B/ISED ICES-003, the host manufacturer is required to show compliance while all the transmitter module(s) are installed and operating. The modules should be transmitting and the evaluation should confirm that the module's intentional emissions are compliant (i.e. fundamental and out of band emissions). The host manufacturer must verify that there are no additional unintentional emissions other than what is permitted in the rule(s) or emissions are complaint with the transmitter(s) rule(s).

5. For RF Exposure requirement: The host manufacturer must verify that the module continues to comply with the RF exposure limits for each host device. Preliminary assessment is normally required to determine if additional certification for RF Exposure is needed.

End Product Labeling

When the module is installed in the host device, the FCC/IC ID label must be visible through a window on the final device or it must be visible when an access panel, door or cover is easily re-moved. If not, a second label must be placed on the outside of the final device that contains the following text: "Contains FCC ID: TVE-110T17";

"Contains IC: 7280B-110T17"

The FCC ID/IC ID can be used only when all FCC/IC compliance requirements are met.

Antenna Installation

Only the same or equivalent-type as shown below may be used with this module. Other un-equivalent types of antennas may require additional authorization for operation. The equivalent type means the same type that results in similar in-band and out-of-band radiation patterns.

Antenna type	Monopole
2.4GHz Peak Gain	1.53 dBi
connector type	iPex MHF1

Manual Information to the End User

The end user manual shall include all required regulatory notices as shown in the following section.

Federal Communication Commission regulatory notice:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- 1. This device may not cause harmful interference, and
- 2. this device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

• Consult the dealer or an experienced radio/TV technician for help.

Any changes or modifications not expressly approved by the party responsible for

compliance could void the user's authority to operate this equipment. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment for operation in qualified FORTINET Network Security Gateway device only.

Industry Canada regulatory notice:

This device contains license-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's license-exempt RSS(s). Operation is subject to the following two conditions:

- 1. This device may not cause interference.
- 2. This device must accept any interference, including interference that may cause undesired operation of the device.

CAN ICES-3(B)/ NMB-3(B)

This equipment complies with ISED radiation exposure limits set forth for an uncontrolled environment for operation in qualified FORTINET Network Security Gateway device only.

The Host Information for FCC

Module Model Name: FBLE-2024TI

	Equipment Name: Network Security Gateway Brand Name: FORTINET
	Model Name:
Installed into the Ho	 FortiWiFi 50G-5Gxxxxxxxxxx, FORTIWIFI-50G-5Gxxxxxxxxxx, FWF-50G-5Gxxxxxxxxxxxxx, FortiWiFi 51G-5Gxxxxxxxxxxxx, FORTIWIFI-51G-5Gxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
	Marketing Name:
	 FortiWiFi 50G-5G, FortiWiFi 51G-5G, FortiGate 50G-5G, FortiGate 51G-5G FortiWiFi 50G-DSL, FortiGate 50G-DSL, FortiWiFi 50G, FortiWiFi 51G, FortiWiFi 50 G-SFP, FortiWiFi 51G-SFP, FortiGate 50G, FortiGate 51G, FortiGate 50G-SFP, FortiGate 51G-SFP, FortiGate 50 G-SFP-POE, FortiGate 51G-SFP-POE
General Specs	Bluetooth-LE
Antenna Type	Monopole

Module Model Name: FBLE-2024TI				
	Equipment Name: Network Security Gateway Brand Name: FORTINET			
	Model Name:			
	FWF-50G-5G, FWF-51G-5G, FG-50G-5G, FG-51G-5G, FG-50G-DSL, FWF-50G-DSL			
	FWF-50G, FWF-51G, FWF-50G-SFP, FWF-51G-SFP, FG-50G, FG-51G, FG-50G-SFP FG-51G-SFP,			
	FG-50G-SFP-POE, FG-51G-SFP-POE			
Installed into the Ho				
	Marketing Name			
	FortiWiFi 50G-5G, FortiWiFi 51G-5G, FortiGate 50G-5G, FortiGate 51G-5G, FortiWiFi 5 0G-DSL, FortiGate 50G-DSL,			
	FortiWiFi 50G, FortiWiFi 51G, FortiWiFi 50G-SFP, FortiWiFi 51G-SFP, FortiGate 50G, FortiGate 51G, FortiGate 50G-SFP, FortiGate 51G-SFP,			
	FortiGate 50G-SFP-POE, FortiGate 51G-SFP-POE			
General Specs	Bluetooth-LE			
Antenna Type	Monopole			

Information on test modes and additional testing requirements

This module does not contain shielding, and each host integration is required to comply with a Class II Permissive Change. In addition to RF exposure evaluation based on the exposure conditions and the co-located transmitters, RF/EMC evaluation needs to be performed as detailed in the table below.

	FCC Rule Part	EUT TX configuration	Remark
AC conducted e mission	15.207	Bluetooth-LE Link, with AC Adapter	
Conducted Pow er	15.247(b)	BLE Tx CH00 (low channel)_2402 MHz BLE T x CH19 (middle channel)_2440 MHz BLE Tx CH39 (high channel)_2480 MHz	In addition to comply with 15.2 47(b), the result should be also within 7.8 dBm which is li sted on the original grant
Conducted out- of-band (Band-e dge)	15.247(d)	BLE Tx CH00 (low channel)_2402 MHz_500 Kbps BLE Tx CH39 (high channel)_2480 MHz _500 Kbps	
Radiated out-of- band (Band-edg e)	15.205 15.209	BLE Tx CH00 (low channel)_2402 MHz_500 Kbps BLE Tx CH39 (high channel)_2480 MHz _500 Kbps	
Radiated unwan ted emission	15.205 15.209	BLE Tx CH39 (high channel)_2480 MHz_500 Kbps	

Additional Test when there is other co-located transmitter which can transmit simultaneously

	FCC Rule Part	EUT TX configuration	Remark
Radiated unwan ted emission	15.205 15.209	This module: Bluetooth Tx CH39 (high channel)_2480 M Hz_500 Kbps Other transmitters: the mode which results in the worst emission, from the test reports of FCC equipment author ization	Radiated spurious emission (RSE) test should also investig ate the FCC rule parts applica ble to the other co-located tran smitter(s)

How to make changes

Only Grantees are permitted to make permissive changes. Please contact us if the host integrator expects the module to be used differently than as granted:

Company Name: Fortinet, Inc. Company Address: 899 KIFER RD SUNNYVALE CA 94086 UNITED STATES

Tel. no.: 408-235-7700

Documents / Resources



FORTINET FBLE-2024TI OEM/Integrators Bluetooth Low Energy Module [pdf] Installation

TVE-110T17, TVE110T17, 110t17, FBLE-2024TI OEM Integrators Bluetooth Low Energy Module, FBLE-2024TI Bluetooth Low Energy Module, OEM Bluetooth Low Energy Module, Integrators Bluetooth Low Energy Module, FBLE-2024TI, Bluetooth Low Energy Module, Bluetooth Module, Low Energy Module, Module

References

• User Manual

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.