Manuals+ — User Manuals Simplified.

FORUM LIGHTING SXLS38941E LED Floodlight with PIR Sensor

FORUM LIGHTING SXLS38941E LED Floodlight with PIR Sensor Instruction Manual

Contents

STANLEY

FORUM LIGHTING SXLS38941E LED Floodlight with PIR Sensor

SPECIFICATIONS

- Die-cast aluminium with frosted polycarbonate diffuser
- Pre wired with 500mm cable
- Adjustable timer, LUX and sensitivity
- Horizontal & Vertical adjustment on bracket
- 25,000 hours lifetime

| PIR Sensor | IP54 Rated | 0.5M Cable | 6500K DW | Class 1 |

Code	Description	Power (w)	Total Flux (lm)	Weight	Dimensions
SXLS38941E		10W LED	700	0.25kg	H:160mm W:105mm Proj:78mm
SXLS38942E SXLS38943E SXLS38944E	Die-cast LED Flood light with PIR Sensor	20W LED 30W LED 50W LED	1400 2100 3500	0.42kg 0.57kg 0.78kg	H:185mm W:130mm Proj:78mm H:215mm W:165mm Proj:78mm H:240mm W:200mm Proj:78mm

Documents / Resources

FORUM LIGHTING SXLS38941E LED Floodlight with PIR Sensor [pdf] Instruction Manual SXLS38941E, SXLS38942E, SXLS38943E, SXLS38944E, SXLS38941E LED Floodlight with PIR Sensor, LED Floodlight with PIR Sensor, Floodlight with PIR Sensor, PIR Sensor, Sensor

References

- **User Manual**