



FPG 4000 Series
800 in
Counter/Square
Ambient



FPG 4000 Series 800 in Counter/Square Ambient Owner's Manual

[Home](#) » [FPG](#) » FPG 4000 Series 800 in Counter/Square Ambient Owner's Manual 

Contents

- [1 FPG 4000 Series 800 in Counter/Square Ambient](#)
- [2 Product Usage Instructions](#)
- [3 Dimension](#)
- [4 FEATURES](#)
- [5 OPTIONS & ACCESSORIES](#)
- [6 Installation note](#)
- [7 Documents / Resources](#)
 - [7.1 References](#)
- [8 Related Posts](#)



FPG 4000 Series 800 in Counter/Square Ambient



Specifications

- Model: 4000 SERIES 800
- Type: In-counter/Square Ambient Range
- Installation Dimensions: 996mm (Height) x 803mm (Width) x 778mm (Depth)
- Core Product Temperature: Ambient
- Construction: Stainless steel frame, toughened safety glass, double-glazed end panels
- Options: Fixed Front or Sliding Doors Ambient Display
- Electrical Data: 220-240 V, Single Phase, 0.23 A, 1.2 kWh per hour (average)
- LED Lighting: 50,000 hours, 2758 lumens per metre, Natural color
- Capacity: Display Area of 1.4 m², 3 Shelves + Base
- Chassis Construction: Stainless 304 and mild steel

Product Usage Instructions

Installation

1. Ensure the model cutout dimensions: 775 x 755mm benchtop cutout.
2. When installing next to an adjacent Inline 4000 Series refrigerated cabinet, use a thermal divider panel.

Operation

1. Connect the appliance to a suitable power source following electrical data specifications.
2. Place items for display on the shelves according to capacity and access directions.

Maintenance

1. Regularly clean the stainless steel frame and glass panels with appropriate cleaning agents.
2. Check LED lighting functionality periodically and replace if necessary.

Dimension

RANGE	INLINE 4000 SERIES	
TEMPERATURE	AMBIENT	
MODEL	IN-4A08-SQ-FF-IC	IN-4A08-SQ-SD-IC
FRONT	SQUARE/ FIXED FRONT	SQUARE/ SLIDING DOORS
INSTALLATION	IN-COUNTER	
HEIGHT	996mm	
WIDTH	803mm	
DEPTH CORE PRODUCT TEMP ERATURE	778mm AMBIENT	

FEATURES

- High energy efficiency: 0.05 kWh per hour (average)
- Cabinet operating at ambient temperature
- Smart display with toughened safety glass encased in brushed stainless steel frame

Fixed Front or Sliding Doors Ambient Display

- Three tiltable, height-adjustable stainless steel shelves and base are full cabinet width to support maximum display capacity
- 50,000 hour LED lighting system at 2758 lumens per metre in cabinet top and to each shelf
- Unique shelf mounted ticket strip front and rear: 30mm

Operational Excellence

- Sliding doors (staff side) and fixed front or sliding doors options (customer side)
- Constructed from stainless and mild steel for durability with toughened safety glass and double-glazed end panels
- Fan assisted air circulation to mitigate heat build-up
- Designed to be installed into joinery

OPTIONS & ACCESSORIES

Contact a FPG Sales Representative for our full range, including:

- Shelf trays: Toughened safety glass or mild steel. Colour and woodprint options available for steel shelf trays
- Angled base insert
- Branded decals
- Rear door or end glass mirror application

- Forward-facing controls
- Thermal divider panels
- Custom joinery solution

AMBIENT DATA

MODEL	CORE PRODUCT TEMPERATURE
IN-4A08-SQ-XX-IC	Ambient

ELECTRICAL DATA

MODEL	VOLTAGE	PHASE	CURRENT	E24 H(kWh)	kWh per hour (average)	IP RATING	MAINS		LED LIGHTING		
							CONNECTION	CONNECTION PLUG1	HOURS	LUMENS	COLOR
IN-4A08-SQ-XX-IC	220-240 V	Single	0.23 A	1.2	0.05	IP 20	3 metre, 3 core cable	10 amp, 3 pin plug	50,000	2758 per metre	Natural

¹Please advise country to change plug specification.

CAPACITY, ACCESS & CONSTRUCTION





MODEL	DISPLAY AREA	LEVELS	ACCESS FRONT	ACCESS REAR	CHASSIS CONSTRUCTION
IN-4A08-SQ-FF-IC	1.4 m2	3 Shelves + Base	Fixed front	Sliding doors	Stainless 304 and mild steel
IN-4A08-SQ-SD-IC	1.4 m2	3 Shelves + Base	Sliding doors	Sliding doors	Stainless 304 and mild steel

DIMENSIONS

MODEL	H x W x D mm (Uncrated)	MASS (Uncrated)
IN-4A08-SQ-XX-IC	996 x 803 x 778	– kg

Installation note

Model cutout dimensions: IN-4A08-SQ-XX-IC models require 775 x 755mm benchtop cutout (see product manual for installation guide). When installing this cabinet next to an adjacent Inline 4000 Series refrigerated cabinet, please install an Inline 4000 Series thermal divider panel (accessory) between them.



More information including technical data and installation guidelines is available from the Product Manual published on our website.


In line with our policy to continually develop, improve and support our products, Future Products Group Ltd reserves the right to change specifications and design without notice.

Have a question? Please email us at sales@fpgworld.com or visit www.fpgworld.com for full contact details for your region.

12/24 © 2024 Future Products Group Limited

FPGWORLD.COM

Worldwide
contact
details:



FAQ


Q: Can I change the plug specification for different countries?

A: Yes, please advise your country for plug specification changes.

Q: Where can I find more technical data and installation guidelines?

A: More information is available in the Product Manual published on our website at www.fpgworld.com.

Documents / Resources

	<p>FPG 4000 Series 800 in Counter/Square Ambient [pdf] Owner's Manual IN-4A08-SQ-FF-IC, IN-4A08-SQ-SD-IC, IN-4A08-SQ-XX-IC, 4000 Series 800 in Counter Square Ambient, 4000 Series, 800 in Counter Square Ambient, in Counter Square Ambient, Square Ambient, Ambient</p>
---	---

References

-  [Home - FPG | Food Display Solutions](#)
- [User Manual](#)

Manuals+ Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.