



## FPG Inline 3000 Series Heated Hot Food Display Owner's Manual

[Home](#) » [FPG](#) » FPG Inline 3000 Series Heated Hot Food Display Owner's Manual 



**Showing :** Inline 3000 Series heated 1500mm curved in-counter fixed front





## Contents

- 1 3000 Series Heated Hot Food Display
- 2 FEATURES
- 3 Operational Excellence
- 4 Documents / Resources
  - 4.1 References

## 3000 Series Heated Hot Food Display

RANGE	INLINE 3000 SERIES	
TEMPERATURE	HEATED	
MODEL	IN-3H15-CU-FF-IC	IN-3H15-CU-SD-IC
FRONT	CURVED/ FIXED FRONT	CURVED/ SLIDING DOORS
INSTALLATION	IN-COUNTER	
HEIGHT	761mm	
WIDTH	1503mm	
DEPTH	663mm	
TEMPERATURE RANGE	+30°C – +90°C	
RECOMMENDED CORE PRODUCT TEMPERATURE	+65°C – +80°C	
ENVIRONMENTAL TEST CONDITIONS	22°C / 65% RH	

## FEATURES

-  High energy efficiency: 1.3 kWh per hour (average)
  -  cabinet operating temperature range +30°C – +90°C  
Recommended core product temperature +65°C – +80°C
  - Smartdisplay with toughened safety glass encased in brushed stainless steel frame:
- ### Fixed Front or Sliding Doors Heated Display
-  Three tittable, height-adjustable stainless steel wire rack shelves are full cabinet width to support maximum display capacity
  -  25000 hour LED lighting system at 2758 lumens per metre in cabinet top
    - Unique shelf mounted ticket strip front and rear: 30mm
    - Bxtrusion at the top of the cabinet – front only – is fitted with a stainless steel panel that can be replaced with a branded insert

## Operational Excellence

-  Sliding doors (staff side) and fixed front or sliding doors options (customer side)



Constructed from stainless and mild steel with toughened safety glass and double-glazed end panels for maximum energy efficiency, climate control and durability



Low wattage density element provides even temperature distribution

- Designed to be installed into joinery

## OPTIONS & ACCESSORIES

Contact a FPG Sales Representative for our full range, including

- Shelf trays: Toughened safety glass or mild steel Colour and woodprint options available for steel shelf trays
- Stainless steel product trays with sides
- Stainless steel pie chutes
- Additional shelf
- Ticket strip to base: 30mm
- 25,000 hour LED lighting to shelves
- Branded decals/insert
- Rear door or end glass mirror application
- Forward-facing controls
- Custom joinery solution

## HEATED DATA

MODEL	TEMPERATURE RANGE	RECOMMENDED CORE PRODUCT TEMPERATURE	ENVIRONMENTAL TEST CONDITIONS	HEATING
IN-3H15-CU-XX-IC	+30°C – +90°C	+65°C – +80°C	22°C / 65% RH	Low wattage density element

## ELECTRICAL DATA

MODEL	VOLTAGE	PHASE	CURRENT	E24 H (kW h)	kWh per hour (average)	IP RATING	MAINS		LED LIGHTING		
							CONNECTION	CONNECTION PLUG <sup>1</sup>	HOURS	LUMENS	COLOR
IN-3H15-CU-XX-IC	220-240 V	Single	7.7 A	31.2	1.3	IP 20	3 metre, 3 core cable	10 amp, 3 pin plug	25,000	2758 per metre	Natural

<sup>1</sup> Please advise country to change plug specification.

## CAPACITY, ACCESS & CONSTRUCTION


MODEL	DISPLAY AREA	LEVELS	ACCESS FRONT	ACCESS REAR	CHASSIS CONSTRUCTION
IN-3H15-CU-FF-IC	1.2 m2	3 Shelves	Fixed front	Sliding doors	Stainless 304 and mild steel
IN-3H15-CU-SD-IC	1.2 m2	3 Shelves	Sliding doors	Sliding doors	Stainless 304 and mild steel

### DIMENSIONS

Crated weights and dimensions vary. Please contact us for information on your shipment.

**Installation note;**

Model cutout dimensions: IN-3H15-CU-XX-IC models require 1480 x 645mm benchtop cutout (see product manual for installation guide).



More information including technical data and installation guidelines is available from the Product Manual published on our website.

In line with our policy to continually develop, improve and support our products, Future Products Group Ltd reserves the right to change specifications and design without notice.

Have a question? Please email us at [sales@fpgworld.com](mailto:sales@fpgworld.com) or visit [www.fpgworld.com](http://www.fpgworld.com) for full contact details for your region.

12/24 © 2024 Future Products Group Limited




Worldwide contact details:  
<https://fpgworld.com/FPG-Global-Locations-Contact>



Please contact FPG to discuss your requirements for meeting country-specific standards.  
[FPGWORLD.COM](http://FPGWORLD.COM)

## Documents / Resources

	<p><a href="#">FPG Inline 3000 Series Heated Hot Food Display</a> [pdf] Owner's Manual Inline 3000 Series, Inline 3000 Series Heated Hot Food Display, Heated Hot Food Display, Food Display, Display</p>
---	---

## References

-  [Home - FPG | Food Display Solutions](#)
- [User Manual](#)

### Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.