

FPG
INLINE 3000
Series On-
Counter Curved
Heated Display



FPG INLINE 3000 Series On-Counter Curved Heated Display Owner's Manual

[Home](#) » [FPG](#) » FPG INLINE 3000 Series On-Counter Curved Heated Display Owner's Manual 

Contents

- [1 FPG INLINE 3000 Series On-Counter Curved Heated Display](#)
- [2 Product Usage Instructions](#)
- [3 FAQs](#)
- [4 SPECIFICATION](#)
- [5 FEATURES](#)
- [6 OVERVIEW](#)
- [7 OPTIONS & ACCESSORIES](#)
- [8 DIMENSIONS](#)
- [9 MORE INFORMATION](#)
- [10 Documents / Resources](#)
 - [10.1 References](#)
- [11 Related Posts](#)



FPG INLINE 3000 Series On-Counter Curved Heated Display



Product Usage Instructions

Installation

1. Place the heated display on a flat, stable counter surface.
2. Ensure proper ventilation around the unit.
3. Connect the appliance to the appropriate power source following electrical guidelines.

Operation

1. Turn on the appliance using the designated power switch.
2. Set the desired temperature range for your products.
3. Load products onto the shelves ensuring even distribution for optimal display.

Cleaning and Maintenance

1. Regularly clean the display using mild soap and water.
2. Inspect and replace any damaged components promptly.
3. Refer to the product manual for detailed maintenance instructions.

FAQs

- **How do I adjust the temperature settings?**

- To adjust the temperature settings, locate the temperature control panel on the appliance and use the designated controls to increase or decrease the temperature as needed.

- **Can I change the plug specification for different countries?**

- Yes, please advise your country when purchasing to change the plug specification accordingly.

SPECIFICATION

RANGE	INLINE 3000 SERIES	
TEMPERATURE	HEATED	
MODEL	IN-3H08-CU-FF-OC	IN-3H08-CU-SD-OC
FRONT	CURVED/ FIXED FRONT	CURVED/ SLIDING DOORS
INSTALLATION	ON-COUNTER	
HEIGHT	770mm	
WIDTH	803mm	
DEPTH	663mm	

TEMPERATURE RANGE	+30°C – +90°C
RECOMMENDED CORE PRODUCT TEMPERATURE	+65°C – +80°C
ENVIRONMENTAL TEST CONDITIONS	22°C / 65% RH

FEATURES

- High energy efficiency: 0.63 kWh per hour (average)
- Cabinet operating temperature range +30°C – +90°C Recommended core product temperature +65°C – +80°C
 - Smart display with toughened safety glass encased in brushed stainless steel frame

Fixed Front or Sliding Doors Heated Display

- Three tiltable, height-adjustable stainless steel wire rack shelves are full cabinet width to support maximum display capacity
- 25,000-hour LED lighting system at 2758 lumens per meter in cabinet top
 - Unique shelf-mounted ticket strip front and rear: 30mm
 - Extrusions at the top and bottom of the cabinet – front only – are fitted with stainless steel panels that can be replaced with branded inserts

Operational Excellence

- Sliding doors (staff side) and fixed front or sliding doors options (customer side)
- Constructed from stainless and mild steel with toughened safety glass and double-glazed end panels for maximum energy efficiency, climate control and durability
- Low wattage density element provides even temperature\ distribution
 - Positioned on countertop

OVERVIEW



Showing: Inline 3000 Series heated 800mm curved on-counter fixed front

OPTIONS & ACCESSORIES

Contact a [FPG Sales Representative](#) for our full range, including:

- Shelf trays: Toughened safety glass or mild steel.
- Color and woodprint options available for steel shelf trays
- Stainless steel product trays with sides
- Stainless steel pie chutes
- Additional shelf
- Ticket strip to base: 30mm
- 25,000-hour LED lighting to shelves
- Branded decals/insert
- Rear door or end glass mirror application
- Forward-facing controls
- Custom joinery solution

HEATED DATA

MODEL	TEMPERATURE RANGE	RECOMMENDED CORE PRODUCT TEMPERATURE	ENVIRONMENTAL TEST CONDITIONS	HEATING
IN-3H08-CU-XX-OC	+30°C – +90°C	+65°C – +80°C	22°C / 65% RH	Low wattage density element

ELECTRICAL DATA

MODEL	VOLTAGE	PHASE	CURRENT	E24 H (kW h)	kWh per hour (average)	IP RATING	MAINS		LED LIGHTING		
							CONNECTI ON	CONNECTI ON PLUG1	HOU RS	LUME NS	COL OUR
IN-3H08-CU-XX-OC	220-240 V	Single	3.9 A	15.12	0.63	IP 20	3 meter, 3 core cable	10 amp, 3 pin plug	25,000	2758 per metre	Natural

1Please advise the country to change plug specification.


CAPACITY, ACCESS & CONSTRUCTION

MODEL	DISPLAY AREA	LEVELS	ACCESS FRONT	ACCESS REAR	CHASSIS CONSTRUCTION
IN-3H08-CU-FF-OC	0.62 m2	3 Shelves	Fixed front	Sliding doors	Stainless 304 and mild steel
IN-3H08-CU-SD-OC	0.62 m2	3 Shelves	Sliding doors	Sliding doors	Stainless 304 and mild steel


DIMENSIONS

MODEL	H x W x D mm (Uncrated)	MASS (Uncrated)
IN-3H08-CU-XX-OC	770 x 803 x 663	62 kg


Crated weights and dimensions vary. Please contact us for information on your shipment.




PLAN VIEW



FRONT ELEVATION



SECTION VIEW



REAR ELEVATION

MORE INFORMATION

More information including technical data and installation guidelines is available from the Product Manual published on our website. In line with our policy to continually develop, improve and support our products, Future Products Group Ltd reserves the right to change specifications and design without notice.

- **Have a question?** Please email us at sales@fpgworld.com or visit www.fpgworld.com for full contact details for your region.

Worldwide contact details



Documents / Resources

	<p>FPG INLINE 3000 Series On-Counter Curved Heated Display [pdf] Owner's Manual INLINE 3000 Series, INLINE 3000 Series On-Counter Curved Heated Display, On-Counter Curved Heated Display, Curved Heated Display, Heated Display, Display</p>
--	--

References

-  [Home - FPG | Food Display Solutions](#)
- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.