



FPG INLINE 4000 Series 800 on Counter/Curved Heated Counter Owner's Manual

[Home](#) » [FPG](#) » [FPG INLINE 4000 Series 800 on Counter/Curved Heated Counter Owner's Manual](#) 

FPG INLINE 4000 Series 800 on Counter/Curved
Heated Counter Owner's Manual



INLINE

4000 SERIES 800
ON-COUNTER/CURVED
HEATED

RANGE	INLINE 4000 SERIES	
TEMPERATURE	HEATED	
MODEL	IN-4H08-CU-FF-OC	IN-4H08-CU-SD-OC
FRONT	CURVED/ FIXED FRONT	CURVED/ SLIDING DOORS
INSTALLATION	ON-COUNTER	
HEIGHT	993mm	
WIDTH	803mm	
DEPTH	774mm	

TEMPERATURE RANGE	+30°C - +90°C
RECOMMENDED CORE PRODUCT TEMPERATURE	+65°C - +80°C
ENVIRONMENTAL TEST CONDITIONS	22°C / 65% RH

Contents

- 1 FEATURES
- 2 OPTIONS & ACCESSORIES
- 3 HEATED DATA
- 4 ELECTRICAL DATA
- 5 CAPACITY, ACCESS & CONSTRUCTION
- 6 DIMENSIONS
- 7 Documents / Resources
 - 7.1 References

FEATURES



Showing : Inline 4000 Series heated 800mm curved on-counter with fixed front

High energy efficiency: 0.62 kWh per hour (average)

Cabinet operating temperature range +30°C – +90°C Recommended core product temperature +65°C – +80°C

- Smart display with toughened safety glass encased in brushed stainless steel frame

Fixed Front or Sliding Doors Heated Display

Three tillable, height-adjustable stainless steel wire rack shelves are full cabinet width to support maximum display capacity 25,000 hour LED lighting system at 2758 lumens per metre in cabinet top and shelves

- Unique shelf mounted ticket strip front and rear: 30mm

- Extrusions at the top and bottom of the cabinet – front only are fitted with stainless steel panels that can be replaced with branded inserts

Operational Excellence

Sliding doors (staff side) and fixed front or sliding doors options (customer side)

Constructed from stainless and mild steel with toughened safety glass and double-glazed end panels for maximum energy efficiency, climate control and durability

Low wattage density element provides even temperature distribution

- Positioned on counter top

OPTIONS & ACCESSORIES

Contact a FPG Sales Representative for our full range, including:

- Shelf trays: Toughened safety glass or mild steel. Colour and woodprint options available for steel shelf trays
- Stainless steel product trays with sides
- Stainless steel pie chutes
- Additional shelf
- Ticket strip to base: 30mm
- Branded decals/insert
- Rear door or end glass mirror application
- Forward-facing controls
- Custom joinery solution



Please contact FPG to discuss your requirements for meeting country-specific standards.

HEATED DATA

MODEL	TEMPERATURE RANGE	RECOMMENDED CORE PRODUCT TEMPERATURE	ENVIRONMENTAL TEST CONDITIONS	HEATING
IN-4H08-CU-XX-OC	+30°C - +90°C	+65°C - +80°C	22°C / 65% RH	Low wattage density element

ELECTRICAL DATA

MODEL	VOLTAGE	PHASE	CURRENT	E24H (kWh)	kWh per hour (average)	IP RATING	MAINS		LED LIGHTING		
							CONNECTION	CONNECTION PLUG ¹	HOURS	LUMENS	COLOUR
IN-4H08-CU-XX-OC	220-240 V	Single	6.7 A	14.88	0.62	IP 20	3 metre, 3 core cable	10 amp, 3 pin plug	25,000	2758 per metre	Natural

¹Please advise country to change plug specification.


CAPACITY, ACCESS & CONSTRUCTION

MODEL	DISPLAY AREA	LEVELS	ACCESS FRONT	ACCESS REAR	CHASSIS CONSTRUCTION
IN-4H08-CU-FF-OC	0.8 m ²	3 Shelves	Fixed front	Sliding doors	Stainless 304 and mild steel
IN-4H08-CU-SD-OC	0.8 m ²	3 Shelves	Sliding doors	Sliding doors	Stainless 304 and mild steel


DIMENSIONS

MODEL	H x W x D mm (Uncrated)	MASS (Uncrated)
IN-4H08-CU-XX-OC	993 x 803 x 774	107 kg


Crated weights and dimensions vary. Please contact us for information on your shipment.




PLAN VIEW



FRONT ELEVATION



SECTION VIEW



REAR ELEVATION

More information including technical data and installation guidelines is available from the Product Manual published on our website.

In line with our policy to continually develop, improve and support our products, Future Products Group Ltd reserves the right to change specifications and design without notice.

Have a question? Please email us at sales@fpgworld.com or visit www.fpgworld.com for full contact details for your region.

Worldwide contact details:



FPGWORLD.COM

Documents / Resources



[FPG INLINE 4000 Series 800 on Counter/Curved Heated Counter](#) [pdf] Owner's Manual
IN-4H08-CU-FF-OC, IN-4H08-CU-SD-OC, IN-4H08-CU-XX-OC, INLINE 4000 Series 800 on Co
unter Curved Heated Counter, INLINE 4000 Series, 800 on Counter Curved Heated Counter, on
Counter Curved Heated Counter, Curved Heated Counter, Heated Counter, Counter

References

- [FPG Home - FPG | Food Display Solutions](#)
- [User Manual](#)

Manuals+, [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.