

FPGWORD 4000 Series Ambient 800mm Curved On-Counter Fixed Front Owner's Manual

Home » FPGWORD » FPGWORD 4000 Series Ambient 800mm Curved On-Counter Fixed Front Owner's Manual



FPGWORD 4000 Series Ambient 800mm Curved On-Counter
Fixed Front Owner's Manual



RANGE	INLINE 4000 SERIES				
TEMPERATURE	AMBIENT				
MODEL	IN-4A08-CU-FF-OC	IN-4A08-CU-SD-OC			
FRONT	CURVED/ FIXED FRONT	CURVED/ SLIDING DOORS			
INSTALLATION	ON-COUNTER				
HEIGHT	993mm				
WIDTH	803mm				
DEPTH	774mm				

AMBIENT

Contents

- 1 FEATURES
- **2 OPTIONS & ACCESSORIES**
- **3 AMBIENT DATA**
- **4 ELECTRICAL DATA**
- **5 CAPACITY, ACCESS &**
- **CONSTRUCTION**
- **6 DIMENSIONS**
- 7 Documents / Resources
 - 7.1 References

FEATURES



High energy efficiency: 0.05 kWh per hour (average)

- · Cabinet operating at ambient temperature
- Smart display with toughened safety glass encased in brushed stainless steel frame

Fixed Front or Sliding Doors Ambient Display

Three tiltable, height-adjustable stainless steel shelves and base are full cabinet width to support maximum display capacity 50,000 hour LED lighting system at 2758 lumens per metre in cabinet top and to each shelf

- Unique shelf mounted ticket strip front and rear: 30mm
- Extrusions at the top and bottom of the cabinet front only are fitted with stainless steel panels that can be

Operational Excellence

Sliding doors (staff side) and fixed front or sliding doors options (customer side)

Constructed from stainless and mild steel for durability with toughened safety glass and double-glazed end panels

- Fan assisted air circulation to mitigate heat build-up
- Positioned on counter top

Showing: Inline 4000 Series ambient 800mm curved on-counter fixed front

OPTIONS & ACCESSORIES

Contact a FPG Sales Representative for our full range, including:

- Shelf trays: Toughened safety glass or mild steel. Colour and woodprint options available for steel shelf trays
- · Angled base insert
- · Branded decals/inserts
- Rear door or end glass mirror application
- · Forward-facing controls
- Thermal divider panels
- · Custom joinery solution



Please contact FPG to discuss your requirements for meeting country-specific standards.

AMBIENT DATA

MODEL	CORE PRODUCT TEMPERATURE
IN-4A08-CU-XX-OC	Ambient

ELECTRICAL DATA

MODEL VOLTAG	VOLTAGE	VOLTAGE PHASE C		E24H		IP RATING	MAINS		LED LIGHTING		
	VOLIAGE			(kWh)			CONNECTION	CONNECTION PLUG ¹	HOURS	LUMENS	COLOUR
IN-4A08-CU-XX-OC	220-240 V	Single	0.21 A	1.2	0.05	IP 20	3 metre, 3 core cable	10 amp, 3 pin plug	50,000	2758 per metre	Natural

¹Please advise country to change plug specification.

CAPACITY, ACCESS & CONSTRUCTION

MODEL	DISPLAY AREA	LEVELS	ACCESS FRONT	ACCESS REAR	CHASSIS CONSTRUCTION
IN-4A08-CU-FF-OC	1.3 m ²	3 Shelves + Base	Fixed front	Sliding doors	Stainless 304 and mild steel
IN-4A08-CU-SD-OC	1,3 m ²	3 Shelves + Base	Sliding doors	Sliding doors	Stainless 304 and mild steel


DIMENSIONS

MODEL	H x W x D mm (Uncrated)	MASS (Uncrated)	
IN-4A08-CU-XX-OC	993 x 803 x 774	- kg	

Crated weights and dimensions vary. Please contact us for information on your shipment.

Installation note;

When installing this cabinet next to an adjacent Inline 4000 Series refrigerated cabinet, please install an Inline 4000 Series thermal divider panel (accessory) between them.



More information including technical data and installation guidelines is available from the Product Manual published on our website.

In line with our policy to continually develop, improve and support our products, Future Products Group Ltd reserves the right to change specifications and design without notice.

Have a question? Please email us at <u>sales@fpgworld.com</u> or visit <u>www.fpgworld.com</u> for full contact details for your region.

Worldwide contact details:



FPGWORLD.COM

Documents / Resources



FPGWORD 4000 Series Ambient 800mm Curved On-Counter Fixed Front [pdf] Owner's Manual

4000 Series Ambient 800mm Curved On-Counter Fixed Front, 4000 Series, Ambient 800mm Curved On-Counter Fixed Front, On-Counter Fixed Front, Fixed Front, Front

References

- Home FPG | Food Display Solutions
- User Manual

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.