

Fujian FCS950U WiFi and Bluetooth Module



# Fujian FCS950U WiFi and Bluetooth Module Instruction Manual

[Home](#) » [FUJIAN](#) » Fujian FCS950U WiFi and Bluetooth Module Instruction Manual 

## Contents

- [1 Fujian FCS950U WiFi and Bluetooth Module](#)
- [2 Specifications](#)
- [3 Product Usage Instructions](#)
- [4 FCC](#)
- [5 FAQs](#)
- [6 Documents / Resources](#)
  - [6.1 References](#)
- [7 Related Posts](#)

# Fujian

Fujian FCS950U WiFi and Bluetooth Module



### Wi-Fi 5 & Bluetooth 5.0 Module Ultra-compact LCC Package

ECS95QU is a high-performance 2.4 GHz and 5 GHz Wi-Fi 5 and Bluetooth Low Energy (BLE) module featuring 1T1R in the LCC package. It can be used to establish WLAN and Bluetooth connections. Designed with a reliable SDIO 3.0 interface to provide WLAN capability, it also provides an integrated PA with advanced architecture enhancement to achieve satisfying receiver sensitivity in noisy home scenarios. With an ultra-compact size of 12.0 mm \* 12.0 mm \* 2.15 mm, ECS950U optimizes the size and cost for end-products. ECS95QU supports WEP, WPA, WPA2, WPA3-Personal and WPA3-Enhanced Open, and both single and multiple channel concurrency. Compliant with Bluetooth 5.0, ECS950U provides the concurrent operation of Classic Bluetooth and BLE, supporting LE 2M, LE Advertise Extension, Long Range, AoD Rx Direction Finding, BLE Mesh, multiple piconets and up to 8 concurrent BLE links. Surface-mount Technology (SMT) makes ECS950U an ideal solution for durable and rugged designs. The low profile and small size of LCC package ensure that it can be easily embedded into size-constrained applications and provide reliable connectivity with these applications. The advanced package and the laser-engraved label with better heat dissipation and indelible markings allow for large-scale automated manufacturing which has strict requirements on cost and efficiency. FCS950U can meet Wi-Fi & Bluetooth application design requirements in fields including industry, POS and printing.

### Specifications

- Dual-band Wi-Fi (2.4 GHz and 5 GHz) and Bluetooth 5.0
- SDIO 3.0 interface for high data transmission rate and low power consumption
- IEEE 802.11 a/b/g/n/ac compliant
- Supports WEP, WPA, WPA2, WPA3-Personal, and WPA3-Enhanced Open encryption
- Ultra-compact LCC Package
- Supports multiple piconets and up to 8 concurrent BLE links

### Key Features

- Dual-band 2.4 GHz and 5 GHz Wi-Fi and BLE
- SDIO 3.0 interface that features higher data transmission rate and lower power consumption
- Faster time-to-market: simple design minimizes design-in time and development efforts
- Wide operating temperature range: -40 °C to +85 °C



Ultra-compact Size



LCC Package



IEEE 802.11  
a/b/g/n/ac



SDIO Interface



Operating Temperature  
Range: -40 °C to +85 °C



BLE (Bluetooth 5.0)

Wi-Fi & Bluetooth Module		FCS950U
WLAN Protocol	IEEE 802.11a/b/g/n/ac	
Wi-Fi Frequency Band	2.4 GHz/ 5 GHz	
Wi-Fi Antenna	1 × 1	
Wi-Fi Modulation Mode	DSSS, DBPSK, DQPSK, CCK, BPSK, QPSK, 16QAM, 64QAM, 256QAM	
2.4 GHz Channel Bandwidth	20/ 40 MHz	
5 GHz Channel Bandwidth	20/ 40/ 80 MHz	
Encryption Mode	WPA3	
Wi-Fi Operating Mode	AP/STA	
Bluetooth Protocol	Bluetooth 5.0	
Dimensions	12.0 mm × 12.0 mm × 2.15 mm	
Weight	0.55 g	
Temperature Range		
Operating Temperature Range	-40 °C to +85 °C	
Data Rate (Max.)		
802.11a	54 Mbps	
802.11b	11 Mbps	
802.11g	54 Mbps	
802.11n	150 Mbps	
802.11ac	433 Mbps	
Interfaces		
SDIO 3.0	× 1 (for Wi-Fi)	
PCM	× 1 (for Bluetooth)	
UART	× 1 (for Bluetooth)	
Wi-Fi/Bluetooth Antenna Interface	× 1	
Electrical Features		
Power Supply Voltage	VBAT: 3.2–3.4 V, Typ. 3.3V	
Power Consumption	Max. current at Tx mode: 210 mA @ VBAT	
Certification		
Regulatory	Europe: CE	
	America: FCC	
	Canada: IC	
	Brazil: Anatel	
	China: SRRC	
Wi-Fi Performance	Australia/New Zealand: RCM	
	Maximun Peak Output Power(Conducted)	
2.4 GHz	2414-2462 MHz(802.11b/g/n ht20)	23.54 dBm
	2422-24522 MHz(802.11n ht40)	

Wi-Fi & Bluetooth Module				
Wi-Fi Performance				
			Maximun Average Output Power(Conducted)	
5 GHz	Band1:			
	5180-5240 MHz(802.11a/n ht20/ac vht20)			
	5190-5230 MHz(802.11n ht40/ac vht40)			
	5210 MHz(802.11ac vht80)			
	Band2:			
	5260-5320 MHz (802.11a/n ht20/ac vht20)		16.57 dBm in 5150-5250 MHz Band	
	5270-5310 MHz(802.11n ht40/ac vht40)			
	5290 MHz(802.11ac vht80)		16.86 dBm in 5250-5350 MHz Band	
	Band3:			
	5500-5720 MHz (802.11a/n ht20/ac vht20)		17.15 dBm in 5470-5725 MHz Band	
	5510-5710 MHz(802.11n ht40/ac vht40)			
	5530-5690MHz(802.11ac vht80)		17.18 dBm in 57250-5850 MHz Band	
Band4:				
5745-5825 MHz (802.11a/n ht20/ac vht20)				
5755-5795 MHz(802.11n ht40/ac vht40)				
5775 MHz(802.11ac vht80)				
Bluetooth Performance				
			Maximum Peak Output Power(Conducted)	
BR			9.15 dBm	
EDR (π/4-DQPSK)			10.79 dBm	
EDR (8-DPSK)			11.08 dBm	
BLE			6.58 dBm	
Ordering Code	Antenna	DBS	Coexistence with Cellular Module	Development Board (Only for Debugging)
FCS950UABMD	One Wi-Fi/Bluetooth Antenna	-	-	FCS950UABM2

## Product Usage Instructions

### Installation:

1. Ensure your device is powered off before installation.
2. Locate the appropriate slot for the module on your device.
3. Gently insert the module into the slot, ensuring proper alignment.
4. Secure the module in place according to your device's design.
5. Power on your device and proceed with setup as per your device's instructions.

### Configuration:

1. Access your device's settings menu.
2. Locate the Wi-Fi & Bluetooth settings section.
3. Select the FCS950U module as the preferred network for Wi-Fi connectivity.
4. Pair Bluetooth devices by following the on-screen instructions.
5. Configure encryption settings as needed for secure connections.

### Maintenance:

1. Regularly check for software updates for optimal performance.
2. Clean the module's exterior gently with a soft, dry cloth if needed.
3. Avoid exposing the module to extreme temperatures or moisture.

**List of applicable FCC rules**

CFR 47 FCC PART 15 SUBPART C&E has been investigated. It is applicable to the modular.

**Specific operational use conditions**

This module is stand-alone modular. If the end product will involve Multiple simultaneous transmitting conditions or different operational conditions for a stand-alone modular transmitter in a host, the host manufacturer has to consult with module manufacturer for the installation method in end system.

**Limited module procedures**

Not applicable

**Trace antenna designs**

Not applicable

**RF exposure considerations**

To maintain compliance with FCC's RF Exposure guidelines, This equipment should be installed and operated with a minimum distance of 20cm from your body.

**Antennas**

This radio transmitter FCC ID: 2AM6U-FCS950U has been approved by the Federal Communications Commission to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Antenna Manufacturer	Antenna Chain	Antenna type	Input impedance (Ohm)	Maximum antenna gain
ZHONGTIAN XUN	1	FPC	50	2.39 dBi/2.4-2.5GHz (WIFI/BT Ant)

**Label and compliance information**

The final end product must be labelled in a visible area with the following" Contains

**FCC ID: 2AM6U-FCS950U"**

**Information on test modes and additional testing requirements**

The host manufacturer is strongly recommended to confirm compliance with FCC requirements for the transmitter when the module is installed in the host.

**Additional testing, Part 15 Subpart B disclaimer**

The host manufacturer is responsible for compliance of the host system with the module installed with all other applicable requirements for the system such as Part 15 B

**FCC**

Any Changes expressly or modifications not approved by the party responsible for compliance could void the user's authority to operate the equipment. This device complies with part 15 of the FCC Rules.

**Operation is subject to the following two conditions:**

- 1. This device may not cause harmful interference, and
- 2. this device must accept any interference received, including interference that may cause undesired operation.

**Note:** This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

**If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:**

- 1. Reorient or relocate the receiving antenna.
- 2. Increase the separation between the equipment and receiver.
- 3. Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- 4. Consult the dealer or an experienced radio/TV technician for help.

**FCC Radiation Exposure Statement:**

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. This equipment should be installed and operated with minimum distance 20cm between the radiator &you body.

**FAQs**

**Q: What encryption modes are supported by the FCS950U module?**

A: The FCS950U module supports WEP, WPA, WPA2, WPA3-Personal, and WPA3-Enhanced Open encryption modes for secure connections.


**Q: How many concurrent BLE links can the FCS950U module support?**

A: The FCS950U module can support up to 8 concurrent BLE links for simultaneous Bluetooth connections.

**Q: What is the power supply voltage requirement for the FCS950U module?**

A: The FCS950U module requires a specific power supply voltage for optimal performance. Please refer to the product specifications for detailed information.

**Documents / Resources**

	<p><a href="#">Fujian FCS950U WiFi and Bluetooth Module</a> [pdf] Instruction Manual FCS950U, 2AM6U-FCS950U, 2AM6UFCS950U, FCS950U WiFi and Bluetooth Module, FCS950U, WiFi and Bluetooth Module, Bluetooth Module, Module</p>
---	--

**References**

- [User Manual](#)

## **Manuals+. Privacy Policy**

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.