Manuals+ — User Manuals Simplified.

FUYAO

FV-98 BT 3-Mode Screen Display Mechanical Keyboard

Fuyao FV-98 BT 3-Mode Screen Display Mechanical Keyboard Instruction Manual

Contents

FUYAO

Fuyao FV-98 BT 3-Mode Screen Display Mechanical Keyboard

Product Specifications

Specification Item	Details
Product Number	FV-98
Keyboard Interface	TYPE-C
Connection Method	Wired + 2.4G + Bluetooth (BT)
Luminous Type	RGB Backlight
Product Type	Mechanical Shaft
Number of Keys	98 Keys
Button Life	20 million times or more
Operating Voltage	3.7V DC
Battery Capacity	2000mAh
Product Size	390 × 150 × 50 mm (± 2 mm)
No Impact Button	Supports full key conflict-free
Keycap Material	ABS
Product Line Length	1500 mm ± 30 mm
Multimedia Support	FN + 12 key combinations
System Compatibility	Mac OS X10, 12, iOS10 or later

Product Usage Instructions

Key Functions:
Use the following key combinations for various functions:

- FN + F1= Music
- FN + F2= Sound –
- FN + F3= Sound +
- FN + F4= Silent
- FN + F5= Stop
- FN + F6= Last song
- FN + F7= Play/pause
- FN + F8= Next song
- FN + F9= Mail
- FN + F10= Home page
- FN + F11= My computer
- FN+F12= Calculator
- FN+ESC Hold down 3s to restore the factory light effect
- Flip the switch to switch BT/Wired /2.4G

Sleep Function: After the wireless keyboard is connected to the device, it goes into hibernation without operation for 1 minute. Click any key to wake up the original state.

Lighting Use:

- FN+W LX98-BT1
- FN+E LX98-BT2
- FN+R LX98-BT3

FN+Q, W, E short press to enter the corresponding hook-back state. The blue light of the corresponding key blinks slowly, and the connection is up or over When the blue goes out. Press and hold for more than 3s to enter the corresponding pairing state, and the red light flashes accordingly. Connected or timed out, red off. (Bluetooth indicator light on prompt mode)

Press FN+T to enter the corresponding 2.4G hookback state. The blue light of the corresponding key blinks slowly to indicate that the connection is up or over When the blue goes out. Press and hold for more than 3s to enter the corresponding pairing state, and the red light flashes accordingly. Connected or timed out, red off. (2.4G indicator steady on prompt mode)

Light mode/Light effect/Backlight brightness/Volume/System toggle switches within the screen

FN+ direction to switch the screen page left/right, press FN+ENTER on the mode page to enter the mode adjustment, then Use FN+ direction to adjust the desired function left/right, and then press FN+ENTER to return to the screen page. All modes are switched according to the display

FCC STATEMENT

Warnning:
This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection againstharmful interference in a residential installation. This equipment generates, uses and can radiateradio frequency energy and, if not installed and used in accordance with the instructions, maycause harmful interference to radio communications. However, there is no guarantee thatinterference will not occur in a particular installation. If this equipment does cause harmfulinterference to radio or television reception, which can be determined by turning the equipmentoff and on, the user is encouraged to try to correct the interference by one or more of thefollowing measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution: Any changes or modifications to this device not explicitly approved by manufacturer could void your authority to operate this equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

1. This device may not cause harmful interference, and
2. this device must accept any interference received, including interference that may cause undesired operation.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This

equipment should be installed and operated with minimum distance 0cm between the radiator and your body

FAQ

Q: How do I restore the factory light effect?
A: Hold down FN+ESC for 3 seconds.

Q: What should I do if the keyboard goes into hibernation?
A: Simply press any key to wake it up.

Q: How do I switch between different lighting modes?
A: Use the specified key combinations like FN+WLX98-BT1, FN+ELX98-BT2, and FN+RLX98-BT3.

Documents / Resources

	Fuyao FV-98 BT 3-Mode Screen Display Mechanical Keyboard [pdf] Instruction Manual FV-98, FV-98 BT 3-Mode Screen Display Mechanical Keyboard, BT 3-Mode Screen Display Mechanical Keyboard, 3-Mode Screen Display Mechanical Keyboard, Display Mechanical Keyboard, Mechanical Keyboard, Keyboard

References

- **User Manual**