

Contents [[hide](#)]

- [1 GeneSys SensorX Audio Visual Signals in Vehicle Interiors](#)
- [2 Product Information](#)
- [3 KEY FEATURES](#)
- [4 APPLICATIONS](#)
- [5 SENSORX BASE SYSTEM](#)
- [6 High-performance Camera](#)
- [7 Microphone](#)
- [8 Basic function](#)
- [9 EXTENSION OPTIONS](#)
- [10 TECHNICAL DATA](#)
- [11 FAQ](#)
- [12 Documents / Resources](#)
 - [12.1 References](#)



GeneSys SensorX Audio Visual Signals in Vehicle Interiors



Specifications

- **Product Name:** SensorX
- **Function:** Detector for audiovisual signals in vehicle interiors
- **Features:** Embedded web interface for configuration

Product Information

SensorX is a powerful measuring system designed to detect and record audio-visual signals in vehicle interiors. It utilizes high-performance cameras and a precise microphone to detect acoustic and visual warnings targeted at drivers within milliseconds.

SENSORX BASE SYSTEM

The SensorX base unit offers a flexible and reliable system for recording and analyzing acoustic and visual signals in vehicles. It comes with powerful computing power and an intuitive web interface for configuration.

High-performance Camera

The SensorX uses industrial camera systems to detect changes in shape and color in real-time, allowing for processing multiple signals simultaneously and outputting results as digital trigger signals and UDP/CAN messages with low latency.

Microphone

The highly sensitive microphone of SensorX can check and recognize sound patterns, single, and multi-frequency sounds in real-time. It features robust Lemo plug-in connections for decentralized installation in vehicles.

Product Usage Instructions

Basic Functionality

In the basic configuration, SensorX includes a camera and a microphone. The system, with its basic software license, can monitor 1 symbol with up to 3 associated statuses and 2 acoustic signals.

Symbol Recognition

SensorX can learn user-defined symbols and reliably detect them in image data. Symbols can be trained using both synthetically generated images and live images from a connected camera.

SENSORX

Detector for audiovisual signals in the vehicle interior with embedded web interface for configuration SensorX is a powerful measuring system that has been specially developed for the detection and recording of audio-visual signals in vehicle interiors. With its high-performance cameras and precise microphone, SensorX detects acoustic and visual warnings that are targeted at the driver in just a few milliseconds.

The high-performance camera reacts to changes in the shape and colour of ICONs in the instrument cluster. The microphone recognises specific sound patterns and acoustic warnings. When visual and acoustic signals are detected, SensorX transmits measurement data within a few milliseconds as digital trigger signals as well as LAN and/or CAN messages.



KEY FEATURES

- Multiple detection of shape and colour changes on the dashboard
- Recognition of sound patterns
- Data output rate up to 1kHz
- Data latency 30 msec
- Data output via Digital-I/O, LAN, CAN
- Embedded web interface for easy configuration

APPLICATIONS

- Advanced Driver Assistance Systems (ADAS) evaluation e.g.:
 - Auto Emergency Braking, AEB
 - Forward Collision Warning, FCW
 - Adaptive Cruise Control, ACC
 - Lane Keeping Assist System, LKA
 - Lane Departure Warning, LDW
 - Blind Spot Detection, BSD
 - Rear Cross Traffic Alert, RCTA
 - Traffic Sign Recognition, TSR
 - Parking Assistance, PA
- Euro NCAP and NHTSA Evaluation
- Autonomous vehicle (AV) operation
- Comprehensive vehicle safety functions with connected sensor systems and V2X



SENSORX BASE SYSTEM

Basic Unit

- Interfaces
 - **Signal IN / OUT:** The base unit has four signal input and output connections that allow flexible integration and control of external devices.
 - **CAN:** Two CAN interfaces enable the reception of vehicle signals directly from the vehicle network or the output of result data.
 - **Sensor:** Four sensor interfaces enable the connection of several cameras and the microphone.
 - **Display:** An integrated display shows status and system informations, allowing the system to be checked and diagnosed quickly.
- Performance and configuration

- **Powerful computing core:** The central processor of the base unit is optimized for real-time processing of audio and video signals, which ensures fast and reliable signal detection and processing.
- **Embedded Webinterface:** The web interface enables simple configuration and the display of important system parameters via a web browser. No additional software is required
- **Robust housing:** The basic unit has a robust, passively cooled housing that can be flexibly installed in the vehicle.

With its powerful computing power and intuitive webinterface, the SensorX base unit offers a flexible and reliable system for recording and analysing acoustic and visual signals in the vehicle.

High-performance Camera

With the help of industrial camera systems, SensorX detects changes in shape and color and processes them in real time. This makes it possible to process several signals in parallel and output the results as digital trigger signals and UDP and CAN messages with low latency.

Technical data

- **High frame rate:** Image processing takes place at a frame rate of at least 100 Hz. Application-specific rates of up to 300 Hz are possible.
- **Automatic focus:** The cameras autofocus enables precise and fast focusing.
- **Robust cabling:** The camera's connection cables are designed for harsh environments.
- **Active lighting:** The optional active lighting ensures maximum reliability for image recognition.

Housing and assembly

The SensorX camera systems are supplied in IP67 housings. The housings have integrated, multifunctional fastening and mounting devices that enable flexible and application-optimized installation in different installation situations. This includes several threaded points for mounting or attaching mirrors. A standard 1/4-inch thread for camera

mounts allows the camera to be attached to the dashboard even under difficult environmental conditions.



Microphone

The highly sensitive microphone of the SensorX is able to check and recognize sound patterns as well as single and multi-frequency sounds in real time.

- **Intelligent filtering:** Advanced filter algorithms reliably suppress ambient noise and interference signals. This ensures precise and stable detection of relevant acoustic information.
- **High sensitivity:** Thanks to its omnidirectional characteristic and a sensitivity of -16 dB FS/Pa, the microphone is able to reliably detect even very quiet signals.
- **Wide frequency response:** With a frequency range of 70 Hz to 18,000 Hz, the microphone captures a wide sound spectrum and is therefore suitable for a wide variety of acoustic applications.
- **Low latency:** Signal processing takes place with a very low latency of less than 15 ms – ideal for real-time applications and fast reactions to acoustic events.

Housing and assembly

The SensorX microphones are equipped with robust Lemo plug-in connections, enabling decentralized installation in the vehicle. Thanks to these high-quality features, the SensorX microphone is ideally suited as a powerful and versatile testing device for recording acoustic signals in automotive applications.



Basic function

In the basic configuration, the SensorX system is equipped with a camera and a microphone. With the associated basic software license, 1 symbol with up to 3 associated statuses and 2 acoustic signals can be monitored.

Symbol recognition

SensorX has the ability to learn user-defined symbols and reliably detect them in image data. The symbols can be trained using both synthetically generated images and live images from a connected camera.

For recognition, the learned symbol is localized within a defined search area in the camera image. Integrated pre-processing compensates for camera-related movements such as vibrations or slight positional deviations. For this purpose, the search area is dynamically adapted to the detected image shifts to ensure robust and stable detection.

Status detection

Different states can be defined for each recognized symbol. A state results from several distinguishable areas within the symbol, each of which is assigned a specific color. These color assignments serve as the basis for evaluating and classifying the current status.

The definition areas can be configured manually or generated automatically. The corresponding color values can either be predefined or determined on the basis of live images. A condition is considered detected as soon as all defined areas have the assigned colour characteristics.

Sound recognition

SensorX enables the visualization of audio signals for the identification and extraction of characteristic signal patterns. The window size for pattern recognition is variably adjustable to ensure an optimum balance between reproducibility and minimum latency (< 15 ms). The frequency-specific signal characteristics can be determined automatically at the touch of a button or adjusted manually.



EXTENSION OPTIONS

Combination of several events

- Up to 8 patterns, colors and color search ranges
- Up to 100 sounds (frequencies)
- Logical linking of individual results to an overall result

Search and alarm functions can be flexibly combined and precisely controlled using logical AND/OR links. SensorX only triggers an alarm if defined criteria are met – for example, if a red warning triangle is simultaneously detected in the instrument cluster based on shape and color. This eliminates the need for downstream manual linking and increases processing efficiency.

Delay determination

The option for high-precision measurement of the delay of the CAN signal between the control unit and the display in the instrument cluster or the sound output enables exact analysis of the communication times in the vehicle. This also makes it possible to determine latency times in the vehicle.

Detection of gaze direction/head rotation

This function enables the driver's line of vision to be detected precisely by monitoring the tilt and rotation of the head. SensorX thus supports a more precise analysis of the driver's behavior, especially with regard to the direction of gaze due to head movements while driving.

TECHNICAL DATA

Basic Unit

Power	<p>1x Lemo</p> <p>9 to 32 VDC</p>
Ethernet	<p>1x RJ45 g</p> <p>1Gbit, gPTP*1</p> <p>Configuration and Data output</p>
Sensor Port	<p>4x Lemo</p> <p>High-speed sensor ports to connect to four cameras and one microphone.</p>
CAN	<p>2x SubD9</p> <p>CAN, 2b, 1 Mbit / CAN FD</p> <p>Data output, input*1</p>
Analog Input	<p>4x SubD9</p> <p>Analog In +/-24V +20% (16 bit)</p> <p>e.g. frequency, PPS, ...</p>
Analog Output	<p>4x SubD9 Signal Out</p> <p>20mA current carrying capacity per channel</p> <p>e.g. Signal, PPS, frequency, ...</p>
Data output rate	100 / 200 / (1000)*1 Hz
Calculation latency	10 msec

Dimensions (W x L x H)	225 x 235 x 75 mm
Weight	2.6 kg
Operation temperature	-10 to +50 °C
Protection class	IP 50

Camera

Frame rate	100 Hz / (300 Hz)*1
Focus	Auto
Resolution	1400 x 1080
Shutter	Global
Dimensions (W x L x H)	40 x 80 x 40 mm
Weight	0,20 kg
Operation temperature	0 to +50 °C
Cable length	4.5 m
Protection class	IP 20

Microphone

Audio frequency response	70 to 18000 Hz
Intrinsic noise	32 dB
Maximum sound pressure level	110 dB
Pick-up pattern	Omni-directional
Weight	0.017 kg

Operation temperature	0 to +50 °C
Cable length	4.5 m
Microphone capsule (L; ø)	26,00; 10,50 mm
Protection class	IP 20

*1 Optional

For any further questions: support@genesys-offenburg.de

GeneSys Elektronik GmbH Maria-und-Georg-Dietrich-Str. 6 77652 Offenburg Germany
GeneSys Datasheet SensorX EN.docx

+49 (0) 781 96 92 79 0


www.genesys-offenburg.de

FAQ

Q: What is the basic configuration of SensorX?

A: The basic configuration includes a camera and a microphone, along with the ability to monitor 1 symbol with up to 3 associated statuses and 2 acoustic signals.

Documents / Resources

	GeneSys SensorX Audio Visual Signals in Vehicle Interiors [pdf] User Guide SensorX Audio Visual Signals in Vehicle Interiors, SensorX, Audio Visual Signals in Vehicle Interiors, Signals in Vehicle Interiors, Vehicle Interiors, Interiors
---	---

References

- [User Manual](#)

Leave a comment

Your email address will not be published. Required fields are marked *

Comment *

Name

Email

Website

☐ Save my name, email, and website in this browser for the next time I comment.

Post Comment

Search:

e.g. whirlpool wrf535swhz

Search

[Manuals+](#) | [Upload](#) | [Deep Search](#) | [Privacy Policy](#) | [@manuals.plus](#) | [YouTube](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.