




GSD W37M2510 Wi-Fi Module Instructions

[Home](#) » [GSD](#) » GSD W37M2510 Wi-Fi Module Instructions 

GSD W37M2510 Wi-Fi Module Instructions

Contents

- [1 Product Description](#)
- [2 Product Features](#)
- [3 Product Specification](#)
- [4 FCC Statement](#)
 - [4.1 Canada Statement](#)
- [5 Documents / Resources](#)
- [6 Related Posts](#)

Product Description

The W37M2510 is a 2.4GHz WIFI 2x2 MIMO module. This module provides a high level of integration with a dual-stream IEEE 802.11n MAC/ base band /radio. The WLAN operation supports 20MHz, 40MHz channels for data rates up to 300Mbps. It fully complies with IEEE 802.11 b/g/n feature rich wireless connectivity at high standards, delivers reliable, cost-effective, throughput from an extended distance.

Product Features

- Complies with IEEE 802.11b/g/n for 2.4GHz Wireless LAN.
- Two transmit and Two receive path(2T2R)
- Works with all existing network infrastructure.
- Capable of up to 128-Bit WEP Encryption.
- Freedom to roam while staying connected.
- UP to 300 Mbps High-Speed Transfer Rate in 802.11n mode of operation.
- Operating Systems Linux, Win7, Win8, Win10, XP
- Low power consumption.
- Easy to install and configure.

- High speed USB 2.0 interface
- ROHS compliant

Product Specification

Model	WIFI Module
Product Name	W37M2510
Standard	802.11 b/g/n
Interface	USB
Data Transfer Rate	1,2,5.5,6,11,12,18,22,24,30,36,48,54,60,90 and maximum of 300Mbps
Modulation Method	DQPSK,DBPSK,CCK(802.11b) QPSK,BPSK,16QAM,64QAM with OFDM (802.11 g) QPSK,BPSK,16QAM,64QAM with OFDM (802.11n)
Frequency Band	2412~2462 MHz
Operation Mode	Infrastructure
Security	WEP, TKIP, AES, WPA, WPA2
Operating Voltage	5V±10%
Current Consumption	750mA
Antenna Type	PIFA

Operating Temperature	0 ~ 60°C ambient temperature
Storage Temperature	-40 ~ 80°C ambient temperature
Humidity	5 to 95 % maximum (non-condensing)

NOTICE

- please keep this product and accessories attached to the places which children can't touch;
- do not splash water or other liquid onto this product, otherwise it may cause damage;
- Do not put this product near the heat source or direct sunlight, otherwise it may cause deformation or malfunction;
- please keep this product away from flammable or naked flame;
- please do not repair this product by yourself. Only qualified personnel can be repaired.

FCC Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This equipment complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

1. This device may not cause harmful interference, and
2. This device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Please notice that if the FCC identification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC ID:2AC23 W37" Or "Contains Transmitter Module FCC ID:2AC23-W37" any similar wording that expresses the same meaning may be used.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20cm between the radiator & your body. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

Information on test modes and additional testing requirements

Any final host product with the modular transmitter installed should be under test according to guidance given in KDB 996369 D04. To enter test mode for module, MT7603 QA V0.0.185 software and command is necessary. When something wrong happens in configuring test modes for host product with module, host product manufacturer should coordinate with module manufacturer for technical support. It is recommended that some investigative measurements should be taken to confirm that host product with module installed does not exceed the spurious emissions limits or band edge limits.

The module is limited to OEM installation ONLY.

The OEM integrator is responsible for ensuring that the end-user has no manual instruction to remove or install module.

The module is limited to installation in mobile application.

A separate approval is required for all other operating configurations, including portable configurations with respect to Part 2.1093 and difference antenna configurations.

There is requirement that the grantee provide guidance to the host manufacturer for compliance with Part 15B requirements.

The module complies with FCC Part 15.247 and apply for Single module approval. Trace antenna designs: Not applicable.

Antennas:

- 2.4G
- PIFA antenna & 3 dBi

The antenna is permanently attached, can't be replaced.

Canada Statement

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

1. This device may not cause interference.
2. This device must accept any interference, including interference that may cause undesired operation of the device.

Please notice that if the ISED certification number is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains IC: 12290A-W37" Or "Contains Transmitter Module IC: 12290A-W37" any similar wording that expresses the same meaning may be used.

RSS-GEN issue 5 section 6.8 requires,

This radio transmitter [IC: 12290A-W37] has been approved by Innovation, Science and

Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for


any type listed are strictly prohibited for use with this device.

Antennas:

- 2.4G
- PIFA antenna & 3dBi



Documents / Resources

	<p>GSD W37M2510 Wi-Fi Module [pdf] Instructions W37, 2AC23-W37, 2AC23W37, W37M2510 Wi-Fi Module, W37M2510, Wi-Fi Module</p>
--	---