



**BOLT ULTIMATE
3.0 Dynamic
Display
Jumpstarter**



HALO BOLT ULTIMATE 3.0 Dynamic Display Jumpstarter User Manual

[Home](#) » [HALO](#) » HALO BOLT ULTIMATE 3.0 Dynamic Display Jumpstarter User Manual

Contents

- [1 HALO BOLT ULTIMATE 3.0 Dynamic Display Jumpstarter](#)
- [2 Product Usage Instructions](#)
- [3 FAQs](#)
- [4 SAFETY INSTRUCTIONS](#)
- [5 PRODUCT MAINTENANCE](#)
- [6 PRODUCT OVERVIEW](#)
- [7 DIGITAL DISPLAY](#)
- [8 JUMP START YOUR VEHICLE](#)
- [9 HOW TO USE THE FLOODLIGHT](#)
- [10 AIR COMPRESSOR](#)
- [11 AC OUTPUT TROUBLESHOOTING](#)
- [12 TECHNICAL SPECIFICATIONS](#)
- [13 FCC NOTE](#)
- [14 CONTACT INFORMATION](#)
- [15 Documents / Resources](#)
 - [15.1 References](#)



HALO BOLT ULTIMATE 3.0 Dynamic Display Jumpstarter



Product Usage Instructions

Safety Instructions

Your safety is important. Follow these precautions:

- Read and understand the manual before use.
- Avoid misuse or abuse of the equipment.
- Keep the jump starter dry and away from moisture.
- Avoid exposure to heat sources.
- Stop using the product if overheating, swelling, or deformation occurs.

Product Maintenance

If maintenance is required:

- Disconnect all power sources before cleaning.
- Use a clean, dry cloth for cleaning.
- Avoid corrosive cleaners or solvents.
- Avoid inserting metal objects into ports.

Charging the Jump Starter

Follow these steps to charge your Bolt Ultimate 3.0:

1. Fully charge the jump starter before use.
2. Connect the included USB-C cable to the jump starter.
3. Use any USB-powered port (wall adapter, car adapter, laptop) for charging.
4. The USB-C input port is rated for 20W and charges in less than 3.5 hours (5-100%).

FAQs

- **Q: What should I do if the jump starter overheats?**

- A: Immediately stop using the product and contact customer service.

- **Q: How can I clean the equipment?**

- A: Disconnect all power sources before cleaning. Use a clean, dry cloth and avoid corrosive cleaners or solvents. Do not insert metal objects into ports.

- **Q: How do I dispose of/recycle the device?**

- A: Do not put the device in the trash. Handle it according to local laws and regulations. For more information, visit www.epa.gov.

SAFETY INSTRUCTIONS

FOR ALL QUESTIONS RELATED TO SAFETY, WARRANTY, OR EXCHANGE REQUESTS, PLEASE CONTACT US.

YOUR SAFETY IS IMPORTANT TO US.

Please read the instructions carefully and utilize the proper precautions before operating this equipment. Save instructions for future reference.

- When used correctly, lithium-ion rechargeable batteries provide a safe and dependable source of portable power. However, if they are misused or abused, this may result in leakage, burns, fire, or explosion, causing personal injury or damage to other devices.
- Misusing or incorrectly connecting your jump starter may cause electric shock to users and damage equipment.
- Keep your jump starter dry and away from moisture, water, and corrosive materials.
- Do not expose your jump starter to moisture, water, rain, or snow.
- Keep your jump starter away from heat sources, including open flames, radiators, stoves, ovens, and any other devices that produce heat.
- Do not be exposed to fire or excessive temperature. Do not expose to heat above 212°F (100°C) or incinerate.
- In the unlikely event of leakage or explosion use sand or a chemical fire extinguisher.
- Your jump starter may become warm under extended high-power operation. Do not cover, wrap, or otherwise restrict air flow around the jump starter during operation.
- Do not disassemble your jump starter. There are no user-serviceable parts inside. Incorrect reassembly may result in shock or fire hazards.
- Do not drop or subject to strong impacts. Do not operate your jump starter if it has received a sharp blow, or has otherwise been damaged in any way.
- Do not puncture, crush, or subject to mechanical shock.
- Keep away from children and pets. The jump starter, along with its accessories are not toys.
- Make sure the jumper cables are fully plugged into the jump-start output before trying to jump-start your vehicle.
- Do not touch red (positive) and black (negative) jumper clamps together at any point.
- Make sure the jump starter's charging ports do not become contaminated with lint or other debris. Use a canned-air type of product periodically to ensure that the port openings are clear.

PRODUCT MAINTENANCE

WARNING

IF THE JUMP STARTER OVERHEATS, BECOMES SWOLLEN OR IS DEFORMED IN ANY WAY, IMMEDIATELY STOP USING THE PRODUCT AND CONTACT CUSTOMER SERVICE. EQUIPMENT CLEANING:

- Please make sure that the device is disconnected from all input power and output devices.
- Wipe with a clean, dry cloth.
- Do not use corrosive cleaners or solvents.
- Do not insert metal objects into the ports to clean them as this could


cause electrical shock. Blow any debris out with a canned-air type of product.

DISPOSAL/RECYCLING:

Do not put the device and its accessories in the trash can. Items must be properly handled in accordance with local laws and regulations. For additional information, please see www.epa.gov.


PRODUCT OVERVIEW

1. Increase Air Pressure
2. Air Compressor ON/OFF
3. Decrease Air Pressure
4. Air Pressure Unit Button
5. Digital Display
6. Jump Start Output
7. Jump Start ON/OFF Button
8. USB ON/OFF Button
9. USB-C Input/Output
10. AC ON/OFF Button
11. AC Output Port
12. USB-A Output
13. LED Floodlight
14. Air Compressor Hose
15. LED Floodlight ON/OFF Button
16. Interchangeable Air Nozzle Kit
17. 20W PD USB-C Charging Adapter
18. 24" Air Hose Extension
19. 24" USB-C to USB-C Cable
20. 16" Jumper Cable Clamps




DIGITAL DISPLAY

- **BATTERY FUEL GAUGE INDICATORS**
 - Each bar presents 20% of the charge capacity.
- **BATTERY PERCENTAGE**
 - Displays the current battery level.
- **UNIT IS CHARGING**
 - When on, this indicates the unit is plugged in and charging.
- **BATTERY TOO LOW**
 - The jump starter is not sufficiently charged to jump-start the vehicle.
- **VOLTMETER**
 - Will illuminate when the vehicle's battery voltage is detected.
- **SAFETY CHECK FAIL**
 - A "SAFETY CHECK FAIL" has been triggered.
- **TEMPERATURE**
 - A high or low temperature has been detected.
- **PRESSURE UNIT DISPLAY**
 - Displays air pressure in KPA, PSI or BAR.



CHARGE YOUR BOLT ULTIMATE 3.0

Fully charge the jump starter before using. To charge, connect the jump starter to the included USB-C cable. The unit can be recharged from any USB powered port, like a wall adapter, car adapter, laptop and more. The USB-C input port is rated for 20W and should be fully charged in less than 3.5hrs (5-100%).



JUMP START YOUR VEHICLE


IMPORTANT: Before connecting the jumper cables, ensure there is no obvious corrosion or dirt on the battery terminals. A direct connection to the positive (+) and negative (-) terminals is recommended. Be sure to follow the vehicle's specific recommended mounting points as pointed out by the vehicle manufacturer

BEFORE YOU GET STARTED

1. Make sure the jump starter has at least 50% charge.
2. You can not jump start while using the USB, AC, or air compressor functions.
3. Ensure the vehic.


• STEP 1: INSERT JUMPER CABLES

- Plug the jumper cables into the jump-start output.



• STEP 2: CONNECT TO BATTERY

- Attach the jumper-cable clamps to the vehicle battery.
 - Red clamp on positive terminal (+)
 - Black clamp on negative terminal (-)




• STEP 3: TURN IT ON

- Press the “Jump Start” button to begin the safety check. The green light should flash for 3 seconds then turn solid.



◦ WARNING

- ONCE THE JUMP STARTER HAS A SOLID GREEN LIGHT, DO NOT REMOVE THE CLAMPS. DO NOT TOUCH THE CLAMPS TOGETHER.
 - **NOTE:** Once the green light is solid, it will only remain in this state for up to 90 seconds.
 - **NOTE:** If you need to reposition the clamps or stop the jump-starting process, press the jump-start button to safely disengage the jump-starter.



• STEP 4: START YOUR VEHICLE

- Start the vehicle. If it doesn't start immediately, wait 15 seconds before attempting to start again (repeat Step 3). Most vehicles should start the first time but some variables play a critical role in the starting process (temperature, engine size/type, battery condition). See the TROUBLESHOOTING section for more information.

• STEP 5: DISCONNECT

- Make sure the jump start button is off. Carefully disconnect the jump starter cable clamps from the car battery.

HOW TO USE THE FLOODLIGHT

The multi-mode floodlight cycles through the following stages each time the button is pressed:

1. Floodlight ON/OFF button once = ON White Floodlight
2. Floodlight ON/OFF button twice = ON Red Floodlight
3. Floodlight ON/OFF button three times = ON Emergency Red S.O.S.
4. Floodlight ON/OFF button four times = OFF




CAUTION

LOOKING DIRECTLY INTO THE FLOODLIGHT CAN RESULT IN MINOR OR MODERATE INJURY.

AIR COMPRESSOR

• STEP 1: CONNECT

- Connect the air hose to the tire or use the appropriate nozzle to connect to your inflatable device.




- **STEP 2: SET DESIRED PRESSURE**

- Press the (+) or (-) button to set the desired pressure. The pressure measuring units can be changed by pressing the UNIT button.

- **STEP 3: INFLATE**

- Once the desired pressure has been set, begin inflating by pressing the Air Compressor ON/OFF button. The air compressor will shut off automatically once the pressure has been reached.




- **NOTE:** The air compressor can be started or stopped at any point by pressing the air compressor ON/OFF button. The (+) and (-) may be long pressed to set the desired pressure quickly.
- **NOTE:** Always check and follow the manufacturer's recommended pressure. Use caution as the air hose and connectors may get hot after extended use. The Bolt Ultimate 3.0 compressor is designed to automatically stop after an extended run-time or if an over-temperature protection set point is reached.

CHARGE YOUR DEVICES

- USB-A output port is rated for up to 20W.
- USB-C output port is rated for up to 20W.
 1. Connect the appropriate cable to your device.
 2. Plug the cable into the appropriate USB output port.
 3. Press the USB ON/OFF button to begin charging your device.

NOTE: It is recommended to use charging cables provided by the manufacturer of your devices.




CHARGING A LAPTOP

NOTE: Electronic devices can be powered by the AC output port as long as it is rated at 75 watts or less. Ensure the electronic device is rated at 75 watts or less.


- **STEP 1: CONNECT**

- Connect the AC power plug from your laptop into the AC output port.



- **STEP 2: POWER ON**

- Press the AC Power ON/OFF Button and wait for a solid green light.



NOTE: Make sure the AC power plug is fully plugged into the AC port before pressing the AC Power ON/OFF Button.

NOTE: The Bolt Ultimate 3.0 charger will automatically power off after 30 minutes of inactivity

AC OUTPUT TROUBLESHOOTING

FOR ALL QUESTIONS RELATED TO SAFETY, WARRANTY OR EXCHANGE REQUESTS, PLEASE CONTACT US.



- [1-800-255-6061](tel:1-800-255-6061)

ISSUE	POTENTIAL CAUSE	SOLUTION
AC button flashes red.	Electronic device is rated greater than 75 watts.	Only electronic devices rated at 75 watts or less can be used.
	The Bolt Ultimate battery is not sufficiently charged to power the connected electronic device.	Recharge the Bolt Ultimate battery.
Bolt Ultimate shuts off unexpectedly.	The Bolt Ultimate battery is not sufficiently charged to power the connected electronic device.	Recharge the Bolt Ultimate battery.
Bolt Ultimate displays a blue or red TEMP indicator.	The Bolt Ultimate has detected a low or high temperature condition.	Disconnect the Bolt Ultimate and allow the unit to acclimate to temperature operating range 14°-104°F (-10°-40°C).

TROUBLESHOOTING

JUMP STARTING IN COLD ENVIRONMENTS: In extreme cold environments, the jump starter should allow a jump start, but the vehicle battery may require a few attempts. If it doesn't jump the first time, try again. Each attempt should contribute to warming the battery just enough to increase jump start performance.

NOTE: The jump starter is designed to allow a jump start when used within a safe temperature range

ISSUE	POTENTIAL CAUSE	SOLUTION
Jump Start button has been pressed but nothing happens.	The USB ON/OFF Button or the Air Compressor ON/OFF Button has been pressed.	The jump start output can not be used in conjunction with the USB output or air compressor modes. Ensure that both USB and AIR Compressor modes are off.
Screen displays a red BATT TOO LOW message. 	Jump starter is not sufficiently charged to jump start the vehicle.	Recharge the jump starter and verify at least 50% charged. Then try the jump start process again.
Jump Start button flashes red and a SAFETY CHECK FAIL message is displayed. 	The jumper cables have not been properly connected to the vehicle battery.	Check the jumper cables and ensure that the red clamp is connected to the positive terminal (+) and the black clamp is connected to the negative terminal (-).

ISSUE	POTENTIAL CAUSE	SOLUTION
<p>Jump Start button flashes green continuously.</p> 	<p>The jump starter is waiting to be connected to a battery or a SAFETY CHECK FAIL has been triggered.</p>	<p>Check the jumper cables and ensure they are properly connected to the battery. Check and ensure the vehicle battery voltage is greater than 2.0V. If the SAFETY CHECK FAIL indicator is triggered during the jump start process, it is recommended that you consult with a certified mechanic.</p>
<p>Screen displays a blue or red TEMP indicator.</p>  	<p>The jump starter has detected a low or high temperature condition.</p>	<p>Disconnect the jump starter and allow unit to acclimate to temperature operating range (14°F-122°F).</p>
<p>You cannot successfully jump start your vehicle. The jump starter displays a vehicle battery voltage greater than 12.0V.</p>	<p>The jump starter detects that it is connected to a vehicle battery with a normal starting voltage. This could indicate that another vehicle component is faulty.</p>	<p>It is recommended that you consult with a certified mechanic.</p>
<p>The Jump Start and On/Off button flashes red and blue.</p>	<p>This could occur when attempting to jump start a vehicle while other electrical components (i.e. headlights, heater, radio, etc.) are on.</p>	<p>Turn off your headlights and any other components that may drain your car battery and try the jump start process again.</p>
	<p>The vehicle battery may be faulty.</p>	<p>It is recommended that you consult with a certified mechanic.</p>

PRODUCT REGISTRATION

- Scan the QR code below to register your product. For product information and videos, visit WWW.HALOPOWER.COM.



TECHNICAL SPECIFICATIONS

USB-C Input/Output	PD 20W Max
USB Output 2	5VDC/2.4A
Peak Current Rating	1500A
Floodlight Output	80lm
Internal Battery Energy	55500mWh
Operating Temperature	Charge: 32°-113°F (0°-45°C) Discharge: 14°-104°F (-10°-40°C)
Storage Temperature	-4°-140°F (-20°-60°C)
Dimensions	6.5 x 3.8 x 1.7 in. (263.5 x 133 x 55mm)
Weight	1.1 lb. (490g)

FCC NOTE

COMPLIANCE WITH FCC REGULATION

This device complies with part 15 of the FCC Rules and RSS-Gen of IC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.








NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced technician for help.
- Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

CAUTION: To comply with the limits of the Class B digital device, pursuant to Part 15 of the FCC Rules, this device must be used with certified peripherals and shielded cables. All peripherals must be shielded and grounded. Operation with non-certified peripherals or non-shielded cables may result in interference to radio or reception.

TRANSPORTING DANGEROUS GOODS

NOTE: Any changes or modifications of this device could void the warranty


 Fully charge before using	 Do not disassemble
 Use original or certified charger or cable	 It's not waterproof, do not expose to liquids
 Avoid extreme temperature	 Dispose of batteries and electronic goods in accordance with local regulations
 Avoid dropping	

This jump starter meets all legal requirements for the transportation of dangerous goods. According to international standards, if the jump starter is transported by air, it must be transported in accordance with IATA standard packaging. The instructions and labeling requirements of the International Air Transport Association and related declarations must be completed.

CONTACT INFORMATION

- ALLIANCE CONSUMER GROUP
- 700 Henrietta Creek Rd, Roanoke, Texas 76262
- Toll-Free: 800.255.6061
- www.acgbrands.com
- WWW.HALOPOWER.COM

Documents / Resources

	HALO BOLT ULTIMATE 3.0 Dynamic Display Jumpstarter [pdf] User Manual BOLT ULTIMATE 3.0 Dynamic Display Jumpstarter, BOLT ULTIMATE, 3.0 Dynamic Display Jumpstarter, Dynamic Display Jumpstarter, Display Jumpstarter, Jumpstarter
---	--

References

- [Alliance Consumer Group - Outdoor and Consumer Lifestyle Products Company](#)
- [U.S. Environmental Protection Agency | US EPA](#)
- [HALOPOWER.COM](#)
- [User Manual](#)