



HEINRICH CE1200H Embedded Conference System Owner's Manual

[Home](#) » [HEINRICH](#) » HEINRICH CE1200H Embedded Conference System Owner's Manual 

Contents

- [1 HEINRICH CE1200H Embedded Conference System](#)
- [2 Product Information](#)
- [3 Product Usage Instructions](#)
- [4 DESCRIPTION](#)
- [5 Specification](#)
- [6 Documents / Resources](#)
- [7 Related Posts](#)

HEINRICH

HEINRICH CE1200H Embedded Conference System



Product Information

- **Product Name:** CE1200H
- **Product Type:** Embedded Conference System

- **Cross Talk Input Voltage:** 20Hz – 80KHz
- **Cross Talk Ratio:** >87dB
- **Signal-to-Noise Ratio:** >98dB

Product Usage Instructions

1. Ensure that the CE1200H is properly connected to the conference room audio system.
2. Make sure the power supply is connected and turned on.
3. Adjust the Cross Talk Input Voltage within the range of 20Hz to 80KHz as per your requirement.
4. For optimal audio quality, maintain a Cross Talk Ratio of at least 87dB.
5. To minimize background noise, ensure a Signal-to-Noise Ratio of at least 98dB.
6. Test the audio output and adjust the volume accordingly.
7. Refer to the user manual for advanced settings and additional features.

Please note that for detailed instructions on installation, troubleshooting, and advanced configuration, refer to the complete user manual provided with the product.

DESCRIPTION

CE1200H series of portable embedded conference system is designed to function room only need the congress system, meeting with basic function, with small and light, installation is simple to use. System including control host, chairman of the meeting, guest conference units and on-demand matching the peripheral equipment, parts through the T connection cable connection. Each meeting the unit has the microphone open closed, speech indicator function. This system configuration is simple and can satisfy the needs of all kinds of large, medium and small conference, at the same time considering the demands of customer's higher future, only increase the corresponding peripheral equipment and software, this system can be upgraded to discuss video tracking meeting system.

With four groups of 8 p – DIN sockets: used in the system of multi-channel meeting unit connection, 60 group meeting unit, standard configuration can be connected with the load and short circuit protection function. Equipped with a microphone to speech at the same time the number of limit function. In this control host has a "1" "2" "3" "5" limit speech and "FREE" (full open) FREE speech several meeting mode selection. When choosing a microphone is open, can be applied to answer first. The chairmen unit open is not restricted by a number of the microphone.

System has a high, medium and low tone adjustment function, the receiver output volume adjustment functions. Built-in video interface, can be connected by the central processing unit (CPU), and camera which has the function of video image locating and tracking unit which can realize video tracking function.

As a phone coupler output and input ports, support functions of remote conference call. 3 set of audio signal output terminal, can be external or sound recording equipment. It can be installed level on the desktop or in the 19-inch standard rack.

As per our company policy one of the constant Product improvement the right is there for reserved to modify product specifications without prior notice

Specification

Model	CE1200H
Power Consumption	450W
Frequency Response	20Hz - 80KHz
Cross Talk	>87dB
S/N Ratio	>98dB
T.H.D	<0.03%
Follow Specification	IEC60914
Input Voltage	24V (Host Power Supply)
Microphone Input	4 Group 8 DIN Socket
Power Supply	220V/50Hz
Dimensions (WxHxD)	485 X 50 X 325mm
Net Weight	5.15KG

HEINRICH LIMITED, Marshall Avenue Worthing BN14 OES

W: www.heinrichlimited.com

E: info@heinrichlimited.com

Documents / Resources



[HEINRICH CE1200H Embedded Conference System](#) [pdf] Owner's Manual
CE1200H, CE1200H Embedded Conference System, Embedded Conference System, Conference System