



HiStone HS520M Self Checkout Terminal User Guide


[Home](#) » [HiStone](#) » HiStone HS520M Self Checkout Terminal User Guide 



Contents

- [1 Key Features](#)
- [2 Documents / Resources](#)
 - [2.1 References](#)
- [3 Related Posts](#)

Key Features

- 27" True flat capacitive touch screen enhancing user experience
- Flexible operational scenarios; wall mount or floor stand
- Multi-modular design allowing for self-service or self checkout customization to suit a variety of retail or hospitality environments
- The host adopts aluminum  alloy frame, More beautiful and fashionable.



QINGDAO HISTONE INTELLIGENT COMMERCIAL SYSTEM CO.,LTD.
 Wisdom Valley,NO.8 Shengshui Road, Laoshan District, Qingdao City,
 China.

Tel: +86 (532) 66069168

infopos@histonetec.com www.hics.histonetec.com

MODEL	HS520M
Processor	Intel Skylake-U, Intel 6th generation CPU 13-6100U, SOC 2.3G hz
Operating System	POSready7/Windows7/Windows 10/Linux
Memory	SO-DIMM DDR4 2166MHz 4GB,up to 16GB
Storage	SATA SSD 128GB, up to 256GB
Display Panel	27inch TFT-LCD 16:9 Display resolution:1920*1080
Touch Screen	True flat capacitive touch screen
Power Supply	150W integrated power supply
Integrated Scanner	Single window, support 1 D/2D barcode
Integrated Printer	80mm thermal printer
Speaker	2*5W Speaker
MIC	MIC, Omnidirectional

I/O Ports		1* RJ45 , 100M/1000M Gigabit LAN port
		4*USB 2.0 Ports
		2* Serial Ports
Dimensions (LxWxH)		1690*1092*482mm
Weight		57kg (Host + stand)
Optional Peripherals	Transaction camera	Face ID camera or Membership camera
	Alarm light	Security camera
		Alarm light
		Number plate
	Card reader	MSR (only)
		MSR +RFID
	Fingerprint reader	Fingerprint Reader
	Stand	Ground Stand
		Big Metal plate(optional for no grounding screws)
	Wall Mount	Wall mount bracket(for no stand)
	Shelving Unit	Big shelving unit(metal /plastic)
		Small shelving unit(metal /plastic)
	Bracket	EFTPOS holder
		External Fiscal Printer holder
		Disinfectant bottle holder
Operating Voltage		110V/240V AC, 50-60hz
Environment	Operating	5°C – 40°C/40%-60% RH non-condensing
	Storage	-5°C – 50°C/30%-80% RH non-condensing
EMC and Safety		CE/ FCC Pending
Colour		Standard: White Optional: Black

- Patented protection lock, printer anti-theft design to prevent accidental touch



- Front opening door for easier maintenance



- Big Shelving Unit or Small Shelving Unit optional

**FCC Statement:**

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:


- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

Documents / Resources

 <p>HiStone Self-service Kiosk HS520M</p> <p>Key Features</p> <ul style="list-style-type: none">21.5" Touch Screen with multi-touch technologyHighly durable and sturdy, with screen or floor standMulti-touch interface allowing for self-service or self-checkout transactions and a variety of other applicationsThe HiStone HS520M is a truly beautiful and intelligent kiosk	<p>HiStone HS520M Self Checkout Terminal [pdf] User Guide</p> <p>HS520M Self Checkout Terminal, HS520M, Self Checkout Terminal, Terminal</p>
---	--

References

- [Point Of Sale Manufacturer | HiStone POS | Qingdao](#)