# HomeSeer HS4-Pi HomeTroller Pi Smart Home Hub Installation Guide

```
     HomeSeer HS4-Pi HomeTroller Pi Smart Home
             Hub Installation Guide
```

**HomeSeer HS4-Pi Install Guide**

This guide will allow you as the user to use your Raspberry Pi to run HS4. When installed on the Raspberry Pi, HS4-Pi creates an ultra-small, powerful Z-Wave home automation gateway controller.

**Requirements:**

- Raspberry Pi2, Pi3, Pi3 B+, or Pi4
- Blank microSD Card of 16GB* or bigger
- SD Card reader

**Downloads:**

- **HomeSeer Rasp-Pi Image** (Full 1.6GB)
- **Etcher** (image flashing)

**Full Image Procedure** (option 1):

1. Download the HS4PiV3-071320.zip from the link above.
2. Once the download is finished, extract the HS4PiV3-071320 from the zip folder. This may take up to 20 minutes.
3. Download, install, and run Etcher.
4. Insert blank SD card into SD card reader.
5. Select the HS4PiV2-071320 file and the correct drive letter of your SD card. Click Flash. The process could take up to 20 minutes.
6. Once the flash completes, remove your SD card and insert into your Pi.
7. Boot up will take about a minute. Go to find.homeseer.com to start using HS4!
   Note: root pw = homeseerpi | homeseer pw = hsthsths4

**Click here** for the complete HS4 Quick-Start Guide.
**Click here** for the getting started video.
**Click here** for more help with HS4.

**Troubleshooting Rasp-Pi**

All customers have lifetime support. Initially you have **30 Day Priority Phone Support** and after that you have support through our **Help Desk** (**helpdesk.homeseer.com**) and our community based **Message Board** (**board.homeseer.com**).

*Some 16GB SD card's capacity may be a few MBs short of the required size due to manufacturers. Most 16GB cards will work but if you experience this issue, we recommend a 32GB SD card.

HomeSeer | 10 Commerce Park North, Unit #10 Bedford, NH 03110 | **www.homeseer.com** | 603-471-2816

rev 2. 07/13/2020

**Contents**

**Documents / Resources**

**HomeSeer HS4-Pi Install Guide**

This guide will allow you to the user to use your Raspberry PI 4 run the HS4-Pi version of the Raspberry PI 4 (Pi 4) HomeTroller software and access and control all of your Home automation systems remotely.

**Requirements:**

- Raspberry Pi 3 (1GB) or 4B
- MicroSD Card (16GB or bigger)
- SD Card reader

**Downloads:**

- HomeSeer HS4-Pi Image Build 1.0GB6
- HS4-Pi Image Putty(img)

**Full Image Procedure** (option 1)

1. Download the HS4-Pi (HS T.1.0.6 zip from the link above.
2. Once the windows is finished, extract the .IMAGE HS4-Pi from the zip folder. This may take up to 60 minutes.
3. Download the Install onto your computer.
4. Insert the microSD card into the card reader.
5. Select the IMAGE HS T.1.0.6 file and the current drive letter of your SD card (Disk Flash). The process could take up to 20 minutes.
6. Once the complete, remove your SD card and insert into your Pi.
7. Now connect the micro USB power to the Pi and boot your into the new directly HS4.
8. Open your web browser's favorites to the running. Computer up in install all.

Click here for the complete HS4-Pi Install Guide

Click here for more help with HS4

**Troubleshooting Help?!**

If it still isn't busy: Before support is finish, get your **60 Day Priority Phone Support** from a HS4 Starter Support through our help Desk on in touch a process and interact via the continued our on a **Manage Board** at touch on interest so to.

*Raspberry's Pi3 GB8 or 4Gb it supporting but a HS4-Pi then if the required now we a recommendation 1 time 16GB run the will and the if it you can extend the it you can recommended it 2GB 3D user.*

HomeSeer | 10 Commerce Park North, Unit #10 Bedford, NH 03110 | www.homeseer.com | 603-471-2816
rev 1.07.06.2022

# HomeSeer HS4-Pi HomeTroller Pi Smart Home Hub [pdf] Installation Guide
HS4-Pi, HomeTroller Pi Smart Home Hub, HS4-Pi HomeTroller Pi Smart Home Hub, Pi Smart Home Hub Software

**Manuals+,**