



HPC FIRE TOR-MLFPK24-TRG H-FLEX Linear Trough Fire Pit Insert Instruction Manual

[Home](#) » [HPC Fire](#) » HPC FIRE TOR-MLFPK24-TRG H-FLEX Linear Trough Fire Pit Insert Instruction Manual 

HPC FIRE TOR-MLFPK24-TRG H-FLEX Linear Trough Fire Pit Insert Instruction Manual




Contents


- [1 Parts Descriptions](#)
- [2 Documents / Resources](#)
- [2.1 References](#)
- [3 Related Posts](#)

Parts Descriptions


SIDE VIEW




FRONT VIEW



ISOMETRIC VIEW



BRACKET DETAIL



MATERIAL: 304 STAINLESS STEEL

PART NUMBER		DIMENSION CHART			
		PAN	STANDARD BTU		I STND FLEX
			PENTA	TORPEDO	LINE LENGTH
TOR-	MLFPK24-TRGH-FLEX	24.5"	50K	65K	36"
TOR-	MLFPK36-TRGH-FLEX	36.5"	65K	65K	36"
TOR-	MLFPK48-TRGH-FLEX	48.5"	65K	65K	36"

*FOR TORPEDO BURNERS ADD TOR-

NOTES:

1. 1. PROPER VENTING

• ENCLOSURES:

- For Fire Pit Inserts upto 65K BTU: Required 2 vents, 18 sq. in each on opposing sides.
- BOWLS (Copper, concrete or metal) Bowl to be raised above mounting surface minimum of 3/4" gap, Bowl to have a minimum of 6" diameter hole in bottom

2. GAS SUPPLY

- Natural Gas: Supply Pressure: Minimum: 3.5" W.C., Maximum: 7.0" W.C. LP Gas: Supply
- Pressure: Minimum: 8.0" W.C., Maximum 11.0° W.C.

IMPORTANT: Ensure any flex line that may be used from the permanent main fuel supply to the product is rated to the stated max btu of the product and certified to ANSI Z21.75°CSA 6.27.

3. MODIFCATION OF PRODUCT WILL VOID ANY CERTIFICATION AND WARRANTY.

4. FOLLOW ALL MANUFACTURER INSTALLATION INSTRUCTIONS AND LOCAL CODES.

5. ALL DIMENSIONS ARE CONSIDERED TRUE AND REFLECT MANUFACTURER'S SPECIFICATIONS AS OF THE REVISION DATE


6. DO NOT SCALE DRAWING

7. THESE DRAWINGS ARE FOR SIZING AND PLANNING PURPOSES. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT. THE MANUFACTURERS RESPONSIBLE FOR THE ACCURACY OF THE DRAWING
8. CONTRACTOR'S NOTE FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info REFERENCE NUMBER 771-011

HEARTH PRODUCTS CONTROLS 2225 LYONS RD.
MIAMISBURG, OH 45342
TOLL FREE: 877.585.9800
PHONE: 937.436.9800
www.hpcfire.com



Documents / Resources



[HPC FIRE TOR-MLFPK24-TRG H-FLEX Linear Trough Fire Pit Insert](#) [pdf] Instruction Manual
TOR-MLFPK24-TRG H-FLEX, TOR-MLFPK36-TRG H-FLEX, TOR-MLFPK48-TRG H-FLEX, TOR-MLFPK24-TRG H-FLEX Linear Trough Fire Pit Insert, Linear Trough Fire Pit Insert, Trough Fire Pit Insert, Fire Pit Insert, Pit Insert

References

- [User Manual](#)