

HSNI SO100 Automatic Jar Opener Instructions

Home » HSNI » HSNI SO100 Automatic Jar Opener Instructions

Contents

- 1 SO100 Automatic Jar Opener
- **2 Product Information**
- **3 Product Usage Instructions**
- 4 Quick Start Guide
- **5 Install Batteries to Operate**
- **6 Operating Steps**
- 7 Documents / Resources
 - 7.1 References
- **8 Related Posts**



SO100 Automatic Jar Opener



Product Information

Specifications

- No OFF Button
- · Automatic shut-off feature
- · Battery-operated
- Manually operable arms

Product Usage Instructions

Installing Batteries

- 1. Open the battery compartment on the unit.
- 2. Insert the required batteries, following the correct polarity.

Operating Steps

- 1. Place the unit on the lid of the Jar.
- 2. Press and hold Power Button for the arms to tighten on the lid of the jar and to open the Jar.
- 3. The unit will open the jar automatically and turn off after the arms return to their outward position.

Manually Operable Arms:

The arms can be manually rotated to their accurate position to restart the opening process.

Note: The unit may operate automatically when moving the arms manually. This is normal.

FAQ

· Q: What should I do if the arms do not tighten on the lid of the jar?

A: Make sure the unit is correctly positioned on the jar lid and try pressing the Power Button again to tighten the arms.

Q: Can I use rechargeable batteries with this product?

A: It is recommended to use standard alkaline batteries for optimal performance.

Quick Start Guide

No OFF Button

- Press and hold Power Button for the arms to move forward.
- The unit turns off automatically after the arms return to their outward position.

Install Batteries to Operate

Note: It is normal that the arms may start moving after inserting batteries. They will stop once they reach their outward position.

Operating Steps

- 1. Place the unit on the lid of the Jar.
- 2. Press and hold Power Button for the arms to tighten on lid of the jar and to open the Jar.

The unit will open the jar automatically, and turn off after the arms return to their outward position.

Manually Operable Arms

The arms can be manually rotated to their an accurate position to re-start the opening process again.

Note: The unit may operate automatically when moving the arms manually. This is normal.

Documents / Resources

Quick State Guide

Not GF State

1 in a site of the control of the

HSNI SO100 Automatic Jar Opener [pdf] Instructions SO100, SO200, SO100 Automatic Jar Opener, SO100, Automatic Jar Opener, Jar Opener

References

User Manual

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.