



HYPERX KHX-HSCP-GM Cloud II Headset User Manual

[Home](#) » [HYPERX](#) » HYPERX KHX-HSCP-GM Cloud II Headset User Manual 

HYPERX KHX-HSCP-GM Cloud II Headset



Contents

- [1 Introduction](#)
- [2 What's Included](#)
- [3 Features](#)
- [4 Technical Specifications](#)
 - [4.1 Headset](#)
 - [4.2 Microphone](#)
- [5 Overview](#)
- [6 Usage \(Direct Connect\) with No Control Box](#)
- [7 Usage \(with Control Box\)](#)
- [8 To ensure that HyperX Cloud II is the default audio device, you must follow these instructions](#)
- [9 To ensure that HyperX Cloud II is the default audio device, you must follow these instructions](#)
- [10 Usage \(PlayStation® 4\)](#)
 - [10.1 PlayStation 4](#)
- [11 Usage \(Xbox® One\)](#)
 - [11.1 \(USB Control Box not needed\)](#)
- [12 Usage with Mobile Device \(Phone or Tablet\)](#)
 - [12.1 Mobile \(Phone / Tablet\)](#)
- [13 Documents / Resources](#)
- [14 Related Posts](#)

Introduction

Optimized for pro-gaming, HyperX Cloud II Headset (KHX-HSCP-xx) is a high-quality communicating device that delivers superior sound, style and comfort. It uses an adjustable, soft-padded leatherette headband and features a closed-cup design for enhanced bass reproduction and minimal sound leakage. The HyperX Cloud II headset is HiFi capable and delivers a durable design for the most rugged gaming environments and is compatible with tablets and smartphones for mobile use.

What's Included



Package Contents

- 1 HyperX Cloud II Headset
- 1 Detachable Microphone (attached to headset)
- 1 spare set of velour ear cushions
- 1 USB control box
- 1 Mesh bag

Features

- Hi-fi capable 53mm drivers for supreme audio quality
- 15-25 KHz frequency response (earphones)
- Detachable microphone (quick and easy to plug/unplug for music-only purposes)
- Solid aluminum construction for durability and stability
- Super-soft padded leatherette headband and leatherette padding on cups

- Closed cup design for enhanced bass-reproduction and sound leakage

Technical Specifications


Headset

- Transducer type: Dynamic 53mm with Neodymium Magnets
- Operating principle: Closed
- Frequency response: 15Hz-25KHz (earphones)
- Nominal impedance: 60 ohm per system
- Nominal SPL: 98+/-3dB
- H.D: < 2%
- Power handling capacity: 150mW
- Sound coupling to the ear: Circumaural
- Ambient noise attenuation: approx.20 dBA
- Headband pressure: 5 N
- Weight with microphone and cable: 320g
- Cable length and type: 1m + 2m extension
- Connection: Mini stereo jack plug (3.5MM)

Microphone

- Microphone Transducer type: Condenser (back electret)
- Operating principle: Pressure gradient
- Polar Pattern: Cardioid
- Power supply: AB powering
- Supply voltage: 2V
- Current consumption: Max 0.5 mA
- Nominal impedance: $\leq 2.2 \text{ k ohm} \pm 30\%$
- Open circuit voltage at $f = 1 \text{ kHz}$ 20 mV / Pa
- Frequency response: 50 – 18,000 Hz (microphone)
- H.D: 2% at $f = 1 \text{ kHz}$
- Max. SPL: 105dB SPL (THD $\leq 1.0\%$ at 1KHz)
- Microphone output: -39+/-3dB
- Dimensions: 6*5mm
- Length mic boom: 150MM(include gooseneck)
- Capsule diameter: 6mm


Overview



- A. Leatherette headband w/ HyperX logo
- B. Aluminum arm to adjust headband
- C. Attached cable w/ 3.5mm input jack
- D. Detachable microphone with adjustable arm and condenser
- E. 3.5mm audio input jack
- F. Extra set of ear cushions
- G. Control box cable w/ USB connector and control box (letter H)
- H. USB Control box w/ volume controls and 7.1 audio button

Usage (Direct Connect) with No Control Box

Connect your headset directly to your computer, game console, or other device (phone or tablet) that has a 3.5mm audio jack.



Usage (with Control Box)

Connect the headset's 3.5mm audio jack to the input jack on the USB control box. The USB control box then connects to a computer using the USB connector on the end of the control box.



Using Control Box

To ensure that HyperX Cloud II is the default audio device, you must follow these instructions

For Windows:

1. Open up Control Panel and select Hardware and Sound and then select Sound.



Figure 1 – Control Panel

2. If the "HyperX 7.1 Audio" is not currently the default audio device, right-click on the option and select "Set as Default Device."




Figure 2 – Right-Click Default Audio

3. This should place a green check mark next to the default audio device.





Figure 3 – Default Sound Device

Repeat the same steps for the microphone portion of the headset, located under the “Recording” tab (also found in the Sound program in Control Panel.)



To ensure that HyperX Cloud II is the default audio device, you must follow these instructions

For Mac:

1. Click the Apple menu and select "System Preferences" from the drop-down menu.



Figure 1 – Apple Menu

2. In “System Preferences”, click on the ‘Sound’ icon.



Figure 2 – System Preferences

3. Click on the Input tab and select “HyperX 7.1 Audio” for default sound input.



Figure 3 – Sound Preferences

4. Click on the Output tab and select “HyperX 7.1 Audio” for default sound output.

Usage (PlayStation® 4)

For optimal use with PlayStation® 4 (PS4®), unplug the headset jack from the USB control box and connect audio jack on the headset directly to the PS4 game controller and follow these steps:

1. Turn on your PS4® game console.
2. Navigate to the Settings Menu and select it.
3. Highlight the ‘**Devices**’ menu option and select it.
4. Scroll down to ‘**Audio Devices**’ and select it.
5. Choose ‘**Output to Headphones**’ and select ‘All Audio.’

PlayStation 4

(USB Control Box not needed)



Usage (Xbox® One)

To use the HyperX Cloud II headset with Xbox® One, you will need the Xbox One adapter (sold separately) that plugs into the Xbox® One controller (pictured below.) Because this adapter has built-in volume controls, you will remove the USB control box (that came with your HyperX Cloud II headset) and connect directly to the Xbox One controller.

Xbox One, requires controller adapter (Adapter sold separately)

(USB Control Box not needed)



Usage with Mobile Device (Phone or Tablet)

To use the HyperX Cloud II headset with a mobile device, unplug the USB control box and plug the 3.5mm headset jack directly into the audio jack on your phone or tablet.

Mobile (Phone / Tablet)

(USB Control Box not needed)

