

ICON PD3V100 DynaMic Dynamic Microphone Instruction Manual



DynaMic

Contents

- 1 Broadcast with confidence.**
 - 1.1 User manual
 - 1.2 Important Safety Instructions
 - 1.3 Introduction
 - 1.4 What's in the package?
 - 1.5 Register your ICON ProAudio product to your personal account
 - 1.5.1 1. Check serial number of your device
 - 1.5.2 2. Log in to your personal account page for existing user or sign up for new user
 - 1.5.3 3. Download all useful materials
 - 1.6 Features
 - 1.7 Operating the DynaMic
 - 1.7.1 Setting up the signal level
 - 1.7.2 Microphone Placement
 - 1.7.3 Connecting the DynaMic
 - 1.7.4 The switches
 - 1.8 Specifications
 - 1.8.1 Frequency response-vary axis
 - 1.9 Services
- 2 Documents / Resources**
 - 2.1 References
- 3 Related Posts**

Broadcast with confidence.

A broadcast quality all metal microphone ideal for podcasting and other vocal applications, offering full, rich tones and a high degree of clarity.



User manual



CAUTION
RISK OF ELECTRIC SHOCK
DO NOT OPEN



CAUTION: TO REDUCE THE RISK OF ELECTRIC SHOCK
DO NOT REMOVE COVER (OR BACK)
NO USER-SERVICEABLE PARTS INSIDE
REFER SERVICING TO QUALIFIED PERSONNEL



The lightning flash with arrowhead symbol within an equilateral triangle is intended to, alert the user to the presence of uninsulated dangerous voltage within the product's enclosure, that may be of sufficient magnitude to electric shock to persons.



exclamation point within an equilateral triangle is intended to alert the user of the presence of important operating and maintenance (servicing) instructions in the literature accompanying the appliance.

Important Safety Instructions

1. Read this manual thoroughly before using this unit.
2. Keep this manual for future reference.
3. Take notice of and comply with all warnings included in the user's manual or indicated on the appliance.
4. Follow all instructions included in this manual.

5. Do not expose this unit to rain or moisture. Avoid having water or other liquids spilled on this unit.
6. Do not block any ventilation openings or interfere with the proper ventilation of this unit. Install in accordance with the manufacturer's instructions.
7. Do not use or store near any heat sources such as radiators, heat registers, stoves, or other heat-producing appliances.
8. To avoid the risk of electrical shock, do not touch any exposed wiring while the unit is in operation.
9. Only use attachments/accessories specified by the manufacturer.
10. Unplug this unit and all connected electrical equipment during lightning storms or when left unused a long period of time.
11. Refer all servicing to qualified service personnel. Servicing is required when the appliance has been damaged in any way or fails to operate normally.

WARNING: To reduce the risk of fire or electric shock, do not expose this unit to rain or moisture

Introduction

Firstly, congratulations on your purchase of the ICON Pro Audio DynaMic dynamic microphone! In these pages, you'll find a detailed description of the features of the DynaMic dynamic microphone and a full list of specifications.

Please register the product on our website at the link below

www.iconproaudio.com/registration:

As with most electronic devices, we strongly recommend you retain the original packaging. In the unlikely event that the product is returned for servicing, the original packaging (or reasonable equivalent) is required. With proper care and adequate air circulation, your DynaMic microphone will operate flawlessly for many years to come.

We trust that this product will provide years of excellent service and in the unlikely event that your product does not perform to the highest standard, every effort will be made to address the issue.

What's in the package?

- DynaMic microphone
- Shock Mount (attached)



Register your ICON ProAudio product to your personal account

1. Check serial number of your device

Please go to <http://iconproaudio.com/registration> or scan the QR code below.



Input your device's serial number and the other information on the screen. Click "Submit".

A message will pop up showing your device information such as model name and its serial number – Click "Register this device to my account" or if you see any other message, please contact our after-sales service team

2. Log in to your personal account page for existing user or sign up for new user

Existing user: Please log into your personal user page by inputting your user name and password.

New user: Please click "Sign Up" and fill in all the information.

3. Download all useful materials

All your registered devices under your account will show on the page. Each product will be listed along with all its available files such as drivers, firmware, user manual in different languages and bundled software etc. for download. Please make sure you have download the necessary files such as driver before you begin device installation.

Features



The DynaMic dynamic microphone is perfect for vocal broadcasting, for example live streaming, podcasts or radio. Its good looks are matched by its robust exterior. The internal pop shield minimises plosive consonants, resulting in a smooth, open, natural and rich sound. The attached swing mount allows for flexible positioning. The extremely high-quality components and architecture within ensure every detail of your voice is captured. Switches to the rear of the DynaMic offer the user both low cut (to rid the source of low frequency rumble) and high-mid boost (to increase 'presence'). Of course, the DynaMic is not limited to just the spoken word. Use it on any number of sources for a fully rounded and detailed sound.

- High degree of clarity and quality for vocal applications
- Ideal as a broadcast microphone suited to radio, podcasts and streaming
- Cardioid pickup pattern for outstanding sound source separation and feedback rejection
- Pressure-gradient transducer with shock-mounted capsule
- Ultra-rugged construction with all metal finish
- Attached swing mount allows for flexibility with positioning
- Internal pop filter - no need for external pop shields
- Robust, high grade XLR connector at the rear
- Low cut filter switch (400 Hz)
- High boost switch (2KHz – 6KHz)
- Extremely robust and hard wearing

Operating the DynaMic

Setting up the signal level

When connecting the DynaMic to a mixer or recorder input, be sure that the input is at a suitable level. Most mixers and recorders of reasonable quality will offer a microphone input with MIC trim (usually called Trim or Gain) control. The purpose of the MIC trim control is to optimize the amount of good signal to any noise associated with the mixers electronics. A good MIC pre with trim also will have a Peak or Clip LED. To set a good level on the DynaMic, set it up in front of the desired sound source (i.e. a presenter talking) and slowly raise the MIC trim control until you see the Peak LED light up. Then, turn the mix trim control down until the LED does not light any more. On most mixers, the ideal setting is that the trim control is turned up as much as possible without lighting the Peak LED.

Microphone Placement

In order to maximize the sound quality, please pay careful attention to the placement of your DynaMic and how it is positioned. All microphones, especially cardioids microphones, exhibit a phenomenon known as the "proximity

effect". Very simply put, proximity effect is a resulting change in the frequency response of a microphone based on the position of the MIC capsule relative to the sound source. Specifically, when you point a cardioid MIC directly at the sound source (on-axis) you will get the best frequency response, however, when you start pointing the microphone slightly away (off-axis) you will notice the low frequency dropping off and the microphone will start to sound thinner.

For most vocal applications you'll want to position the microphone directly in front of the presenter. If you find that the voice produces an overly 'bassy' effect, try switching the low cut on and re-positioning the mic (experimentation is the best teacher, here). Equally, if you feel the voice is in need of more 'presence', try switching on the 'high boost' switch.

Connecting the DynaMic

This DynaMic has an XLR connection, which provides a balanced output. Unlike condenser mics, you will not need to use 'phantom power' if you are connecting using an 'XLR to XLR' cable. Simply plug straight in to your device and the microphone will work.

You will need a standard 3-pin XLR cable, as well as an audio-interface like the iCON Duo 44 which will act as the 'connector' to your computer for recording. You can then use the microphone to record to a Digital Audio Workstation (DAW) like Cubase, Harrison Mixbus 32C or Pro Tools.

Equally, you can use a device such as iCON Pro Audio's 'Live Console', specifically designed for live streaming. Find out more here; <https://iconproaudio.com/product/live-console/>

The switches

The low cut and high boost switches at the rear of the microphone can be switched on and off using your finger.



The window below the switches will indicate the EQ change. For example, when the switches are both off, a straight line will display. When the low cut is switched on, the window will display a low cut shelf (a slope veering to zero on the left). When the high boost switch is on, the EQ setting will display in the window with a 'bell' shape, indicating a 'boost' in the upper-mid frequencies.

The bass roll off is at 400Hz and the mid-high frequency boost is at 2KHz - 6KHz



Specifications

Frequency response-vary axis



No EQ

Low Cut



Mid-High Boost

Frequency range	50 Hz to 15 kHz
Polar pattern	cardioid
Sensitivity (dB re iV/Pa)	54.5dbv/pa
Output impedance	150 Ω
Output connector	3-pin XLR male
Dimension	55mm X 55mm X 130mm
Weight	0.563kg

Services

If your DynaMic needs servicing, follow these instructions.

Check our online Help Center at <http://support.iconproaudio.com>, for information, knowledge, and downloads

such as:

1. FAQ
2. Download
3. Product Registration
4. Video Tutorials

Very often you will find solutions on these pages. If you don't find a solution, create a support ticket at our online Help Center at the link below, and our technical support team will assist you as soon as we can.

Navigate to <http://support.iconproaudio.com> and then sign in to submit a ticket. Once you have submitted an inquiry ticket, our support team will assist you to resolve the problem with your ICON ProAudio device as soon as possible.

To send defective products for service:

1. Ensure the problem is not related to operation error or external system devices.
2. Keep this owner's manual. We don't need it to repair the unit.
3. Pack the unit in its original packaging including end card and box. This is very important. If you have lost the packaging, please make sure you have packed the unit properly. ICON is not responsible for any damage that occurs due to non-factory packing.
4. Ship to the ICON tech support center or the local return authorization. See our service centers and distributor service points at the link below:

If you are located in US

Send the product to:

North America

Mixware, LLC - U.S. Distributor

3086 W. POST RD.

LAS VEGAS NV 89118

Tel.: (818) 578 4030

Contact: www.mixware.net/help

If you are located in Europe

Send the product to:

Sound Service GmbH

European Headquarter Moriz-

Seeler-Straße3 D-12489 Berlin

Telephone: +49 (0)30 707 130-0

Fax: +49 (0)30 707 130-189

E-Mail: info@sound-service.eu

If you are located in Hong Kong

Send the product to:

ASIA OFFICE:

Unit F, 15/F., Fu Cheung Centre,

No. 5-7 Wong Chuk Yueng Street,

Fotan,

Sha Tin, N.T., Hong Kong.

Tel: (852) 2398 2286

Fax: (852) 2789 3947

Email: info.asia@icon-global.com

5. For additional update information please visit our website at:

www.iconproaudio.com



Twitter



www.twitter.com/iconproaudio

Instagram



www.instagram.com/iconproaudio

Facebook



www.facebook.com/iconproaudio

Youtube



www.youtube.com/iconproaudio

Website



www.iconproaudio.com

Support



support.iconproaudio.com


Dashboard



iconproaudio.com/dashboard/

www.iconproaudio.com

Documents / Resources

	<p>ICON PD3V100 DynaMic Dynamic Microphone [pdf] Instruction Manual PD3V100 DynaMic Dynamic Microphone, PD3V100, DynaMic Dynamic Microphone, Dynamic Microphone, Microphone</p>
---	---

References

- [🌐 Global | Leading UK media company offering radio and outdoor advertising](#)
- [🌐 Domain im Kundenauftrag registriert](#)
- [📷 Icon Pro Audio \(@iconproaudio\) • Instagram photos and videos](#)
- [🌐 Help - Mixware](#)