




ICY BOX IB-DK4060-CPD Mobile USB Type C Notebook Docking Station User Manual


[Home](#) » [ICY BOX](#) » ICY BOX IB-DK4060-CPD Mobile USB Type C Notebook Docking Station User Manual 



ICY BOX®



**IB-DK4060-CPD Mobile
USB Type C Notebook Docking Station
User Manual**



Contents


1 IB-DK4060-CPD Mobile USB Type C Notebook Docking Station

2 Documents / Resources

IB-DK4060-CPD Mobile USB Type C Notebook Docking Station







1x




1x




i



1




2



Video matrix design (Host PC = USB Type-C® DP Alt Mode, DP 1.2), maximum resolutions (Windows)						
	Inputs (plug-in)			Output		
Number of displays	HDMI® 1	HDMI® 2	DP	HDMI® 1	HDMI® 2	DP
Triple video output*	✓	✓	✓	1920×1080@60 Hz	1920×1080@60 Hz	Only 2 possible
Dual video output	✓	✓		1920×1080@60 Hz	1920×1080@60 Hz	
		✓	✓		1920×1080@60 Hz	1920×1080@60 Hz
	✓		✓	1920×1080@60 Hz		1920×1080@60 Hz
Single video output	✓			3840×2160@30 Hz		
		✓			3840×2160@30 Hz	
		✓			3840×2160@30 Hz	

Video matrix design (Host PC = USB Type-C® DP Alt Mode, DP 1.4), maximum resolutions (Windows)						
	Inputs (plug-in)			Output		
Number of displays	HDMI® 1	HDMI® 2	DP	HDMI® 1	HDMI® 2	DP
Triple video output*	✓	✓	✓	3840×2160@60 Hz	3840×2160@30 Hz	3840×2160@30 Hz
Dual video output	✓	✓		3840×2160@60 Hz	3840×2160@60 Hz	
		✓	✓		3840×2160@60 Hz	3840×2160@60 Hz
	✓		✓	3840×2160@60 Hz		3840×2160@60 Hz
Single video output	✓			7680×4320@30 Hz		
		✓			7680×4320@30 Hz	
			✓			7680×4320@30 Hz

Video matrix design (Host PC = USB Type-C® DP Alt Mode), maximum resolutions (macOS)						
	Inputs (plug-in)			Output		
Number of displays	HDMI® 1	HDMI® 2	DP	HDMI® 1	HDMI® 2	DP
Triple video output *	✓	✓	✓	3840×2160@60 Hz only mirrored (SST)		



www.icybox.de

Legacy USB standards	Current USB standards	Data transfer rate
USB 3.0 = USB 3.1 (Gen 1)	= USB 3.2 Gen 1	= 5 Gbit/s
USB 3.1 = USB 3.1 (Gen 2)	= USB 3.2 Gen 2	= 10 Gbit/s
USB 3.2 (Gen 2×2)	= USB 3.2 Gen 2×2	= 20 Gbit/s



Our products and packaging can be recycled, do not throw them away Find where to deposit them on the site

www.quefairedemesdechets.fr


© Copyright 2023 by RaidSonic Technology GmbH. All Rights Reserved.

The information contained in this manual is believed to be accurate and reliable. Raid-Sonic Technology GmbH assumes no responsibility for any errors contained in this manual. RaidSonic Technology GmbH reserves the right

to make changes in the specifications and/or design of the above-mentioned product without prior notice. The diagrams contained in this manual may also not fully represent the product that you are using and are there for illustration purposes only. RaidSonic Technology GmbH assumes no responsibility for any differences between the product mentioned in this manual and the product you may have. DisplayLink® is the registered trademark of DisplayLink Corp. in the EU, the US, and other countries DisplayPort™, and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. The terms HDMI® and HDMI® High-Definition Multimedia Interface, and the HDMI® logo are trademarks or registered trademarks of HDMI® LA, Inc. in the United States and other countries. Apple and macOS are registered trademarks of Apple Computer Inc. Microsoft, Windows and the Windows logo are registered trademarks of Microsoft Corporation.



Documents / Resources

	ICY BOX IB-DK4060-CPD Mobile USB Type C Notebook Docking Station [pdf] User Manual IB-DK4060-CPD, IB-DK4060-CPD Mobile USB Type C Notebook Docking Station, Mobile USB Type C Notebook Docking Station, USB Type C Notebook Docking Station, Notebook Docking Station, Docking Station
---	---