

ideal lux Style Ap Sensor Bianco User Guide

Home » ideal lux » ideal lux Style Ap Sensor Bianco User Guide 🖺



Contents

- 1 ideal lux Style Ap Sensor
- **2 Product Information**
- **3 Product Usage Instructions**
- 4 General info
- 5 Technical info
- 6 Source info
- 7 Documents / Resources
 - 7.1 References

ideal lux.

ideal lux Style Ap Sensor Bianco



Style	rev. 21-02-2023
General Info	Outdoor – Floor
Description	Outdoor ground mounted bollard with integrated LED sources and direct light emission
Ean Item	8021696209906
Installation Guarantee	5 years
Gross Weight	2.11 kg
Volume	0.023861 m3
Net Weight	
Insulation Class	
Protection Index	
Compliance	
Operating Temperature	
Dimmer	
Power Output	
Power Supply	
Source Info	IDEAL LUX s.r.l. Via Taglio Destro, 32, 30035 Mirano (Venezia) Tel +39 041 5790500 Fax +39 041 8872349 E-mail info@ideal-lux.com Website www.ideal-lux.com

Product Usage Instructions

To use the product:

- 1. Choose a suitable outdoor location for the bollard.
- 2. Ensure the ground is level and stable.
- 3. Position the bollard on the ground and secure it using the provided installation method.
- 4. Connect the power supply to the bollard.
- 5. Turn on the power.

Note: Please refer to the complete user manual for detailed installation instructions and safety guidelines.

General info

Outdoor - Floor

Outdoor ground mounted bollard with integrated LED sources and direct light emission

- Ean 8021696209906
- Item STYLE PT ANTRACITE 4000K

- Installation Floor
- Guarantee 5 years
- Gross weight 2.11 kg
- Volume 0.023861 m3

Technical info

- Net weight 1.67 kg
- Insulation class
- Protection index IP54
- Compliance CE
- Operating temperature -15° ~ +45 °C
- Dimmer Non-dimmable, On-Off
- Power output 220-240 V AC 50/60 Hz
- Power supply In-built, included Replaceable (by qualified operators only), electronic

Source info

- Integrated source Integrated LED module
- Repleaceable source No
- Power LED 9 W
- Emission Direct
- Max consuption max 9 W
- Features LED LED SMD CCT 4000 K
- Duration LED (t. 25°c) 30000 h CRI > 80
- Light beam 120°
- Light beam flux 920 lm
- Useful light flux 770 lm
- Standby power < 0.50 W

IDEAL LUX s.r.l.

Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | Fax +39 041 8872349 | E-mail info@ideal-lux.com
www.ideal-lux.com

Documents / Resources



ideal lux Style Ap Sensor Bianco [pdf] User Guide Style Ap Sensor Bianco, Style Ap, Sensor Bianco, Bianco

References

- Fragrant Bar Soap, Body Wash and Shower Gel from LUX | LUX India
- Ideal-Lux | Home IT

Manuals+,