



IDS 20-Key Wireless RF Remote Controller Instructions

[Home](#) » [IDS](#) » **IDS 20-Key Wireless RF Remote Controller Instructions**

IDS 20-Key Wireless RF Remote Controller



Contents

1 Product Specifications

1.1 Summarization

1.2 Technical parameters

2 Interface Specifications

3 Direction for use

4 Typical application

5 Documents / Resources

6 Related Posts

Product Specifications


Summarization

The wireless 20-key controller adopts a control chip to control various lamps with LED as the light source, Is used to control a variety of led lamps as the light source, For instance, point source of light, flexible light strip, wall washer lamp, glass curtain wall light and so on; With competitive price, easy wiring, simple to use etc.

Technical parameters

- Working temperature -20-60°C
- Supply voltage 3V
- Output 1channels
- Connection method: Common anode
- Net weight 50g
- Gross weight 70g
- Static power consumption <1W
- Output current <2A

Interface Specifications






1. INPUT: DC Power supply Vcc is positive electrode GND is negative electrode
2. OUTPUT: Load light strip Vcc is positive electrode R,G,B is negative electrode
3. The picture on the right is the remote control panel

Direction for use

1. Connect the load wire at first, following by the power wire; Please ensure short circuit cannot occur between connecting wire before you turn on the power;
2. The function of each key is shown in the table below (arranged according to the position of the key):
3. When the controller is powered on, press and hold the red switch key for 3 seconds, the remote control and the controller are paired.

Static colors (8 in total)	Dynamic mode (6 in total)	Turn off the load output	Dimming and speed control keys
Static red, Green, Blue	Automatic mode	Red on/off	White and black brightness plus and minus keys
Static white, orange yellow	Three-color jumpy changing , three-color gradual changing	Black pause button	SPEED speed plus and minus keys
Static cyan, purple	Seven-color jump, 7-color gradual changing		
Static yellow	Static light blue	Static pink	Colorful gradual changing
Static light yellow	Static light blue	Static purple	Red, green and blue three-color jumpy changing

Typical application



FCC STATEMENT:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
This device may not cause harmful interference, and This device must accept any interference received, including interference that may cause undesired operation.

Warning: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:


- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

— Consult the dealer or an experienced radio/TV technician for help.

RF warning statement:

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.

Documents / Resources



[IDS 20-Key Wireless RF Remote Controller](#) [pdf] Instructions
GB-DT06ARF, GBDT06ARF, 2A6EP-GB-DT06ARF, 2A6EPGBDT06ARF, 20-Key Wireless Cont
roller, 20-Key Wireless RF Remote Controller