

# Inhand Networks IR302 Cellular Modem Owner's Manual

Home » InHand Networks » Inhand Networks IR302 Cellular Modem Owner's Manual

Inhand Networks IR302 Cellular Modem



Inhand Networks IR302 is a cellular to Ethernet modem that can provide the eGauge unit and related supported equipment with internet access on a 4G LTE T-Mobile network.

A compatible T-Mobile data plan can be purchased through eGauge Systems. eGauge cannot guarantee support for data plans from other parties. eGauge supplied data plans are for use with eGauge meters and not third party products, line suspension or termination will occur if there is excessive data usage from third-party devices or general internet usage.

Modems sold by eGauge systems are pre-configured for the T-Mobile service provided by eGauge and utilize InHand Networks device manager for remote troubleshooting and customer assistance.

Metered (not unlimited) data plans can accrue charges for data overages. eGauge recommends against using metered data plans without extensive testing for data usage. Data usage is not fully predictable and will greatly vary with interface access. See **this article** for additional information on data usage.

If installing in an underground or high electrical noise area, a custom antenna solution or separate mounting location for the cellular moder may be necessary in order to have sufficient cellular signal.

## **Contents**

- 1 Specifications
  - 1.1 Communication
  - 1.2 Environmental and Operational
  - 1.3 Physical
- 2 Hardware included
- 3 Assembly/installation information
  - 3.1 Detailed SIM card install instructions
- 4 Software configuration and troubleshooting
  - 4.1 LED indicator description
  - **4.2 Factory Reset**
  - 4.3 Configuration steps
  - 4.4 Additional diagnostics and

troubleshooting

- **5 Documents**
- **6 Related Information**
- 7 Documents / Resources
  - 7.1 References
- **8 Related Posts**

## **Specifications**

# Full specs (datasheet PDF)

#### Communication

- T-Mobile LTE CAT4 (LTE-FDD Band B2/B4/B5/B12/B13/B14/B66/B71)
- 2x LAN ports

#### **Environmental and Operational**

- Operating Temperature: -20 ~ 70°C
- Humidity: 5 ~ 95% relative humidity (noncondensing)

• IP30 protection

• Input voltage: 9-36Vdc

• Consumption: 100-120mA @ 12V (peak 190mA @ 12.0V)

# **Physical**

• 4G cellular connections: SMA x2

• 90 x 90 x 25 mm

• DIN-rail mountable

## Hardware included

- Inhand Networks IR302 box kit
  - 1x IR302 modem
  - 1x DIN rail clip
  - AC power adapter
  - 1x CAT5 cable
- · Cellular router accessory Kit
  - 2x Rubber O-Ring
  - 2x Extension Cable (short, SMA)
  - 2x rubber stick antennas

# Assembly/installation information



The cellular antennas must be located on the outside of any enclosure. Even plastic enclosures can degrade or block a cellular signal.

1. If the modem is ordered with a data plan, an activation instruction sheet will be included with a SIM card. Insert the SIM card into the modem as shown above, ensuring the SIM card is in the "SIM 1" position. Follow the data plan activation instructions provided to activate the data plan.

- 2. Connect the DIN rail to either the left or right side of the modem using the included bracket and screws.
- 3. Locate a suitable location to install the cell modem. If installing in a Powered Enclosure Kit (PEK), mount on the DIN rail.
- 4. If using the PEK or other suitable enclosure, use the 2x short SMA extension cables to connect from the Cellular1 and Cellular2 connectors on the modem to create a bulkhead connector on the enclosure.
- 5. Connect the antennas to the bulkhead connectors on the enclosure, or directly to the cell modem if not using an enclosure.
- 6. Connect the power cord to the cellular modem.
- 7. Connect the eGauge meter via Ethernet to a LAN port on the modem.

#### **Detailed SIM card install instructions**

1. Use the SIM card remover tool to eject the SIM card tray.



2. Remove the SIM card from the SIM card holder. The SIM card has 2 outer shells that must be removed prior to inserting into the holder.



3. Insert the SIM card (with no outer shells) into the lower (SIM 1) position of the SIM card holder tray and insert back into the IR302 modem.



SIM card in holder before Inserted

# Software configuration and troubleshooting

Modems provided by eGauge are pre-configured to work on the T-Mobile network using data plans provided by eGauge Systems.

The default DHCP range of IR302 modems provided by eGauge is 192.168.2.2 to 192.168.2.100. Devices may be given static IPs in the range of 192.168.2.101 to 192.168.2.254. A particular static IP must not be used on more than one device on a single modem.

If the modem is not functioning and configuration may have been modified after shipment, perform a factory reset and upload the eGauge-specific cellular configuration if using a dataplan provided by eGauge Systems.

# LED indicator description

The modem has a "Signal" LED with 3 different colors to indicate the signal strength level:

**Red:** Signal strength 0-10 (Signal strength is weak, please check antenna and the signal strength of current location).

Yellow: Signal strength 11-20 (signal strength is adequate, and the modem can be used).

Green: Signal strength 21-30 (signal strong).

The other LED behavior is described below:

Power (Red)	Status (Green)	Cellular (Yellow)	Description
Off	Off	Off	Powered Off
On	Off	Off	System failure
On	On	Off	The module or SIM card i s not recognized
On	On	Blinking	Dialing (Connection attem pt is being made)
On	On	On	Dialing Succeeded (A con nection to the provider wa s made. This does not gu arantee the SIM card data plan is active)
On	Blinking	On	Software Upgrade in progress
On	Blinking, then On	Off	A reset is being performe d

# **Factory Reset**

1. Power on the modem and allow it at least 60 seconds to fully start running. Locate the Reset button next to the SIM card tray,




- 2. Use a push-pin or paperclip to hold down the "Reset" button on the side of the modem for 10 seconds. The status LED will turn off and back on again. Release the reset button.
- 3. Push the reset button again for 2 seconds and release. The Status LED should alternate on and off.
- 4. The LEDs will all turn off, and the modem will restart with the normal start-up LED sequence.
- 5. Use the configuration steps below to reconfigure the modem for T-Mobile plans provided by eGauge Systems.

# **Configuration steps**

Modems provided by eGauge are pre-configured to work on the T-Mobile network using data plans provided by eGauge Systems. These steps are only needed if the modem was factory reset or configuration was modified.

The APN for T-Mobile plans provided by eGauge is lot.tmowholesale

- 1. Download the IR302 eGauge configuration for T-Mobile here.
- 2. Connect a computer to a LAN port of the cell modem.
- 3. Open a web browser to <a href="http://192.168.2.1/">http://192.168.2.1/</a> and log in with username adm and password 123456 .



- 4. The modem may prompt to opt-in to a User Experience Program from InHand. You may click "CANCEL" on this. It may be toggled on or off later in Services -> User Experience Plan.
- 5. Navigate to System -> Config Management.



6. Under "Router Configuration", click the "Browse" button and choose the file downloaded earlier.



7. Press "Import", choose "OK" when it asks if you are sure, and finally press "Reboot" when it prompts to be rebooted.

# Import configuration successfully. The system needs to be rebooted!

Reboot

## Additional diagnostics and troubleshooting

The following pages provide information and diagnostics that can be helpful in identifying poor signal or other issues. Connect a computer to a LAN port of the modem and visit <a href="http://192.168.2.1/">http://192.168.2.1/</a> logging in with username adm and password 123456. If this does not work, perform a factory reset and initial configuration as described in the above sections.

Page location	Description	
Tools -> Ping	Have the modem ping an external IP or domain.	
Status -> Modem	Contains signal level, RSSI, SIM card number, network type and other modem-related information	
Status -> Network Connections	Dialup (cellular) IP information from cellular provider	
Status -> Device List	DHCP list of connected devices to the LAN ports	
Status -> Log	Raw log from modem	

• The APN for plans provided by eGauge with the IR302 modem is iot.tmowholesale.

# **Documents**

- · OEM owner's manual
- Certification documents and other documents may be found on manufacturers website: https://www.inhandnetworks.com/

## **Related Information**

- Inhand Networks IR615 (previously offered modem)
- Multitech MTE-LAT6 (previously offered modem)

Revision #15 Created 26 April 2022 17:05:08 by aaron Updated 13 October 2022 20:22:43 by aaron

## **Documents / Resources**



<u>Inhand Networks IR302 Cellular Modem</u> [pdf] Owner's Manual IR302 Cellular Modem, IR302, Cellular Modem, Modem

# References

• Region Fig. | Cellular Routers & Gateways | IoT Solutions | 5G | InHand Networks

Manuals+,