





InTemp CX5500 Cellular IoT Gateway Owner's Manual

Home » InTemp » InTemp CX5500 Cellular IoT Gateway Owner's Manual 🖺

Contents

- 1 InTemp CX5500 Cellular IoT Gateway
- **2 Product Usage Instructions**
- 3 Features
- 4 FAQS
- 5 Documents / Resources
 - **5.1 References**



InTemp CX5500 Cellular IoT Gateway



Product Usage Instructions

InTemp Cellular IoT Gateway

Bluetooth connection to data loggers for cold chain cloud automation services

The CX5500 Gateway automatically downloads data from in-range InTemp CX loggers and uploads it to the InTempConnect cloud platform via a cellular connection, enabling automatic alarm notifications, compliance report automation, and remote monitoring capabilities.

Important Information

This product is only available to US customers. If you are outside of the US, please consider the CX5001 WiFi/Ethernet Gateway. Requirements:

- CX Gateway Annual Cellular Data Plan [(SP1-CX5500): \$200 per Gateway/per year, added automatically to purchase]
- InTempConnect cloud account, at least one CX data logger, a compatible mobile device, and InTemp mobile app (for configuration.



Features

- Automates logger management (downloading and configuring) to reduce manual, on-site activities
- Notifies you of temperature, humidity, and or excursion of low device battery in real time via text message and
 or email Cellular data connectivity to upload your logger's data directly to the InTempConnect cloud platform
- Removes the need to add an external device to your organization's network
- · Decreases the risk of product loss
- Reduces time spent on regulatory compliance activities

InTemp Cellular IoT Gateway (CX5500) Specifications

- Transmission Range Approximately 30.5 m (100 ft) line-of-sight
- Wireless Data Standard Bluetooth 4.2 (BLE)
- Connectivity Cellular Cat 1 LTE with 2G/3G fallback
- Power Source AC adapter
- **Dimensions** 12.7 x 12.7 x 2.99 cm (5.0 x 5.0 x 1.18 inches)
- External Antennae: 3.81 x 19.58 cm (1.5 x 7.71 inches)
- Weight 680 g (24 oz)

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

• 1-508-743-3309 (US & International)

+45 6154 5745 (EMEA)

Technical Support (8am to 5pm ET, Monday through Friday)

- Email InTempHelp@onsetcomp.com
- Contact Support online <u>www.onsetcomp.com/intemp/contact/support</u>

Onset Computer Corporation 470 MacArthur Boulevard Bourne, MA 02532

- www.onsetcomp.com/intemp
- Onset®, InTemp®, InTempConnect® and other names of Onset products referenced herein are trademarks or registered trademarks of Onset Computer Corporation. ® 1995-2025 Onset Computer Corporation. All rights reserved.
- www.onsetcomp.com/intemp

FAQS

Q: Can I use the CX5500 Gateway outside of the US?

A: No, this product is only available to US customers. For international use, consider the CX5001 WiFi/Ethernet Gateway.

Q: How do I receive alarm notifications?

A: The Gateway notifies you of temperature, humidity, low device battery, or excursion events in real-time via text message or email.

Q: What is the purpose of the external antennae?

A: The external antennae improve cellular connectivity for uploading data to the InTempConnect cloud platform.

Documents / Resources



InTemp CX5500 InTemp Cellular IoT Gateway [pdf] Owner's Manual CX5500 InTemp Cellular IoT Gateway, CX5500, InTemp Cellular IoT Gateway, Cellular IoT Gateway, IoT Gateway

References

- 0 IoT Monitoring Solutions for Cold Chain & Healthcare Onset's InTemp Monitoring Solutions
- 0 Technical Support | InTemp Monitoring Solutions
- User Manual

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.