




Home » Intesis » Intesis IN701KNX3K00000 KNX TP to Modbus TCP and RTU Server Application Installation Guide ™

Contents [hide]

- 1 Intesis IN701KNX3K00000 KNX TP to Modbus TCP and RTU Server Application
- 2 Product Information
- 3 Features and benefits
- 4 Technical Data
- 5 Certifications and Standards
- 6 Use Case
- 7 Documents / Resources
 - 7.1 References

Intesis®

Intesis IN701KNX3K00000 KNX TP to Modbus TCP and RTU Server Application



Specifications

- Item Number: IN701KNX3K00000
- Integrates KNX devices with Modbus BMS or Modbus TCP/RTU controller
- Supports KNX TP devices
- Supports Modbus RTU and Modbus TCP protocols
- Commissioning-friendly with Intesis MAPS Templates

Product Information

KNX TP to Modbus TCP & RTU Server Application

Item number: IN701KNX3K00000

Integrate any KNX device or install on with a Modbus BMS or any Modbus TCP or Modbus RTU controller. This integration aims to make KNX communica on objects and resources accessible from a Modbus-based control system or device as if they were a part of the Modbus system and vice versa.

Features and benefits

• Up to six concurrent Modbus TCP clients supported

The gateway supports up to six simultaneous Modbus TCP clients.

Easy integra on with Intesis MAPS

The integra on process is quickly and easily managed using the Intesis MAPS configuration tool.

Configura on tool and gateway automa c updates

Both the Intesis MAPS configura on tool and the gateway's firmware can receive automatic updates.

Control up to 3000 KNX communica on objects

Up to 3000 KNX communica on objects can be controlled by the gateway.

Support for both Modbus RTU and Modbus TCP

The gateway supports both Modbus RTU and Modbus TCP protocols.

• Commissioning-friendly approach with Intesis MAPS

Templates can be imported and reused as open as needed, significantly reducing commissioning me.

• Support for KNX TP devices

The gateway supports KNX TP (twisted pair) devices.

Technical Data

KNX TP to Modbus TCP & RTU Server Application


General	
Net Width (mm)	88
Net Height (mm)	90
Net Depth (mm)	58
Net Weight (g)	194
Packed Width (mm)	127
Packed Height (mm)	86
Packed Depth (mm)	140
Packed Weight (g)	356
Operating Temperatur e °C Min	-10
Operating Temperatur e °C Max	60
Storage Temperature ° C Min	-30
Storage Temperature ° C Max	60
Power Consumption (W)	1.7

Input Voltage (V)	For DC: 9 36 VDC, Max: 180 mA, 1.7 WFor AC: 24 VAC ±10 %, 50-60 Hz, Max: 70 mA, 1.7 W Recommended volta ge: 24 VDC, Max: 70 mA
Power Connector	3-pole
Configuration	Intesis MAPS
Capacity	Up to 3000 points.
Installation Conditions	This gateway is designed to be mounted inside an enclosur e. If the unit is mounted outside an enclosure, precautions s hould always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making a djustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
Content of Delivery	Intesis Gateway, Installation Manual, USB Configuration ca ble.


General		
Not Included (in delive ry)	Power supply not included.	
Mounting	DIN rail mount (bracket included), Wall mount	
Housing Materials	Plastic	
Warranty (years)	3 years	
Packaging Material	Cardboard	
Identification and Status		
Product ID	IN701KNX3K00000_MBS_KNX	
Country of Origin	Spain	

HS Code	8517620000	
Export Control Classi fication Number (ECC N)	EAR99	
Physical Features		
Connectors / Input / Output	Power supply, KNX, Ethernet, Console port USB Mini-B type, USB storage, EIA-232, EIA-485.	
LED Indicators	Gateway and communication status.	
DIP & Rotary Switches	EIA-485 serial port configuration.	
Battery Description	Manganese Dioxide Lithium button battery.	
Certifications and Standards		
ETIM Classification	EC001604	
WEEE Category	IT and telecommunications equipment	

Use Case



Integration example



FAQ

- Q: Does the gateway support both Modbus RTU and Modbus TCP protocols?
 - A: Yes, the gateway supports both Modbus RTU and Modbus TCP protocols.
- Q: What is the warranty period for the product?
 - A: The product comes with a 3-year warranty.

Documents / Resources



Intesis IN701KNX3K00000 KNX TP to Modbus TCP and RTU Server App lication [pdf] Installation Guide

IN701KNX3K00000, IN701KNX3K00000 KNX TP to Modbus TCP and RT U Server Application, IN701KNX3K00000, KNX TP to Modbus TCP and R TU Server Application, TCP and RTU Server Application, RTU Server Application, Application

References

- User Manual
- Intesis
- Application, IN701KNX3K00000, IN701KNX3K00000 KNX TP to Modbus TCP and RTU Server Application Intesis, KNX TP to Modbus TCP and RTU Server Application, RTU Server Application, TCP and RTU Server Application

Leave a comment

Your email address will not be published. Required fields are marked *

Comment *	
Name	
Name	
Email	
Website	
Save my name, email, and website in this browser for the next time I comme	ent.
Post Comment	
Search:	
e.g. whirlpool wrf535swhz	Search

Manuals+ | Upload | Deep Search | Privacy Policy | @manuals.plus | YouTube

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.